

Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

VersaLink® B7000 Series Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to **www.connectkey.com**.



SYSTEM SPECIFICATIONS	VERSALINK® B7025	VERSALINK® B7030 VERSALINK® B7035		
One-sided Speed ¹				
8.5 x 11 in./A4/210 x 297 mm	Up to 25 ppm (pages per minute) long edge feed (LEF)	Up to 30 ppm LEF Up to 35 ppm LEF		
8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm	Up to 16 ppm Up to 14 ppm	Up to 20 ppm Up to 17 ppm	Up to 22 ppm Up to 19 ppm	
Two-sided Speed ¹				
8.5 x 11 in./A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm	Up to 19 ppm LEF Up to 10 ppm Up to 9 ppm	Up to 23 ppm LEF Up to 12 ppm Up to 11 ppm	Up to 26 ppm LEF Up to 14 ppm Up to 13 ppm	
Monthly Duty Cycle ²	Up to 107,000 pages/month ¹	p to 107,000 pages/month ¹ Up to 129,000 pages/month ¹ Up to 153,00		
Recommended Average Monthly Print Volume ³	Up to 13,000 pages		Up to 17,000 pages	
Hard Drive	320 GB HDD (Optional on Desktop model)			
Processor	1.05 GHz Dual-Core			
Memory	2 GB			
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair			

Detailed Specifications Page 1 of 13

Controller Features	Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support				
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian				
DEVICE SPECIFICATIONS					
ELECTRICAL REQUIREMENTS					
North America	Voltage: 110-127 V -10	%/+6%			
	Frequency: 50/60 Hz +/-	3%,12A			
Europe and Other Geographies	Voltage: 220-240 V +/- 1	10%			
	Frequency: 50 Hz +/-3%	, 8A			
POWER CONSUMPTION					
Printing ⁴	25 ppm = 1.1 kWh; 30 p	pm = 1.5 kWh; 35 ppm = 1.7	kWh		
Standby Mode ⁴	110V: 83 watts or less; F	or 220V: 86 watts or less			
Sleep Mode ⁴	0.81 Watts or less				
OPERATING ENVIRONMENT					
Required Temperature Range (Storage)	32° to 95° F (0° to 35° C)	32° to 95° F (0° to 35° C)			
Required Temperature Range (Operating)	50 to 90° F (10 to 32° C)				
Required Relative Humidity	10% to 85%				
Sound Power Levels	Printing: 6.75 B(A) or less				
	• 25 ppm = 6.54 B(A); 30 ppm = 6.70 B(A); 35 ppm = 6.75 B(A)				
	Standby: 4.10 B(A) or less				
	• 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A); 35 ppm = 4.10 B(A)				
		Full System (including Finisher and HCF)			
	Printing: 25 ppm = 7.22 B(A); 30 ppm = 7.37 B(A); 35 ppm = 7.46 B(A)				
Count Durant Laurela	Standby: 25 ppm = 6.54 B(A); 30 ppm = 6.70 B(A); 35 ppm = 6.75 B(A)				
Sound Pressure Levels	Printing: 50.0 dB(A)	; 30 ppm = 49.7 dB(A); 35 pp	om - EO O dB(A)		
	Standby: 16.4 dB(A)	, 30 ppm = 49.7 db(A), 33 pp	JIII = 30.0 UB(A)		
		; 30 ppm = 16.4 dB(A); 35 pp	om = 16 0 dB(A)		
	Full System (including I		10.0 45(11)		
		dB(A); 30 ppm = 53.6 dB(A);	35 ppm = 54.0 dB(A)		
	Standby: 25 ppm = 16.0	dB(A); 30 ppm = 16.0 dB(A)	; 35 ppm = 15.7 dB(A)		
Boot Time (from Off to UI Ready)	As fast as 98 seconds				
Warm-up Time (from Sleep to UI Ready)	As fast as 12 seconds				
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT	
Base Unit	23.23 in./590 mm	26.41 in./670.8 mm	30.23 in./767.9 mm	113.1 lbs./51.3 kg	
Base Unit with Single Tray with Stand Module	24.24 in./615.7 mm	26.41 in./670.8 mm	44.04 in./1118.6 mm	168.21 lbs./75.8 kg	
Base Unit with High Capacity Tandem Tray Unit	24.24 in./615.7 mm	26.41 in./670.8 mm	44.04 in./1118.6 mm	193.35 lbs./87.2 kg	
	1			1	

Detailed Specifications Page 2 of 13

Base Unit with Three Tray Module and Office Finisher (with Booklet Maker)	45.22 in./1148.6 mm	26.7 in./678.6 mm		44.04 in./1	118.6 mm	273.81 lbs./124.2 kg
Base Unit with Three Tray Module and Office Finisher LX (with Booklet Maker)	47.0 in./1194.0 mm	26.8 in./681.8 mm		44.04 in./1	118.6 mm	249.12 lbs./113.0 kg
CERTIFICATIONS						
To view the latest list of certification	s. go to www.xerox.com/(OfficeCertific	ations			
PRINT	VERSALINK® B7025					
First-Print-Out Time	As fast as 10.4 seconds		s fast as 9.1 s			
Print Resolution	Up to 1200 x 1200 dpi				I	
Page Description Languages	PCL® 5e, 6					
l age 2 coonpaion canguages	PDF					
	XPS					
	TIFF					
	JPEG					
	HP-GL					
	Adobe® PostScript® 3™ ((Ontional)				
Maximum Print Area	· · · · · · · · · · · · · · · · · · ·	•	from Side and	d Trail edaes of	paper	
Print Features	4 mm from Lead edge of paper, 2 mm from Side and Trail edges of paper Application Defaults					
	Banner Pages Enable/Disable					
	Bi-directional Real-time S					
	Booklet Layout	cacas				
	Draft Mode					
	Finishing (requires finishing)					
	Fit to New Paper Size					
	Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)					
	Job Monitoring (Client or Local User Interface)					
	LAN Fax (requires Fax Kit)					
	N-up Page Layout (up to 16 pages per sheet)					
	Paper Selection by Attribute					
	Personal Print					
	Print Around Enable/Disable					
	Print from USB					
	Sample Set					
	Saved Job					
	Scaling					
	Secure Print					
	Skip Blank Pages					
	Special Pages (exception	page program	nmina: covers	inserts, except	ions pages)	
	Store and Recall Driver Se		J			
	Stored Jobs Deletion	5				
	Two-sided Printing (as de	efault)				
	Watermark (predefined a					
	Earth Smart Driver Setting					
Print from USB	Allows walk-up printing fr	-	SB port			
	Supports direct printing f		•	SB port		
	Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A					

Detailed Specifications Page 3 of 13

Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 Mac OS® version 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX®			
	HP-UX® Oracle® Solaris SUSE® SAP® Note: For information about suppor Downloads page and specify your d	ted versions for the above operating s evice at www.support.xerox.com .	ystems, please visit our Drivers &	
Fonts	PostScript fonts: 136 PCL fonts: 83			
Xerox® Global Print Driver®	devices from a single driver. It provide	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.		
Xerox® Pull Print Driver	Print environment. Uses a single que across a broad range of printing ass	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.		
СОРУ	VERSALINK® B7025	VERSALINK® B7030	VERSALINK® B7035	
Document Scanner	110-sheet Single Pass Duplex Auton	natic Document Feeder (DADF)	•	
Document Scanner Size	· ·	Platen: Up to 13.1 x 17.2 in./332.0 x 437 mm DADF: Up to 11.7 x 17 in./297 x 431.8 mm		
Simplex Copy Speed	Up to 25 cpm (copies per minute) 8.5 x 11 in.	Up to 30 cpm (copies per minute) 8.5 x 11 in.	Up to 35 cpm (copies per minute) 8.5 x 11 in.	
	Up to 25 cpm A4 (210 x 297 mm)	Up to 30 cpm A4 (210 x 297 mm)	Up to 35 cpm A4 (210 x 297 mm)	
Duplex Copy Speed	Up to 20 cpm (copies per minute) 8.5 x 11 in.	Up to 20 cpm (copies per minute) 8.5 x 11 in.	Up to 20 cpm (copies per minute) 8.5 x 11 in.	
<u></u>	<u> </u>	Up to 20 cpm A4 (210 x 297 mm) Up to 20 cpm A4 (210 x 297 mm) Up to 20 cpm A4 (210 x 297 mm)		
First-Copy-Out Time	As fast as 6.8 seconds	As fast as 5.4 seconds	As fast as 5.4 seconds	
Sides (input: output)		1:1, 1:2, 2:2 and 2:1		
Quantity		1 to 999		
Resolution (max.)		Up to 600 x 600 dpi		
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments			
Concurrency	Concurrent scanning and printing			

Detailed Specifications Page 4 of 13

Copy Features	Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping)*
	Automatic Background Suppression
	Book Copying with Center Erase
	Booklet Copying*
	Collation
	Darkness Control
	Edge Erase
	Front Cover
	ID Card Copy
	Image Enhancement
	Image Shift
	Lighten/Darken
	N-up
	Reduce/Enlarge 25% to 400%
	Original Orientation
	Original Size
	Original Type
	Page Layout
	Sample Copy
	Saturation
	Sharpness
	*Requires HDD/Productivity Kit
SCAN	Requires TIDD/T Todated Victoria
Capability	Black-and-white and color scanning
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
Simplex Input Speed	Black-and-white: Scan up to 55 ipm – 8.5 x 11 in./A4 (210 x 297 mm)
	Color: Scan up to 55 ipm – 8.5 x 11 in./55 ipm A4 (210 x 297 mm)
Duplex Input Speed	Black-and-white: Scan up to 26 ipm – 8.5 x 11 in./A4 (210 x 297 mm)
	Color: Scan up to 26 ipm – 8.5 x 11 in./26 ipm A4 (210 x 297 mm)
Resolution	Optical – 600 x 600 dpi
Bit Depth	24-bit color/8-bit grayscale
Maximum Scan Area	Platen: Up to 13.1 x 17.2 in./332 x 437 mm
Waxiiiaiii Scaii Area	Document Feeder: 11.7 x 17 in./297 x 431.8 mm
N . 150 B . 1	
Network Filing Protocols	FTP
	SMTP
	SMB
	sFTP
File Formats	JPG
	TIFF (single and multi-page)
	XPS (single and multi-page)
	PDF (single and multi-page)
	Searchable PDF via Optical Character Recognition (OCR)
	Password-protected PDF
	Linearized PDF (set via embedded web server) and PDF/A
Scan Driver Compatibility	WIA
(Network Only)	TWAIN

Detailed Specifications Page 5 of 13

c	
Supported Scan Destinations	Scan to Home
	Scan to USB
	Scan to Email
	Scan to Network (Browse FTP or Browse SMB)
NETWORK SCANNING – SOFTWAR	
Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the Xerox® ConnectKey® Technology-enabled multifunction printer.
PSTN ONE-LINE OR THREE-LINE F	FAX (OPTIONAL)
Fax ⁵	
Fax Speed	33.6 Kbps
Resolution	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi
Compression	MH, MR, MMR, JBIG
Fax Features	Walk-up Fax, includes LAN Fax, Direct Fax, Server Fax Enablement, Fax Forward to Email, Fax dialing via Unified Address Book (up to 2,000 contacts)
FAX OVER IP (OPTIONAL)	
Compliance	T.38 compliant IP/SIP
Resolution	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi
Compression	MH, MR, MMR, JBIG
Fax Features	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email, Fax dialing via Unified Address Book (up to 2,000 contacts)
MOBILE SOLUTIONS AND MOBIL	E DEVICE APPS
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Mopriα® Print Service	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.
Xerox® @PrintByXerox App	@PrintByXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
Xerox® Workplace Mobile App (download from the Xerox App Gallery)	The Xerox® Workplace Mobile App gives you the personal contactless connection you need with your multifunction printer (MFP), allowing you to save time on daily tasks and get work done safely. You can scan, print, copy or release jobs using your mobile smartphone as a remote control, without having to touch your MFP user panel. It takes the guesswork out of quickly and securely connecting your iOS and Android devices to your Xerox® MFP. Download the app for free. Use it with Xerox® Workplace Solutions to access advanced features.
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.

Detailed Specifications Page 6 of 13

SECURITY	
Security Features	Access Controls
	AES 256-bit Encryption
	Audit Log
	Certificate Path Validation
	Certificate Revocation List (CRL)/Status Protocol (OCSP)
	Detection of External Program Falsification (XCP Plug-in)
	Cisco® Identity Services Engine (ISE)
	Integration Domain Filtering
	FIPS 140-2
	Firmware Verification
	Immediate Disk Overwrite*
	IP Address Filtering
	IPsec
	Network Authentication
	Port Filtering
	Pre-installed Self-Signed Certificates
	Role Based Permissions
	Secure Email
	Secure Fax
	Secure Print
	Security Certificate Management
	Smart Card Enablement (CAC/PIV/.NET)
	SNMPv3
	Status Protocol (OCSP)
	TLS/SSL
	*Requires HDD/Productivity Kit
ACCOUNTING	
XEROX® STANDARD ACCOUNT	ING/NETWORK ACCOUNTING (STANDARD)
Tracking	Copy, Print, Fax, Scan and Email usage
Accounting	Xerox® Standard Accounting Tool
	Up to 1,000 User Accounts without HDD
	Up to 9,999 User Accounts with HDD
	Up to 500 General Accounts
	Network Accounting (Job Based Accounting)
	Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD
	Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD
	Up to 14,000 Accounting Records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NET	WORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)
	Enhanced network accounting with up to the minute data on how the system is being used
	Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print,
	scan and fax
	Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com
	Security enhancements include simultaneous support for HTTP/HTTPS protocols
	Device requests account authentication from third party server enabling larger databases of users
	and accounts
	Accept Authentication Login at control panel and pass to third party Networking Account

Detailed Specifications Page 7 of 13

PAPER HANDLING				
DOCUMENT FEEDER				
Capacity ⁶	Duplex Automatic Document Feeder (DADF): 110 sheets			
Sizes One-sided: Two-sided:	Custom sizes: 4.92 x 3.35 in. to 11.69 x 17 in./125 x 85 mm to 297 x 431.8 mm 4.92 x 4.33 in. to 11.69 x 17 in./125 x 110 mm to 297 x 431.8 mm			
Weights One-sided: Two-sided:	11 to 34 lb. bond/38 to 128 gsm 13 to 34 lb. bond/50 to 128 gsm			
BYPASS TRAY				
Capacity ⁶	100 sheets			
Sizes	Custom sizes: 3.5 x 3.87 in. to 11.69 x 17 in./88.9 x 98.4 mm to 297 x 431.8 mm			
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 216 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm			
Types	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Heavyweight Labels Letterhead Lightweight Cardstock Pre-Printed Recycled			
TRAY 1				
Capacity ⁶	520 sheets			
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm			
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm			
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled			

Detailed Specifications Page 8 of 13

SINGLE TRAY MODULE (OP	TIONAL – BASE MODEL ONLY)
Capacity ⁶	520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
Types	Bond
	Plain Paper
	Cardstock
	Custom
	Hole Punched
	Labels
	Heavyweight Labels
	Extra Heavyweight Labels
	Letterhead
	Lightweight Cardstock
	Heavyweight Cardstock
	Pre-Printed
	Recycled
SINGLE TRAY MODULE WIT	TH STAND (OPTIONAL)
Capacity ⁶	520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
Types	Bond
•	Plain Paper
	Cardstock
	Custom
	Hole Punched
	Labels
	Heavyweight Labels
	Extra Heavyweight Labels
	Letterhead
	Lightweight Cardstock
	Heavyweight Cardstock
	Pre-Printed
	Recycled
THREE TRAY MODULE (OPT	TIONAL)
Capacity ⁶	Tray 2: 520 sheets
· •	Tray 3: 520 sheets
	Tray 4: 520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights	
One-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm
Two-sided:	16 lb. bond to 60 lb. cover/60 to 169 gsm

Detailed Specifications Page 9 of 13

Types	Bond
	Plain Paper
	Cardstock
	Custom
	Hole Punched
	Labels
	Heavyweight Labels
	Extra Heavyweight Labels
	Letterhead
	Lightweight Cardstock
	Heavyweight Cardstock
	Pre-Printed
	Recycled
HIGH CAPACITY TANDEM TRAY M	ODULE (OPTIONAL)
Capacity ⁶	Tray 2: 520 sheets
	Tray 3: 870 sheets
	Tray 4: 1,130 sheets
Sizes	Tray 2: Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
	Tray 3: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5
	Tray 4: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5
Weights	
One-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm
Two-sided:	16 lb. bond to 60 lb. cover/60 to 169 gsm
Types	Bond
	Plain Paper
	Cardstock
	Custom
	Hole Punched
	Labels
	Heavyweight Labels
	Extra Heavyweight Labels
	Letterhead
	Lightweight Cardstock
	Heavyweight Cardstock
	Pre-Printed
	Recycled
ENVELOPE TRAY – REPLACES TRAY	1 (OPTIONAL)
Capacity ⁶	Up to 60 envelopes
Sizes	#10 commercial, Monarch, DL, C5
	Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./98 x 148 mm to 162 x 241 mm
Weights	20 to 25 lb. bond/75 to 90 gsm
HIGH CAPACITY FEEDER (OPTIONA	AL)
Capacity ⁶	2,000 sheets
Sizes	Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5
Weights	
_	16 lb. bond to 80 lb. cover/60 to 216 gsm
	16 lb. bond to 60 lb. cover/60 to 169 gsm

Detailed Specifications Page 10 of 13

TOTAL CAPACITY	
Base Unit Capacity ⁶	620 sheets
Single Tray Module Capacity ⁶	1,140 sheets
Single Tray Module with Stand Capacity ⁶	1,140 sheets
Three Tray Module Capacity ⁶	2,180 sheets
High-Capacity Tandem	3.140 sheets
Tray Capacity ⁶	
FINISHING	
OUTPUT TRAYS (OPTIONAL ON DE	SKTOP MODEL)
Dual Catch Trays ⁶	250 sheets each; Lower tray offsets
INTEGRATED OFFICE FINISHER TY	PE A AND INTEGRATED OFFICE FINISHER (OPTIONAL)
Stacking Tray	500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4 or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in./A3
Sizes	3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 432 mm
Weights	Integrated Office Finisher Type A: 16 lb. bond to 80 lb. cover/60 to 220 gsm Integrated Office Finisher: 16 lb. bond to 95 lb. cover/60 to 256 gsm
Stapling	Dual Auto Stapling (Single for Type A): 50 sheets maximum: Letter/A4/B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4-size sheets (less than 90 gsm or (2) 220 gsm covers)
OFFICE FINISHERS (OPTIONAL)	
Capacity ⁶	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4) (dual stapling only with optional booklet maker)
Sizes: Office Finisher LX Office Finisher	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm 5.8 x 11.7 in. to 5.8 x 17 in./148.0 x 297.0 mm to 148.0 to 432.0 mm
Weights	Office Finisher LX: 16 lb. bond to 80 lb. cover/60 to 220 gsm
	Office Finisher: 16 lb. bond to 80 lb. cover/60 to 256 gsm
Multiposition Stapling	50 sheets of 24 lb. bond/90 gsm
Hole Punch (Optional) North America: Europe:	Office Finisher LX up to 65 lb. cover (200 gsm)/Office Finisher up to 80 lb. cover (220 gsm) 2-3 Hole Punch 2-4 Hole Punch
BOOKLET MAKER FOR OFFICE FINI	SHERS (SCORE/CREASE, SADDLE-STITCH STAPLE) (OPTIONAL)
Capacity ⁶	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or less)
Sizes	Letter — 8.5 x 11 in./A4 SEF Legal — 8.5 x 14 in./B4 SEF Ledger — 11 x 17 in./A3 SEF
Saddle-stitch Stapling	2-15 sheets/8-60 page booklet
	Office Finisher LX: 16 lb. bond to 24 lb. bond/60 to 90 gsm
S 16	Office Finisher: 16 lb. bond to 80 lb. cover/64 to 220 gsm
Score/Crease	1-15 sheets/unstapled/64-105 gsm
CONVENIENCE STAPLER (OPTIONA	
Capacity ⁶	50-sheet stapling 5,000 staples
	Requires a separate outlet
DEVICE MANAGEMENT	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ FTP
	Most protocols not in use can be disabled

Detailed Specifications Page 11 of 13

Administrative Protocols	DHCP, SNM	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS			
REMOTE CONTROL PANEL	-				
	• Enables f	aster, more convenient technical support and use	er training		
		• IT administrators and other authorized users can control the device remotely from a web page on any device			
		Remote user experience is identical to performing tasks directly at the device			
XEROX® CENTREWARE® WEB					
		A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system			
	Works wi	th any SNMP-managed printer from any manufa	cturer		
		help with device discovery and installations, healt s, as well as basic accounting and asset managem			
XEROX® EMBEDDED WEB SERV	'ER – INTEGRAT	ED DEVICE WEB PAGE			
Device Status	Tray Stat	us/Contents			
	• Consumo	ables Status			
	Billing/U	sage			
	Quick Lin	ks			
	Online Su	upport			
Print Queue Viewing	Job print qu	ieue management — view and delete			
Job Submission	Print-ready	Print-ready files (PS (with optional PostScript option), PCL, PDF, XPS, JPEG)			
Device Administration	Allows simp	Allows simple, remote installation setting of configuration options and management of the device			
Browsers	Microsoft E Mozilla™ Fir	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™			
REMOTE SERVICES					
Automatic Meter Readings (AMR)	usage. Elim	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.			
Automatic Supplies Replenishment (ASR)	Automatico manually m	ılly orders supplies for Xerox® output devices base nanage supplies inventory.	ed on actual usage, eliminating the need to		
SUPPLIES AND ACCESSORIES		QUANTITY	PART NUMBER		
SUPPLIES					
Standard Capacity Print Cartric	lges ⁷	15,500 standard pages	106R03393		
High Capacity Print Cartridges ⁷		31,000 standard pages	106R03394		
Worldwide Metered Print Cartridge ⁸		30,000 standard pages	106R03392		
Black Drum Cartridge ⁹		80,000 pages	113R00779		
Office Finishers Booklet Maker Cartridge (8 cartridges per carton)		16,000 staples	008R12897		
Staple Refills for Finishers (3 cartridges per carton)		15,000 staples	008R12941		
Staple Cartridge for Finishers (1 cartridge per carton)		5,000 staples	008R12964		

Detailed Specifications Page 12 of 13

Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

ACCESSORIES/OPTIONS	PART NUMBER
Single Tray Module (does not include Stand – for Base Model only)	097S04910
Single Tray with Stand Module	097S04907
Three Tray Module	097S04908
High-Capacity Tandem Tray Module	097S04909
Envelope Tray (This replaces Tray 1)	497K17720
Center Output Tray (Dual Catch Tray)	497K17800
HDD (320 GB Hard Drive)	497K17740
Integrated Office Finisher (Type A)	097S04911
Integrated Office Finisher	097S04847
Office Finisher LX	097S04848
Office Finisher	097S05019
Booklet Maker for Office Finisher LX	497K03852
Booklet Maker for Office Finisher	497K20590
2/3 Hole Punch for Office Finisher LX (available in Western Hemisphere)	497K03860
2/3 Hole Punch for Office Finisher (available in Western Hemisphere)	497K20600
2/4 Hole Punch for Office Finisher LX (available in Eastern Hemisphere)	497K03870
2/4 Hole Punch for Office Finisher (available in Eastern Hemisphere)	497K20610
1 Line Fax Kit (PSTN Fax)	497K17750
3 Line Fax Kit (PSTN Fax)	497K17760
Wireless Network Adapter Kit	497K16750
Internal Card Reader/RFID Kit	497K18120 (Western Hemisphere)
	497K18140 (Eastern Hemisphere)
PostScript Kit	497K17810
Fax Over IP Kit	497K17820

¹ Declared print speed in accordance with ISO/IEC 24734.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.



² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Requires analog phone line.

⁶ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

⁷ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

⁸ Assumptions: Toner cartridge yield is based on 5% area coverage on 8.5 x 11 in./A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set-points.

⁹ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: https://www.office.xerox.com/latest/SUPGL-01.pdf.