

GBC[®] AdvancedPunch[™] Expand your Xerox[®] 4112[™]/4127[™] family and Xerox 700 Digital Colour Press finishing options to produce a wider variety of print jobs

The new GBC AdvancedPunch for the Xerox 4112/4127 Family and the Xerox 700 Digital Colour Press lets you create professionally bound documents in-house by combining printing, punching and collating into one convenient step.

Features

- Enables inline printing, punching and collating for ready to bind offline applications
- AdvancedPunch module is fully integrated with the printer
- Select from various interchangeable (optional) die sets for popular binding styles; no need for offline manual punching
- User-friendly replacement of die sets without need for levers or tools
- Supports punching of pre-cut tab stock to create punched applications such as manuals, guides or planners

Benefits

- Maximise productivity and lower overall cost of production; reduces setup time and cost associated with manual finishing by providing ready-to-bind documents at the touch of a button!
- Add style and versatility to bound documents; up to eleven common punching styles produce ready-to-bind documents at rated speeds
- Easy to create professionally bound documents in-house for commonly used offline binding styles
- Designed for walk-up users or for production professionals







Xerox 700 Digital Colour Press

Power Requirements

• 220 Volts, 50 Hz

Dimensions

305 mm Width
 978 mm Height
 724 mm Depth

Weight

• 70 kg.

Paper Type

• Coated and uncoated

Paper Weights

- 75 gsm 216 gsm, Uncoated
- 106 gsm 216 gsm, Coated

Paper Size (min./max.)

- A4 Long Edge Feed
- Bypass mode up to 330 mm x 488 mm

Punch Type

• Customer replaceable die sets

Note: GBC AdvancedPunch requires the Interface module and follow on finisher – High Capacity Stacker or Booklet Maker Finisher/Light Production C Finisher. The Standard Finisher is only available to 4127/4112.





Die Punch Sets for A4 Size

21-Hole Punch CombBind		_		_	_					_		_		
(standard with punch module)	1												21	
Conventional binding style Pages lie flat														
Editing capability with a machine	PB Plasti	c Bind: F	- Iole Size	: 8 mm >	(3.2 m)	n (Lx	W): C	entre-t	o-Centr	e Hole Si	oacina: '	14.3 mm		
20-Hole Punch CombBind	- Bridser						, c		.o centr		suching.			
 Conventional binding style 	1												20	
 Pages lie flat Editing capability with a 														
machine	PB Plastic Bind; Australia Hole Size: 8 mm x 3.2 mm (LxW) Centre-to-Centre Hole Spacing: 14.3 mm													
 34-Hole Twin Loop™ Binding Professional and on trend 						•			•••					
• Pages lie flat with 360°	1 34													
rotationPermanently binds														
 Keeps shape with bounce back flexibility 	W3 Wire; Round; 3 Holes per 25.4 mm; Hole Size: 4 mm Diameter; Centre-to-Centre Hole Spacing: 8.5 mm													
23-Hole Twin Loop Binding														
Professional and on trend	1													
 Pages lie flat with 360° rotation 													23	
 Permanently binds Keeps shape with bounce 	W2 Wire	W2 Wire; Round; 2 Holes per 25.4 mm; Hole Size: 6.5 mm Diameter;												
back flexibility	Centre-to-Centre Hole Spacing: 12.7 mm													
34-Hole Twin Loop Binding High-tech look 														
• Pages lie flat with 360°	1	1 34												
rotationPermanently binds	W2 Wire Square Australia 2 Holes per 25 (mm H-1- Size (mm H-1- Size)													
	W3 Wire; Square; Australia; 3 Holes per 25.4 mm; Hole Size: 4 mm x 4 mm (L x W) Centre-to-Centre Hole Spacing: 8.5 mm													
23-Hole Twin Loop Binding								_				_		
 High-tech look Pages lie flat with 	1										23			
360° rotation • Permanently binds														
	W2 Wire; Square; Australia; 2 Holes per 25.4 mm; Hole Size: 6.4 mm x 5.5 mm (L x W) Centre-to-Centre Hole Spacing 12.7 mm													
4-Hole Punch 4 Ring														
	1									,			4	
	4 Ring Bi	nder; Eu	iropean	(Standa	rd Loos	e-lea	f Patt	ern); H	ole Size:	8 mm D	iameter		-	
2-Hole Punch 2 Ring														
					1					2				
	2 Ring Bi	nder: Fu	ropean	(Loose-l	-	tern)	Hole	Size: 8						
12-Hole VeloBind®							-							
 Most secure style – permanently binds 		•	•	•	•	•	•	•	•	•	•	•	• 12	
documents														
 Book-like finish Great for filing, mailing 	VB VeloBind Round; 1 Hole per 25.4 mm; Hole Size: 3.2 mm Diameter; Centre-to-Centre Hole Spacing: 25.4 mm													
47-Hole Colour Coil™ Bind						•••		••••						
 Professional and on trend Pages lie flat with 360° 	1												47	
rotation														
Permanently binds Keeps shape with bounce C4 Coil; Round; 4 Holes per 25.4 mm; Hole Size: 4.5 mm Diameter;														
back flexibility	Centre-to-Centre Hole Spacing: 6.3 mm													
 34-Hole ProClick[®] Professional, upscale look 	1												34	
 Fast and easy Pages lie flat with 360° 														
rotation	PC ProCli				per 25	.4 mr	n, Ho	le size:	5.5 mm	x 5.0 mr	n			
Zips and unzips for quick edits	Centre-to	o-Centre	e 8.5 mn	n										

Additional dies can be purchased from your local Xerox Supplies Representative.

