

Product: 1040

PSDS No.: 0651
ISSUE DATE: 10/31/86
REV. DATE: 2/27/90

Section I - Product Identification

Manufacturer's Name
 Xerox Corporation

Emergency No. EH&S Inquiries
 (585) 422-2177 (800) 828-6571

Manufacturer's Address
 Rochester, New York 14644

Product Designation
 1040

Product Code
 P67, P69, P70, P74, P76, P78

Section II - Electrical Information

Line Voltage (Volts)	Line Current (Amps)	Freq. (Hertz)
115 or 220	12A	60

Branch Cir. Protection
 115V -15A sole use
 220V - 30A (adapter)

Line Cord / Plug Specification
 Single phase two wire & ground
 or 3 wire & ground/NEMA 5-15P

Power Consumption (Watts)*
 Running: 1400
 Standby: 200

Agency Approvals

UL File Number 24014
CSA LR Number 52267

Section III - Supplies

	Xerox Part No.
Dry Ink	6R112/113/119/128 US 6R520/521 Can.
Developer	5R111/127/139/140 US 5R507/505/509 Can.
Fuser Oil	8R983

Material Safety Data Sheet

	0024
	0024
	0223
	0223
	0407

Section IV - Environmental Information

Product Size Centimeters/Inches)	Heat Emission* (BTU/HR)
D: 71 / 28	Running: 4788
W: 130 / 51	Standby: 684
H: 106 / 42	

Environmental Limitations

	<u>Min</u>	<u>Max</u>
Relative Humidity (%)	15	85
Ambient Temp. (°C)	10	32

Floor Space Requirements
 (Meters/Feet)

Movable 2 x 1 / 7 x 5
 Stationary 2 x 2 / 8 x 7

Weight
 (K Grams/Lbs.)

Processor & I/O	181 / 399
Processor	163 / 359

* Based on a five-minute average

Section V - Emission/Exposure Information*

Light Source

Quartz Halogen

Electromagnetic Emissions

FCC: Class A

DOC: Class A

Audible Noise

Run 60.0 dB(A)
Standby 40.0 dB(A)
Impulse 65.0 dB(A)

TLV:

85 dB(A)

Ozone

138 ug/min
000.015 ppm (TWA)
000.032 ppm (Peak)

TLV:

0.1 ppm

Concentration Based on Customer Simulation Model:

Daily Copy Volume 1500 copies/7.76 hours

Room Size 5.78 m³

1/2 Air Room Change per Hour

Ozone Filter in machine

Ozone Filter is Activated Carbon fitted for Product Life

Total Dust

0.023 -0.061 mg/m³

TLV

10 mg/m³

Selenium

0.004 - 0.034 ug/m³

TLV

200 ug/m³

Arsenic

<0.01 ug/m³

PEL

10 ug/m³

Tellurium

<0.004 mg/m³

TLV

100 ug/m³

Zinc Stearate

0.252 mg/m³

TLV

10 mg/m³

Managanese

0.013 ug/m³

TLV

5 mg/m³

* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight hour workday.

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.