

Product Safety Data Sheet

XEROX

Product: 2020

PSDS No.: 0645
ISSUE DATE: 11/28/84
REV. DATE: 1/13/97

Section I - Product Identification

Manufacturer's Name

Xerox Corporation

Manufacturer's Address

Rochester, New York 14644

Product Designation

2020

Emergency No. EH&S Inquiries
(585) 422-2177 (800) 828-6571

Product Code

896

Section II - Electrical Information

Line Voltage

(Volts)

115

Line Current

(Amps)

14

Freq.

(Hertz)

60

Branch Cir. Protection

(Amps)

15A Sole use or
20A multi-use (sole use
recommended)

Line Cord / Plug Specification

220 +Single Phase 2 Wire + Ground
(NEMA 5-15R / 5-20R)

Power Consumption (Watts)*

Simplex: 1,620

Standby: 72

Agency Approvals

UL File Number E24014

CSA LR Number LR2196

Section III - Supplies

Xerox Part No.

Toner
Toner (magnetic)
Developer
Photoreceptor

6R189
6R59
5R121
1R74

Material Safety Data Sheet

0009
0009A
0209
Article (C2) **

Section IV - Environmental Information

Product Size

(Centimeters/Inches)

D: 117 / 46.1

W: 121 / 47.6

H: 122 / 48.0

Heat Emission*

(BTU/HR)

Running: 5,700

Standby: 273

Environmental Limitations

	Min	Max
Relative Humidity (%)	10	85
Ambient Temp. (°C)	10	32

* Based on a five-minute average

** MSDS is not required by OSHA, Hazard Communication Std., 29CFR or WHMIS HPA (Section II (2))

Floor Space Requirements

(Meters/Feet)

3 x 2 / 9.2 x 6.9

Weight

(K Grams/Lbs.)

231 / 509

Section V - Emission/Exposure Information*

Light Source

Long term viewing of exposure lamp may be uncomfortable but not harmful.

Electromagnetic Emissions

US FCC: Class A

Canada DOC: Class A

Ozone

422 ug/min

0.035 ppm (TWA)

0.08 ppm (Peak)

TLV

0.1 ppm

Concentration Based on Customer Simulation Model:

Daily Copy Volume 898 copies/7.88 hours

Room Size 7.01 m³

1/2 Air Room Change per Hour

Dust

0.06mg/m³

TLV

10 mg/m³

Selenium

0.04 - 0.07 ug/m³

TLV

200 ug/m³

Arsenic

0 - 0.03 ug/m³

PEL

10 ug/m³

* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight hour workday.