

Product Safety Data Sheet

XEROX

Product: 2080

PSDS No.: 0606

ISSUE DATE: 6/18/82

REV. DATE: 1/13/97

Section I - Product Identification

Manufacturer's Name

Xerox Corporation

Emergency No. EH&S Inquiries

(585) 422-2177 (800) 828-6571

Manufacturer's Address

Rochester, New York 14644

Product Designation

2080

Product Code

892

Section II - Electrical Information

Line Voltage

(Volts)

208 or 240

Line Current

(Amps)

30

Freq.

(Hertz)

60

Branch Cir. Protection

(Amps)

40A (sole use recommended)

Line Cord / Plug Specification

Single Phase 3 Wire + Ground

Three Phase 4 Wire + Ground or

"Y" Connected System + Ground

Industrial Twist/Lock Plug Cap

Rated 40 Amp, 250 VAC

Power Consumption (Watts)*

Running: 6,000

Standby: 800

Agency Approvals

UL File Number E24014

CSA LR Number LR45955

Section III - Supplies

Xerox Part No.

Dry Imager

6R230

Developer

5R218

Photoreceptor

1R19

Material Safety Data Sheet

0011

0212

Article (C2) **

Section IV - Environmental Information

Product Size

(Centimeters/Inches)

D: 140 /

W: 231 /

H: 160 /

Heat Emission*

(BTU/HR)

Running: 17,880

Standby: 9.840

Environmental Limitations

Min Max

Relative Humidity (%) 10 85

Ambient Temp. (°C) 10 32

Floor Space Requirements

(Meters/Feet)

4 x 4 /

Weight

(K Grams/Lbs.)

1,100 /

* Based on a five-minute average

** MSDS is not required by OSHA, Hazard Communication Std., 29CFR or WHMIS HPA (Section II (2))

Section V - Emission/Exposure Information*

Light Source

Long term viewing of exposure lamp may be uncomfortable but not harmful.

Electromagnetic Emissions

US FCC: Class A

Canada DOC: Class A

Ozone

155.0 ug/min
0.012 ppm (TWA)

TLV

0.1 ppm

Concentration Based on Customer Simulation Model:

Daily Copy Volume

Room Size

1/2 Air Room Change per Hour

Dust

0.02 mg/m³

TLV

10 mg/m³

Selenium

<0.04 ug/m³

TLV

200 ug/m³

Arsenic

< 0.04 ug/m³

PEL

10 ug/m³

* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight hour workday.