

# Product Safety Data Sheet

**XEROX**

**Product:** 2350

**PSDS No.:** 0608  
**ISSUE DATE:** 6/18/83  
**REV. DATE:** 2/26/90

## Section I - Product Identification

### Manufacturer's Name

Xerox Corporation

### Manufacturer's Address

Rochester, New York 14644

### Product Designation

2350

**Emergency No.** EH&S Inquiries  
(585) 422-2177 (800) 828-6571

### Product Code

T14

## Section II - Electrical Information

### Line Voltage

(Volts)

115

### Line Current

(Amps)

9

### Freq.

(Hertz)

60

### Branch Cir. Protection

(Amps)

15A Sole or Multi-use  
(sole use recommended)

### Line Cord / Plug Specification

Single Phase 2 Wire + Ground  
NEMA 5-15R / 5-20R

### Power Consumption (Watts)\*

Running: 1,000  
Standby: 160

### Agency Approvals

**UL** File Number E24014

**CSA** LR Number LR2196

## Section III - Supplies

### Xerox Part No.

Dry Imager (magnetic)	6R130
Dry Imager	6R189
Developer	5R129
Fuser Oil	8R79
Photoreceptor	1R19

## Material Safety Data Sheet

A-0009A  
A-0009  
B-0209A  
D-0407  
Article (C2) \*\*

## Section IV - Environmental Information

### Product Size

(Centimeters/Inches)

D: 56 / 22.1

W: 95 / 37.4

H: 33 / 13.0

### Heat Emission\*

(BTU/HR)

Running: 3,800

Standby: 607

## Environmental Limitations

	Min	Max
Relative Humidity (%)	10	85
Ambient Temp. (°C)	10	32

### Floor Space Requirements

(Meters/Feet)

2 x 2 / 6.6 x 6.6

### Weight

(K Grams/Lbs.)

79 / 174

\* Based on a five-minute average

\*\* MSDS is not required by OSHA, Hazard Communication Std., 29CFR or WHMIS HPA (Section II (2))

**Section V - Emission/Exposure Information\***

**Light Source**

Long term viewing of exposure lamp may be uncomfortable but not harmful.

**Electromagnetic Emissions**

US FCC: Class A  
 Canada DOC: Class A  
 Germany VDE: Class B

**Audible Noise**

Running: 57.0 dB (A)  
 Standby: 37.5 dB (A)  
 Impulse: 66.0 dB (A)

**TLV**

85.0 dB (A)

**Ozone**

120 ug/min  
 0.009 ppm (TWA)  
 0.024 ppm (Peak)

**TLV**

0.1 ppm

Concentration Based on Customer Simulation Model:

Daily Copy Volume 280 copies / 8.08 hours  
 Room Size 5.0 m<sup>3</sup>  
 1/2 Air Room Change per Hour

**Dust**

0.02 - 0.05 mg/m<sup>3</sup>

**TLV**

10 mg/m<sup>3</sup>

**Selenium**

0 - 0.04 ug/m<sup>3</sup>

**TLV**

200 ug/m<sup>3</sup>

**Arsenic**

0 - 0.02 ug/m<sup>3</sup>

**PEL**

10 ug/m<sup>3</sup>

**Nitrogen Dioxide**

0.9 ppm

**TLV**

3 ppm

\* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight hour workday.