

Product Safety Data Sheet

XEROX

Product: 2400

PSDS No.: 0640
ISSUE DATE: 6/18/82
REV. DATE: 6/19/95

Section I - Product Identification

Manufacturer's Name
Xerox Corporation
Manufacturer's Address
Rochester, New York 14644

Emergency No. EH&S Inquiries
(585) 422-2177 (800) 828-6571

Product Designation
2400

Product Code
150

Section II - Electrical Information

Line Voltage (Volts)	Line Current (Amps)	Freq. (Hertz)
208 or 240	18.5	60

Branch Cir. Protection
(Amps)
30A Sole Use (recommended)

Line Cord / Plug Specification
Single Phase 3 Wire +Ground
Three Phase 2 Wire & Neut. of "Y"
Connection System + Ground
NEMA 14-30

Power Consumption (Watts)*
Running: 3,290
Standby: 486

Agency Approvals
UL File Number E24014
CSA LR Number LR2196

Section III - Supplies

	Xerox Part No.
Dry Ink	6R208
Developer	5R54
Fuser Oil	8R79
Photoreceptor	1R14

Material Safety Data Sheet
0010
0211
0407
Article ** (C1)

Section IV - Environmental Information

Product Size (Centimeters/Inches)	Heat Emission* (BTU/HR)
D: 79 / 31	Running: 10,080
W: 165 / 65	Standby: 1,530
H: 127 / 50	

Environmental Limitations

	<u>Min</u>	<u>Max</u>
Relative Humidity (%)	15	85
Ambient Temp. (°C)	10	32

Floor Space Requirements
(Meters/Feet)
Stationary - 3.2 x 2.3 / 10.5 x 7.5
Movable - 2.7 x 2.1 / 8.9 x 6.9

Weight
(K Grams/Lbs.)
522 / 1151

*Based on a five-minute average

** MSDS is not required by OSHA, Hazard Communication Std., 29CFR or WHMIS HPA (Section II (2))

Section V - Emission/Exposure Information*

Light Source

Long Term Viewing of Exposure Lamp May Be Uncomfortable But Not Harmful.

Audible Noise

Run: 68.0 dB (A)
 Standby: 54.0 dB (A)
 Impulse: 74.0 dB (A)

TLV

85 dB (A)

Ozone

410 ug/min
 0.027 ppm (TWA)
 0.053 ppm (Peak)

TLV

0.1 ppm

Concentration Based on Customer Simulation Model:

Daily Copy Volume 3747 copies/8.08 hours
 Room Size 12.56 m³
 1/2 Air Room Change per Hour

Dust

0-0.15 mg/m³

TLV

10 mg/m³

Selenium

0-0.03 ug/m³

TLV

200 ug/m³

Arsenic PEL

0.01-0.03 ug/m³

10 ug/m³

* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight hour workday.