

# Product Safety Data Sheet

**XEROX**

**Product:** 2510 / 2511/ 2515 / 2520

**PSDS No.:** 0655  
**ISSUE DATE:** 12/15/86  
**REV. DATE:** 7/23/96

## Section I - Product Identification

**Manufacturer's Name**  
Xerox Corporation

**Emergency No.** (585) 422-2177  
**EH&S Inquiries** (800) 828-6571

**Manufacturer's Address**  
Rochester, New York 14644

**Product Designation**  
2510 / 2511/ 2515/ 2520

**Product Code**  
NA-1 / NB-1, / 64G

## Section II - Electrical Information

<b>Line Voltage</b> (Volts)	<b>Line Current</b> (Amps)	<b>Freq.</b> (Hertz)
115	12	60

**Branch Cir. Protection**  
(Amps)  
15A sole use or 20A  
Multi-use (sole use recommended)

**Line Cord / Plug Specification**  
Single Phase 2 Wire +Ground  
NEMA 5-15

**Power Consumption (Watts)\***  
Running: 1,248  
Standby: 36

### Agency Approvals

**UL** File Number E24014  
**CSA** LR Number LR60832-C

## Section III - Supplies

	<b>Xerox Part No.</b>
Dry Ink	6R234/6R239/6R254
Developer	5R178/152
Fuser Oil	19E03032
Photoreceptor	1R67

**Material Safety Data Sheet**  
A-0042A  
B-0239  
D-0407  
Article\*\* (C11)

## Section IV - Environmental Information

<b>Product Size</b> (Centimeters/Inches)	<b>Heat Emission*</b> (BTU/HR)
D: 51 / 20.1	Running: 4,300
W: 140 / 55.2	Standby: 125
H: 41 / 16.2	

**Environmental Limitations**

	<u>Min</u>	<u>Max</u>
Relative Humidity (%)	15	85
Ambient Temp. (°C)	16	32

**Floor Space Requirements**  
(Meters/Feet)  
1 x 1 / 3.3 x 3.3

**Weight**  
(K Grams/Lbs.)  
79 / 175

\* Based on a five minute average

\*\* MSDS is not required by OSHA, Hazard Communication Std., 29 CFR or WHMIS HPA (Section II (2))

**Section V - Emission/Exposure Information\***

**Light Source**

Fluorescent Lamp- Not Directly Visible to Operator

**Electromagnetic Emissions**

FCC / DOC: Class A

**Audible Noise**

Run: 53.5 dB (A)  
 Standby: 40.0 dB (A)  
 Impulse: 57.5 dB (A)

**TLV**

85.0 dB (A)

**Ozone**

200 ug/min  
 0.009 ppm (TWA)  
 0.022 ppm (Peak)

**TLV**

0.1 ppm

Concentration Based on Customer Simulation Model:

Daily Copy Volume 71 copies/8 hours  
 Room Size 15.5 m<sup>3</sup>  
 1/2 Air Room Change per Hour

**Dust**

0.018 mg/m<sup>3</sup>

**TLV**

10 mg/m<sup>3</sup>

**Selenium**

<0.013 ug/m<sup>3</sup>

**TLV**

200 ug/m<sup>3</sup>

**Arsenic**

<0.013 ug/m<sup>3</sup>

**PEL**

10 ug/m<sup>3</sup>

**Organics**

<0.1 ppm

**TLV\*\***

50 ppm

**Nickel**

0.013 ug/m<sup>3</sup>

**TLV**

1000 ug/m<sup>3</sup>

\* TLV (Threshold Limit Value) and PEL (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. these levels are considered maximum exposure permitted to ensure no health hazard. TWA (Time Weighted Average) for a normal eight hour workday.

\*\* TLV For Lowest Constituent

4/16/97

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.