

Product Safety Data Sheet

XEROX

Product: 2700

PSDS No.: 0610
ISSUE DATE: 7/14/83
REV. DATE: 1/10/01

Section I - Product Identification

Manufacturer's Name
Xerox Corporation

Emergency No. **EH&S Inquiries**
(585) 422-2177 (800) 828-6571

Manufacturer's Address
Rochester, New York 14644

Product Designation
2700

Product Code
XP11-12

Section II - Electrical Information

Line Voltage (Volts)	Line Current (Amps)	Freq. (Hertz)
115	12	60

Branch Cir. Protection
(Amps)
20A - XCI
15A - US

Line Cord / Plug Specification
Single Phase 2 Wire +Ground
NEMA 5-15P

Power Consumption (Watts)*
Running: 1,150
Standby: 250

Agency Approvals
UL File Number ES1242
CSA LR Number LR47961

Section III - Supplies

	Xerox Part No.
Dry Imager	6R99
Developer	5R136
Photoreceptor	1R33

Material Safety Data Sheet
0009
0229
Article ** (C7)

Section IV - Environmental Information

Product Size (Centimeters/Feet)	Heat Emission* (BTU/HR)
D: 66 / 26	Running: 3,930
W: 65 / 26	Standby: 1,380
H: 91 / 36	

Environmental Limitations

	<u>Min</u>	<u>Max</u>
Relative Humidity (%)	15	65
Ambient Temp. (°C)	10	32

Floor Space Requirements
(Meters/Feet)
1 x 1 / 4 x 5

Weight
(K Grams / Lbs.)
136 / 300

* Based on a five-minute average

** MSDS is not required by OSHA, Hazard Communication Std., 29CFR or WHMIS HPA (Section II (2))

Section V - Emission/Exposure Information*

Light Source

Class 1 Laser Product With an Internal Helium Neon Laser

FDA Accession

8120164-02

Electromagnetic Emissions

FCC: Class A

DOC: Class A

Audible Noise

Run: 57.0 dB (A)

Standby 34.0 dB (A)

Impulse: 61.0 db (A)

TLV

85 dB (A)

Ozone

84 ug/min

0.020 ppm (TWA)

0.039 ppm (Peak)

TLV

0.1 ppm

Concentration Based on Customer Simulation Model:

Daily Copy Volume 1200 copies/7.52 hours

Room Size 5.0 m³

1/2 Air Room Change per Hour

Dust

0.08-0.10 mg/m³

TLV

10 mg/m³

Selenium

0-0.02 ug/m³

TLV

200 ug/m³

Arsenic

0-0.05 ug/m³

PEL

10 ug/m³

Tellurium

0-0.04ug/m³

TLV

* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight hour workday.

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.