

# Product Safety Data Sheet

XEROX

**Product: 3030**

**PSDS No.: 0718**

**ISSUE DATE: 4/6/94**

**REV. DATE: 11/07/03**

## Section I - Product Identification

### Manufacturer's Name

Xerox Corporation

**Emergency No. EH&S Inquiries**

(585) 422-2177 (800) 828-6571

### Manufacturer's Address

Rochester, New York 14644

### Product Designation

3030

### Product Code

US: YA-1

Canada:YA-1

## Section II - Electrical Information

### Line Voltage

(Volts)

115

### Line Current

(Amps)

16

### Freq.

(Hertz)

60

### Branch Cir. Protection

(Amps)

20A - sole use recommended

### Line Cord / Plug Specification

Single phase two wire & ground

Plug Config. - NEMA 5-20P

### Power Consumption (Watts)\*<sup>1</sup>

Running: 1,760

Standby: 690

### Agency Approvals

**UL** File Number E51242

**CSA** LR Number LR47961

## Section III - Supplies

Toner

Developer

Fuser Oil

### Xerox Part No.

6R395

5R310

94R9181/94K9182

### Material Safety Data Sheet

A-0042A

B-0239

D-0407

## Section IV - Environmental Information

### Product Size

(Centimeters / Inches)

D: 65 / 25.6

W: 145 / 57.1

H: 119 / 46.9

### Heat Emission\*

(BTU/HR)

Running: 6,000

Standby: 2,350

### Environmental Limitations

	Min	Max
Relative Humidity (%)	15	85
Ambient Temp. (°C)	16	32

### Floor Space Requirements

(Meters / Feet)

D: 2 / 6.6

W: 3 / 9.8

### Weight

(K Grams / Lbs.)

280 / 617

\*Based on a five minute average

**Section V - Emission/Exposure Information\***

**Light Source**

Fluorescent Lamp (Not directly visible to operator)

**Electromagnetic Emissions**

US FCC: Class A  
 Canada DOC: Class A

**Audible Noise**

Run 50.5 dB(A)  
 Standby 47.0 dB(A)  
 Impulse 55.0 dB(A)

**TLV**

85.0 dB(A)

**Ozone**

138 ug/min  
 0.007 ppm (TWA)  
 0.011 ppm (STEL)

**TLV**

0.1 ppm

Concentration Values Based on Simulation Model:

Daily Copy Volume 250 ft./8 hours  
 Room Size 15.5 m<sup>3</sup>  
 1/2 Air Room Change per Hour  
 Ozone Filter Replacement Interval: (Not Applicable)

**Dust**

0.053 mg/m<sup>3</sup>

**TLV**

10.0 mg/m<sup>3</sup>

**Section VI - Product Recycling and Disposal**

Xerox operates a worldwide equipment takeback and reuse/recycle program. Contact your Xerox sales representative (1-800-ASK-XEROX) to determine whether this Xerox product is part of the program. For more information about Xerox environmental programs, visit [www.xerox.com](http://www.xerox.com) (refer to "About Xerox" section). If your product is not part of the Xerox program and you are managing its disposal, please note that the product may contain lead, mercury and other materials whose disposal may be regulated due to environmental considerations. For recycling and disposal information, contact your local authorities. In the United States, you may also refer to the Electronic Industries Alliance web site: [www.eiae.org](http://www.eiae.org).

\* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight hour workday. **STEL** (Short Term Exposure Limit).

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.