

Product Safety Data Sheet

XEROX

Product: 3300

PSDS No.: 0616

ISSUE DATE: 5/18/82

REV. DATE: 7/23/96

Section I - Product Identification

Manufacturer's Name

Xerox Corporation

Emergency No. EH&S Inquiries

(585) 422-2177 (800) 828-6571

Manufacturer's Address

Rochester, New York 14644

Product Designation

3300

Product Code

903

Section II - Electrical Information

Line Voltage

(Volts)

120

Line Current

(Amps)

12.9

Freq.

(Hertz)

60

Branch Cir. Protection

(Amps)

15A sole or 20A
Multi-use (sole use
recommended)

Line Cord / Plug Specification

Single Phase 2 Wire + Ground
NEMA 5-15R (15 Amp)
5-20R (20 Amp)

Power Consumption (Watts)*

Running: 1,355
Standby: 144

Agency Approvals

UL File Number E24014

CSA LR Number LR2196

Section III - Supplies

| | Xerox Part No. |
|----------------------|-----------------------|
| Dry Toner (magnetic) | 6R59 |
| Dry Imager | 6R233 |
| Developer | 5R108 |
| Photoreceptor | 1R19 |

Material Safety Data Sheet

0009A
0009
0209
Article ** (C2)

Section IV - Environmental Information

Product Size

(Centimeters / Inches)

D: 73 / 28.7

W: 66 / 26.0

H: 102 / 40.1

Heat Emission*

(BTU/HR)

Running: 6,420

Standby: 300

Environmental Limitations

| | <u>Min</u> | <u>Max</u> |
|-----------------------|------------|------------|
| Relative Humidity (%) | 15 | 85 |
| Ambient Temp. (°C) | 16 | 32 |

* Based on a five minute average

** MSDS is not required by OSHA Hazard Communication Std., 29 CFR or WHMIS HPA (Section II (2))

PRODUCT: 3300

PSDS No. 0616

Floor Space Requirements

(Meter / Feet)

1.2 X 1.5 / 3.9 X 4.9

Weight

(K Grams / Lbs.)

131 / 289

Section V - Emission/Exposure Information*

Light Source

Long Term Viewing of Exposure Lamp May Be Uncomfortable But Not Harmful

Electromagnetic Emissions

FCC: Class A

DOC: Class A

Audible Noise

Run 54.0 dB (A)

Impulse 66.5 dB (A)

TLV

85 dB (A)

Ozone

220 ug/min

0.022 ppm (TWA)

0.05 ppm (Peak)

TLV

0.1 ppm

Concentration Based on Customer Simulation Model:

Daily Copy Volume 670 copies/7.58 hours

Room Size 5.0 m³

1/2 Air Room Change per Hour

Total Dust

Total 0.06 mg/m³

TLV

10 mg/m³

Selenium

0.12 ug/m³

TLV

200 ug/m³

Arsenic

0.47 ug/m³

PEL

10 ug/m³

* Time weighted average (TWA) for normal, eight hour workday. TLV (Threshold Limit Value) and PEL (Permissible Exposure Level) respectively set by American Conference of Government Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposures permitted to ensure no health hazard.

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions