

# Product Safety Data Sheet

XEROX

**Product:** 3700

**PSDS No.:** 0647

**ISSUE DATE:** 6/07/85

**REV. DATE:** 1/10/01

## Section I - Product Identification

### Manufacturer's Name

Xerox Corporation

**Emergency No. EH&S Inquiries**

(585) 422-2177 (800) 828-6571

### Manufacturer's Address

Rochester, New York 14644.

### Product Designation

3700

### Product Code

E35, G78, P21

Product Identifier: CA-3

## Section II - Electrical Information

### Line Voltage

(Volts)

115

### Line Current

(Amps)

12

### Freq.

(Hertz)

60

### Branch Cir. Protection Watts

(Amps)

XCI 20A

US 15A

### Line Cord / Plug Specification

Single Phase, 2 Wire + Ground

NEMA 5-15P

### Power Consumption (Watts)\*

Running 1,440

Standby 200

### Agency Approvals

**UL** File Number E51242

**CSA** LR Number LR 47961 - 20C

## Section III - Supplies

Dry Toner (magnetic)

### Xerox Part No.

6R130

Dry Imager

6R99, 6R403

Developer

5R136, 5R403

Photoreceptor

1R19

### Material Safety Data Sheet

0009A

0009

0229

Article \*\* (C2)

## Section IV - Environmental Information

### Product Size

(Centimeters / Inches)

D: 66.0 / 26.0

W: 87.6 / 34.5

H: 91.4 / 36.0

### Heat Emission\*

(BTU/HR)

Running: 5,263

Standby 683

### Environmental Limitations

Min Max

Relative Humidity (%) 15 65

Ambient Temp. (°C) 10 32

### Floor Space Requirements

(Meters / Feet)

1.40 x 1.69 / 4.6 x 5.5

### Weight

(K Grams / Lbs.)

148 / 326

\* Based on a five-minute average

\*\* MSDS is not required by OSHA Hazard Communication Std., 29 CFR or WHMIS HPA (Section II (2))

**PRODUCT: 3700**

**PSDS No. 0647**

**Section V - Emission/Exposure Information\***

**Light Source**

Class 1 Laser Product with an  
Internal Helium Neon Laser

**FDA Accession #**

8120164-00

**Electromagnetic Emissions**

FCC: Class A

DOC: Class A

**Audible Noise**

Run: 57 dB (A)

Standby: 55 dB (A)

Impulse: 59 dB (A)

**TLV**

85 dB (A)

**Ozone**

160 ug/min

0.06 ppm (TWA)

0.09 ppm (Peak)

**TLV**

0.1 ppm

Concentration based on Customer Simulation Model:

Daily Copy Volume 4500 Copies/7.86 hours

Room Size 5.72m<sup>3</sup>

1/2 Air Room Change per Hour

**Total Dust**

0.033-0.061 mg/m<sup>3</sup>

**TLV**

10 ug/m<sup>3</sup>

**Selenium**

0.046 ug/m<sup>3</sup>

**TLV**

200 ug/m<sup>3</sup>

**Arsenic**

0.017 ug/m<sup>3</sup>

**PEL**

10 ug/m<sup>3</sup>

**Tellurium**

<0.01 ug/m<sup>3</sup>

**TLV**

100 ug/m<sup>3</sup>

\* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.

considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight hour workday.

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.

[www.xerox.com](http://www.xerox.com) Reference "About Xerox"