

# Product Safety Data Sheet

XEROX

**Product:** 4000

**PSDS No.:** 0620

**ISSUE DATE** 6/07/85

**REV. DATE:** 2/27/90

## Section I - Product Identification

### Manufacturer's Name

Xerox Corporation

### Emergency No.

(585) 422-2177

### EH&S Inquiries

(800) 828-6571

### Manufacturer's Address

Rochester, New York 14644

### Product Designation

4000

### Product Code

282

## Section II - Electrical Information

### Line Voltage

(Volts)

120

### Line Current

(Amps)

17.3

### Freq.

(Hertz)

60

### Branch Cir. Protection

(Amps)

20A sole use recommended

### Line Cord/Plug Specification

Single Phase 2 Wire + Ground

NEMA 5-30

### Power Consumption (Watts)\*

Running: 2,050

Standby: 378

### Agency Approval

**UL** File Number E24014

**CSA** File Number LR2196

## Section III - Supplies

Dry Ink

### Xerox Part No.

6R66

Developer

5R37

Photoreceptor

1R42

Fuser Oil

8R79

### Material Safety Data Sheet

0011

0212

Article \*\* (C4)

0407

## Section IV - Environmental Information

### Product Size

(Centimeters/Inches)

D: 70 / 28

W: 86 / 34

H:110 / 43

### Heat Emission\*

(BTU/HR)

Running: 6,960

Standby: 1,062

### Environmental Limitations

Min Max

Relative Humidity (%) 15 85

Ambient Temp. (°C) 16 32

### Floor Space Requirements

(Meters / Feet)

Stationary - 2 x 2 / 7 x 7

Movable - 1 x 2 / 4 x 5

### Weight

(K Grams / Lbs.)

315 / 695

\* Based on a 5 minute average

\*\* MSDS is not required by OSHA Hazard Communication Std., 29 CFR or WHMIS HPA (Section II (2))

**Section V - Emission/Exposure Information\***

**Light Source**

Long Term Viewing of Exposure Lamps May be uncomfortable but not harmful

**Electromagnetic Emissions**

FCC: Class A

DOC: Class A

**Audible Noise**

Run: 60.5 dB (A)

**TLV**

85 dB (A)

**Ozone**

379 ug/min

0.029 ppm (TWA)

0.058 ppm (Peak)

**TLV**

0.1 ppm

Concentration Based on Simulation Model:

Daily Copy Volume 2462 copies/7.86 hours

Room Size 10.0 m<sup>3</sup>

1/2 Air Room Change per Hour

**Total Dust**

0.08 mg/m<sup>3</sup>

**TLV**

10 mg/m<sup>3</sup>

**Selenium**

0.02 ug/m<sup>3</sup>

**TLV**

200 ug/m<sup>3</sup>

**Arsenic**

0.05 ug/m<sup>3</sup>

**PEL**

10 ug/m<sup>3</sup>

\* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight hour workday.