

Product Safety Data Sheet

XEROX

Product: 4018

PSDS No.: 0680
ISSUE DATE: 6/17/91
REV. DATE: 9/17/91

Section I - Product Identification

Manufacturer's Name
Xerox Corporation

Emergency No. (585) 422-2177
EH&S Inquiries (800) 828-6571

Manufacturer's Address
3-7-1 Iwatsuki-shi
Saitama-ken 339, Japan

Product Designation
4018

Product Code
Printer 9E0
Stacker 9E1

Section II - Electrical Information

Line Voltage (Volts)	Line Current (Amps)	Freq. (Hertz)
115	11.3	60

Branch Cir. Protection
(Amps)
15

Line Cord / Plug Specification
2 wire & ground
NEMA 5-15

Power Consumption (Watts)*
Running: 1344
Standby: 316

Agency Approvals
UL File Number E51242
CSA LR Number 47961 C

Section III - Supplies

	Xerox Part No.	Material Safety Data Sheet
Black Toner Cartridge	6R349	A 0082
Xerox Drum	1R116	Article** (C23)

Section IV - Environmental Information

Product Size (Centimeters / Inches)		Heat Emission* (BTU/HR)	Environmental Limitations	
Printer	Stacker		<u>Min</u>	<u>Max</u>
D: 86 / 34	D: 70 / 28	Running: 4602	Relative Humidity (%)	15 85
W: 76 / 30	H: 73 / 29	Standby: 2410	Ambient Temp. (°C)	10 35
H: 97 / 38	H: 79 / 31			

* Based on a five-minute average

** MSDS is not required by OSHA, Hazard Communication STD. 29CFR or WHMIS HPA (Section II (2))

Floor Space Requirements

(Meters / Feet)

Printer 2 x 3 / 8 x 8

Printer &

Stacker 3 x 3 / 9 x 8

Weight

(K Grams / Lbs.)

Printer 300 / 661

Stacker 85 / 187

Section V - Emission/Exposure Information*

Light Source

LED Display - Not Visible

Electromagnetic Emissions

FCC: Class A

DOC: Class A

Audible Noise

Run: 56.0 dB (A)

Standby 44.0 dB(A)

TLV

85 dB (A)

Ozone

39.9 ug/min

00.0015 ppm (TWA)

ppm (Peak)

TLV

0.1 ppm

Concentration Based on Customer Simulation Model:

Daily Copy Volume copies/7.84 hours

Room Size m³

1/2 Air Room Change per Hour

Total Dust

0.033 mg/m³

XEL

2.5 mg/m³

Selenium

0.02 µg/m³

TLV

200 µg/m³

Arsenic

<0.05 µg/m³

PEL

3.0 µg/m³

* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight hour workday.

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.