



Product Safety Data Sheet

Product: 4110 / 4590

PSDS No.: 0964
ISSUE DATE: 02/21/05
REV. DATE: 04/02/07

Section I - Product Identification

Manufacturer's Name

Xerox Corporation

Emergency No. EH&S Inquires
(585) 422-2177 (800) 828-6571

Manufacturer's Address

Webster New York 14580

Product Designation

4110 / 4590 Copier / Printer

Product Identifier:

EPB-2

Section II - Electrical Information

Line Voltage

(Volts)
208 – 240

Line Current

(Amps)
12

Freq.

(Hertz)
50/60

Branch Cir. Protection

(Amps)
15

Line Cord/Plug Specification

Power cord will be included in the system.
This is a 250V/15A cable with a length
Of 8.2 feet / 2.5 meter

Power Consumption (Watt hrs.)

Running: 1920
Standby: 375
Low Power: 120
Off: 1.20
Off/FEMP: 0.04

Xerox ENERGY STAR equipment is preset at the factory. Your machine will be delivered with the timer for switching to Power Save Mode from the last copy/print out, set at 60 minutes. A more detailed description of this feature can be found in the *Products User Guide*.

Agency Approvals

UL UL 60950-1

CAN / CSA C22.2 No 60950-1-03

Section III - Supplies

Material Safety Data Sheet

Black Toner	A-1016
Developer Black	B-2006
Drum Cartridge	C-3009

Section IV - Environmental Information

Product Size

(Centimeters / Inches)

D: 60.95 / 24

W: 274.3 / 108

H: 145.5 / 57.3

Heat Emission*

(BTU/HR)

Running: 7680

Standby: 1500

Environmental Limitations

Min Max

Relative Humidity (%) 15 - 85

Ambient Temp. (°C) 10 - 32

* Based on a five minute average

Product: 4110 / 4590

PSDS No.: 0964

Floor Space Requirements

Width x Depth, (Meters / Feet)
(3.96 x 2.74 / 13 x 9)

Weight

(K Grams / Lbs.)
268 / 595.6

Section V - Emission/Exposure Information

Light Source

Class 1 Laser Product containing an
embedded Class 3B laser

Accession Number

0421968-00

Electromagnetic Emissions

US / Canada FCC Part 15 Class A

AUDIBLE NOISE

System Configuration: HCF + IOT + Finisher/Folder

Operating Conditions

Sound Power Level B(A)

Standby	5.44
Continuous	7.87
Impulse	8.15

Ozone

Daily Copy Volume copies/ hours: 6,600
Room Size 50.0 m³

Concentration Based on Simulation Model: 0.007 ppm (parts per million parts of air)

Dust

0.024mg/m³

Styrene

0.004mg/ m³

Section VI - Product Recycling and Disposal

Xerox operates a worldwide equipment takeback and reuse/recycle program. Contact your Xerox sales representative (1-800-ASK-XEROX) to determine whether this Xerox product is part of the program. For more information about Xerox environmental programs, visit www.xerox.com/environment.

If you are managing the disposal of your Xerox product, please note that the product contains lead and other materials whose disposal may be regulated due to environmental considerations. The presence of lead is fully consistent with global regulations applicable at the time that the product was placed on the market. For recycling and disposal information, contact your local authorities. In the United States, you may also refer to the Electronic Industries Alliance web site: www.eiae.org."

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.

www.xerox.com Reference "About Xerox"