

THE XEROX 5900*i*
PRODUCTION SERIES COPIER



WORK POWER
AND SIMPLICITY



DIGITAL
THE DOCUMENT COMPANY
XEROX

THE XEROX 5900i PRODUCTION SERIES COPIER

This is our most powerful Production Series copier. In addition to its 120 page per minute speed, it features the Interposer module that enables you to use up to six stocks in a single job. The 5900i is also available without the Interposer as the 5900.

Xerox 5900i Copier Specifications

COPY SPEED

120 copies per minute, 8 1/2 x 11" (216 x 279mm); 80 copies per minute, 11 x 17" (279 x 432mm). Warm-up time: 4 minutes. First-copy-out time: 6.5 seconds. Quantity selector: 1-9,999.

ORIGINALS

Universal Document Handler:
Top Document Feeder: 8 x 10" to 11 x 17" (203 x 254mm to 279 x 432mm) in 13 lb. to 110 lb. (A4), 90 lb. (B4), 32 lb. index (A3). Holds up to 150 sheets simplex 8 1/2 x 11" (216 x 279mm) (A4), 100 sheets, 8 x 10" to 8 1/2 x 14" (203 x 254mm to 216 x 356mm); 50 sheets, 11 x 17" (279 x 432mm). Side Document Feeder: 5 x 7" to 11 x 17" (127 x 178mm to 279 x 432mm) in 13 lb. bond to 110 lb. index. Feeds one original at a time. Document Glass: 12 x 17" (305 x 432mm).

THROUGHPUT

One-sided and two-sided copying: 8 x 10" to 11 x 17" (203 x 254mm to 279 x 432mm) in 20 lb. bond to 110 lb. index. Throughput can include plain bonds, colored stock, cover stock, index stock, tab stock, three-hole drilled paper, recycled paper, carbonless paper, multipart forms, and transparencies. Interposer allows post-process insertion of preprinted color sheets with increased capacity, Mylar-edge stock and tabs, and other heat-sensitive materials.

PAPER SUPPLY

Tray 1: 550 sheets. Tray 2: 550 sheets. Tray 3: 2,100 sheets.
With Interposer: Tray 4: 550 sheets, post-process.
Tray 5: 550 sheets, pre-process or post-process.
Tray 6: 2,400 sheets, pre-process.
Continuous run while loading and automatic tray switching.

REDUCTION/ENLARGEMENT

Fully variable from 64% to 155% in 1% increments. Seven preset percentages: 64%, 71%, 78%, 100%, 129%, 141% and 155%, Auto-Centering available. All settings are customer-selectable.

MARGIN SHIFT

Shift left and right margins from 0 to 1.0 inch (0 to 25 mm) in 0.1 inch (1 mm) increments, separately selectable for Side 1 and Side 2. Shift top and bottom margins from 0 to 0.7 inch (0 to 18 mm) in 0.1 inch (1 mm) increments, applicable to both Side 1 and Side 2.

AUTOMATIC TWO-SIDED COPYING

One-sided to two-sided, two-sided to two-sided, two-sided to one-sided. Dedicated Duplex Tray capacity: 100 sheets, 8 x 10" to 8 1/2 x 14"; 50 sheets, 11 x 17".

ENHANCED EXCEPTION PAGE PROGRAMMING

Seven Page-Programmable Copy Quality settings within the same set. Subset Stapling within the same 100 sheet job. Ordered Tabs feature enables programmable sub level tab programming e.g. Have five tab supplies, program three and automatically purge two. Blank Page programming to disable billing of non-imaged sheets.

ENHANCED EDGE ERASE

Up to 4 inches (100 mm) can now be edited from the Bottom, Right or Left Side of each page. Up to 1 inch (25mm) can still be edited from the page Top.

CUSTOM COPYING FEATURE

Create your own walk up User Interface, by using the new custom copying Tools feature. Provides quick access to the most used features in your office.

OUTPUT TRAYS

Top tray: 200 sheets, 8 x 10" to 11 x 17".
Finisher tray: 2,000 sheets in sizes 8 x 10" to 11 x 17". Up to 100 sheets per collated set, 8 x 10" to 8 1/2 x 14"; 50 sheets, 11 x 17". Unload while running. Convenience Stapler staples up to 100 sheets, supplied by a refillable 5,000-staple cartridge.

FINISHER

Proportional stapling of up to 100 sheets, 8 x 10" to 8 1/2 x 14"; 50 sheets, 11 x 17". Three adjustable staple locations: portrait, landscape, and dual (book) staple. Cartridge holds 5,000 staples and is customer-replaceable. Subset Stapling and pads capability available. Optional finishing accessories available.

ELECTRONIC AUDITRON

Accounting mode: 8,794 accounts. Controlled Access mode: 2,929 accounts using 12-digit codes, 4,396 accounts using 5-digit codes.

OPTIONAL ACCESSORY KITS

Computer Forms Feeder, Interposer, Foreign Interface, Paginator, Document Binder 120, ASF 100 Automatic Stapler-Folder, ASF 100 Trimmer, Footswitch, Mouse Enable, Heat Duct Kit, Printer Enablement, Modem and PC Auditron Kit for Auditron information.

SIZE AND WEIGHT

Length: 103" (2,616 mm). Depth: 39" (991 mm). Height: 55" (1,397 mm). Weight: 1,706 lbs. (775 kg).
With Interposer: Length: 127" (3,225 mm). Weight: 2,098 lbs. (954 kg).

ELECTRICAL REQUIREMENTS

Sole use of 60 Hz, 30 amp, 120/208V or 120/240V service.

HEAT EMISSION

Standby: 1,800 BTU/hour. Running: 10,700 BTU/hour maximum.

ENVIRONMENTAL FACTORS

Noise: standby: 46 dBA maximum; running: 70 dBA maximum.
Power Saver and Power Off modes are standard.
Ozone emissions: 0.002 ppm.

NOTE: All capacities are based on 20 lb. (80 gsm) paper. Capacity will vary with different stock weights.

For more information, contact your Xerox representative, call 1-800 ASK XEROX, or visit our Web site at www.xerox.com



All Xerox 5900 Production Series Copiers are backed by the Total Satisfaction Guarantee. With Xerox, you decide if you're satisfied. Make sure to ask your Xerox representative for more details.

KEEP THE CONVERSATION GOING.
SHARE THE KNOWLEDGE.

DIGITAL
THE DOCUMENT COMPANY

XEROX



XEROX®, The Document Company®, the Digital X, Paginator, Document Binder 120, ASF 100, 5900i and 5900 are trademarks of XEROX CORPORATION. Xerox Canada Ltd. is a licensee of the trademarks. The 5900i and 5900 are newly manufactured equipment. Product appearance, build status and/or specifications are subject to change without notice. In support of Xerox' environmental leadership goals, this model may contain some recycled components that are reconditioned. ENERGY STAR® is a U.S. registered mark. As an ENERGY STAR® Partner, Xerox has determined that this copier model meets the ENERGY STAR® guidelines for energy efficiency. Terra Choice Environmental Services, Inc. of Canada has verified that this Xerox product conforms to all applicable Environmental Choice EcoLogo requirements for minimized impact to the environment.
Printed in U.S.A. 1/00 610P67522