



XEROX DOCUCOLOR 2000 SERIES

FIERY EX2000v COLOR SERVER



THE DOCUMENT COMPANY
XEROX

FIERY EX2000v COLOR SERVER

Performance. Value.

Introducing the new Fiery EX2000v—a color server that offers benchmark performance and state-of-the-art color management.

A blazing-fast 1 GHz Intel Pentium III processor delivers the processing power you need to achieve maximum productivity of your DocuColor 2045/2060—all at a price you can afford.

Tap into the full potential of your DocuColor 2045/2060

For more information on how the Fiery EX2000v can help maximize the full potential of your DocuColor 2045/2060, contact your local Xerox Sales

Representative or call 1-800-ASK-XEROX. Or, visit our Web site at www.xerox.com.



The included EFI Densitometer provides simple color calibration for fast, consistent color every time.

SPECIFICATIONS

STANDARD HARDWARE

- 1 GHz Intel Pentium III processor
- 256 MB high-speed memory; 133 MHz system bus
- 60 GB hard drive (IDE ATA 100)
- CD-ROM drive; 250 MB Zip drive
- EFI Densitometer

NETWORK PROTOCOLS

- Simultaneous, autoswitching protocols
- Ethernet protocols
 - EtherTalk Phase II
 - Novell IPX NDS
 - TCP/IP, LPR
 - SMB print sharing (over TCP/IP)
- Token Ring protocols (with optional interface card)
 - Novell IPX
 - TCP/IP, LPR
 - SMB print sharing

XEROX
TOTAL SATISFACTION GUARANTEE
For more information, contact your local Xerox representative or call 1-800 ASK XEROX in the US or Canada. Also, you can visit our Web site at www.xerox.com.

NETWORK CONNECTIVITY

- Ethernet 10/100BaseT
 - (Unshielded Twisted Pair) RJ45
- Fast Ethernet 100BaseT
- Token Ring 4MBps/16 MBps (Unshielded Twisted Pair) RJ45 and (Shielded Twisted Pair) DB9 (optional)

PAGE DESCRIPTION LANGUAGES

- Standard PDL
 - Adobe PostScript Level 3
 - Native PDF printing
 - EPS
 - TIFF

RESOLUTION

- Continuous tone at 600 x 600 dpi

UTILITIES

- Command WorkStation software for job management and control
- Fiery Link®
- Fiery Web Tools®
- Fiery Downloader®
- Fiery Spooler®

COLORWISE PRO TOOLS 2.0®

- Color Editor
- Profile Manager
- Calibration via EFI Densitometer
- Color Setup

REGULATORY APPROVALS

- Safety
 - CE Mark
 - TUV/GS
 - CB Scheme
 - CSA
 - UL
- FMC
 - EN55024 Part B (CE Marked)
 - FCC Class A
 - VCCI II

POWER SUPPLY

- Autoswitching 110/220V, 50/60 Hz for global use

POWER CONSUMPTION

- 100.5 W maximum
- 344.5 BTU/hr

Electronics
FOR Imaging

THE DOCUMENT COMPANY
XEROX

XEROX®, The Document Company® and the digital X® are trademarks of XEROX CORPORATION. Fiery®, ColorWise®, Fiery Driver®, Fiery Link® and Fiery FreeForm® are registered trademarks of Electronics for Imaging, Inc. NetWise™, DocBuilder™, Command WorkStation™ and WebTools™ are trademarks of Electronics for Imaging, Inc. Product appearance, build status and/or specifications are subject to change without notice. 6/01 610P708530