

WorkCentre™

PRO 665

Economical and expandable, the multifunction productivity solution for mid-sized workgroups with moderate-to-heavy fax traffic. The WorkCentre Pro 665 features the fastest, most efficient fax performance available, thanks to a 33.6 Kbps modem and JBIG compression, plus 12-ppm, 600x600 dpi printing in an affordable workgroup solution. The versatile but intuitive user interface, combined with ControlCentre software, make the WorkCentre Pro 665 easy to use and manage. Available network printing and faxing, as well as optional Fax-to- E-Mail capability, deliver even more productivity to every desktop.



DIGITAL
THE DOCUMENT COMPANY

XEROX

PRO 665

Fax	
Operation	Plain Paper Fax
Compatibility	ITU-T Group 3
Data Compression	JBIG, MMR, MR, MH
Modem	One V.34/33.6 Kbps with auto fallback
Handshaking Protocol	ITU-T compliant (V.8) and Xerox Accelerated Protocol (XAP)
Transmission Speed	3 seconds per page**
Security	Confidential send and receive, department codes and ITU-T T.30 subaddressing
Fax Scan Resolution	406 x 392 dpi, 300 x 300 dpi, 203 x 392 dpi Superfine, 203 x 196 dpi Fine, 203 x 98 dpi Standard***
Halftone	Error-diffusion (256 logical levels), Superfine, Fine
Memory	3 MB/300 pages*
Dual Access	Multi-access
Battery Back-up	Up to 72 hours for document storage
Dialing	300 speed dials; 68 one-touch; 50 groups of up to 368 stations each; relay broadcast up to 5000 destinations; fast dialing: dialing starts before entire document is scanned
Fast Scan	2.4 seconds per page****
ADF	Up to 50 sheets of 20lb. letter/A4 paper
Main Paper Capacity	One front-loading tray at 550 sheets (20lb/80 gsm letter/A4); 2 optional 550 sheet trays and one 100 sheet bypass tray can be added for total of 1750 sheets
Main Tray Paper Size	Letter/Legal/A4
Bypass Tray Paper Size	Envelopes, transparencies, labels, special paper (see options)
Key Reports	Activity Report, Confirmation Report, Mailbox Receipt Report, Power Failure Report, Settings Report, Pending Job List, Phonebook Lists, Department codes.
Convenience	Auto-reduction and auto-selection of legal/letter with optional tray, monitor speaker, external telephone jack, auto-redial, fax, print and copy separator pages, permanent line monitor, alternative phone numbers, auto-save for undeliverable faxes, optional handset, remote diagnostics service capability
Ease of Use	4-line, 80-character LCD display, direct feature access, ControlCentre software, front loading universal paper trays (letter/legal/A4), keyboard for character entry
Mailboxes	Up to 100 ITU-T mailboxes
Maximum Document Size	8.5 inches (216 mm) x unlimited length with operator assistance
Maximum Scan Width	8.5 inches (216mm)
Software	ControlCentre for programming machine settings and phonebooks from a connected PC
PC Fax Software	DocuLAN Fax Personal Edition version 7.0
Fax to E-Mail/Internet Fax (available with the e-mail network kit)	
Compliance	ITU-T T.37 Full/Extended Mode; IETF RFC's 2305, 2532, et al.
E-mail Compliance	SMTP, ESMTP, POP3
Confirmation	Message delivery and disposition
File Format	TIFF-FX (IETF RFC 2301—Profiles S,F,J) with MH, MR, MMR or JBIG compression
Convenience	Receiver's capabilities tracked for use in future communications; on ramp/off ramp capabilities for least cost routing
Ease of Use	Phonebook search, keyboard on control panel, ControlCentre software, programmable e-mail and fax addresses for each auto-dial, automatic multipart e-mails for large size documents
Network Scanning	Up to 400x400 dpi

Printer	
Print Technology	Laser Beam Printer Dry Electro-Xerographic, Microfine Toner
Output Print Resolution	600 x 600 dpi
Engine Speed	12-pages-per-minute
Hardware Connectivity	Bi-directional parallel port; Ethernet Network Interface Card with the e-mail network kit
Print Description Language	Windows Enhanced GDI
Printer Cable	6' IEEE 1284 compliant parallel cable (DB25 Male to Centronics 36 pin Male, double shielded) included
Supplies Yield Rates	Toner: 3,000 pages @ 5% document coverage (750 pages for included initial supplies); Drum: 10,000 pages

Copier	
Resolution	406 x 391 dpi Superfine, 203 x 195 dpi Fine printed at 406 x 391 dpi with smoothing
Multiple Copies	1-99 of multiple page originals
Reduction	100%, 86%, 75%, 50% or autofit (user selectable)
Collation	Collate or Uncollate (user selectable)
Halftone	Error-diffusion (256 logical levels), Superfine, Fine
Contrast Control	Normal, lighten, darken

Scanner	
Resolution	Up to 406 x 391 dpi
Scanning Software	TWAIN Driver, TextBridge Pro version 9.0

General	
Power	89-138 VAC, 50/60 Hz (US, Canada, Latin America) 196-266 VAC, 50/60 Hz (Europe, Latin America) 2W Superpower Save Mode, Super and Printer Power Save Mode on/off (user selectable), Energy Star Compliant, Energy 2000 compliant, Canadian Environmental Choice.
Size	Base Model (wxdxh): 28.4 x 23.3 x 13.9 inches (722 x 596 x 354 mm)
Weight	60 lbs (27 Kg) in standard configuration
Environment	Temperature operating range: 50°F (10°C) to 90°F (33°C) Humidity range: 20% to 80 % non condensing Altitude: up to 8200 feet (2,500 m) above sea level

Options	
Main Paper Trays	550 sheet universal tray for letter/legal/A4; Up to 2 optional trays can be added
Bypass Tray	100 20 lb/80 gsm Letter/A4 sheet bypass tray. Handles envelopes and transparencies up to 20 sheets at 22C/60% humidity and paper weights to 24lb/90gsm including up to 5 labels
Telephone Handset	Hearing Aid Compatible
E-mail Network Kit	Includes Fax to E-mail/Internet Fax capability and PCL 6e network printing with 10/100baseT Ethernet Network Interface Card. Available mid-2000
LAN Fax Software	DocuLAN Fax for network faxing. Available mid-2000.

Minimum System Requirements for PC Connection	
PC	Pentium with ECP or Standard Parallel Port (IEEE 1284/ECP mode recommended)
Operating System	Microsoft Windows 95, 98 or NT 4.0
Hard Disk Storage	7 MB for Print Driver, TWAIN driver and ControlCentre (Addtl 30MB for documentation), 24 MB for DocuLAN Fax Personal Edition (and 20K per stored fax page), 45MB for TextBridge Pro 9.0

Minimum Network Requirements (with the E-mail network kit)	
Network Protocols	TCP/IP, IPX/SPX (for Novell Netware 3.x, 4.x, 5.x printing only), DHCP/BOOTP
Internet Protocols	ESMTP(to support ITU-T T.37/RFC2532/Full/Extended Mode); SMTP or POP3 (to support ITU-T T.37 RFC 2305/Simple Mode)
NMS supported	HP OpenView 5.0
Network Compatibility	Ethernet 10/100baseT

*ITU-T Document # 1, (3.8% coverage), JBIG
 **ITU-T Document # 1, 33.6Kbps, MMR, ECM, Memory to Memory, Standard Resolution
 ***ITU-T G3 compatible
 ****ITU-T Document # 1, Standard Resolution

Design and specifications are subject to change without notice. For more accurate, up-to-date information, please visit www.xerox.com.

© Copyright Xerox Corporation 2000. Xerox and THE DOCUMENT COMPANY are registered trademarks of XEROX CORPORATION. DocuLAN, ControlCentre and WorkCentre are trademarks of XEROX CORPORATION. All trademarks and registered trademarks are the property of their respective owners.

Available At:



DIGITAL
 THE DOCUMENT COMPANY
 XEROX

Xerox Corporation
 Xerox Square
 Rochester, NY 14644

Xerox Canada Ltd.
 5650 Yonge Street
 North York, Ontario M2M 4G7