

PRODUCT DESCRIPTION

Phaser 8500 / 8550 Color Solid Ink Printer

MANUFACTURER INFORMATION

XEROX Corporation Office Group
P.O. Box 1000, Wilsonville, Oregon 97070-1000

PRODUCT DIMENSIONS

	Depth	Width	Height
Base Configuration	52.1 cm / 20.5 inches	40.6 cm / 16.0 inches	36.8 cm / 14.5 inches

WEIGHT

26.8 kg / 59 lbs (max)

ELECTRICAL INFORMATION

Voltage (Volts)	100-240 VAC
Frequency (Hertz)	50/60 Hertz
Current (Amps)	10-5 Amps

PRODUCT SAFETY CERTIFICATION

	Standard	Certifying Body
CB Report & Certificate	<ul style="list-style-type: none">IEC 60950-1:2001 (1st Edition)	CSA International
UL Report	<ul style="list-style-type: none">CAN/CSA C22.2 No. 60950-1-03ANSI/UL 60950-1-2002	CSA International

ELECTROMAGNETIC COMPATIBILITY

Standard	Certifying Body
89/336/EEC	XEROX – Office Group
73/23/EEC	
FCC Part 15 Class B	XEROX – Office Group

POWER CONSUMPTION

115 V			
Off Mode (W)	Power Save (W)	Standby (W)	Run Mode (W)*
0.3	48	124	330
230 V			
Off Mode (W)	Power Save (W)	Standby (W)	Run Mode (W)*
0.9	50	125	341

*Hourly rate extrapolated.

XEROX
Product Safety Data Sheet
Phaser 8500 / 8550

HEAT OUTPUT

115 V			
Off Mode (BTU/hr)	Power Save (BTU/hr)	Standby (BTU/hr)	Run Mode (BTU/hr)*
1.1	164	424	1126

230 V			
Off Mode (BTU/hr)	Power Save (BTU/hr)	Standby (BTU/hr)	Run Mode (BTU/hr)*
3.0	170	425	1164

*Hourly rate extrapolated.

NOTE: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

LIGHT SOURCE

Not applicable

AUDIBLE NOISE

Declared noise emissions in accordance with ISO 9296:1988(E):

Model: Phaser 8550 DP (Tray 2)	Idling	Operating (Enhanced Mode)
LWAd (1B=10dB)	LWAd = 4.4 B (A)	LWAd = 7.2 B (A)
Bystander Position (1.0 m)	LpAm = 30 dB (A)	LpAm = 56 dB (A)

CHEMICAL EMISSIONS

	Measured Product Concentration
Ozone	2 ppb (0.004 mg/m ³)
Styrene	Not detected
Particles (Dust)	Not detected

OZONE FILTER REPLACEMENT

Not applicable