Xerox® EX C9065/C9070 Print Server Powered by Fiery®

Get the high performance needed for higher value jobs with the Xerox® EX C9065/C9070 Print Server for the Xerox® Primel ink® C9065/C9070 Printer

BOOST YOUR PRODUCTION AND PROFITS

Easily handle heavy workloads and provide faster turnaround times with the most powerful DFE for the Xerox® PrimeLink® C9065/C9070 Printer.

OUTSTANDING COLOR, EVERY TIME

Fiery Edge™ profiles deliver stunning color with the smoothest color blends, maximum shadow details, and superb image definition. Add the optional Fiery Graphic Arts Pro Package to produce the most accurate brand colors, correct images on the fly, and generate soft proofs.

XEROX® ADAPTIVE CMYK PLUS TECHNOLOGY

Paired with the Xerox® EX-i C9065/C9070 Print Server, Xerox® Adaptive CMYK Plus Technology opens new opportunities in one of the fastest growing segments in print – specialty printing. It is sold as an accessory and engineered to augment the traditional cyan, magenta, yellow, and black (CMYK) offering and deliver specialty embellishments on demand.

The accessory expands the device's color capabilities with fluorescents and metallics, white and clear, transforming one printer into three. This technology opens new doors to growth, allowing printers and creatives in all fields to produce brilliant and unique pieces such as greeting cards, flyers, invitations, posters, and signage.

REDUCE ERRORS AND WASTE

Reduce setup time and cut waste with Fiery JobExpert[™] — a built-in feature in Fiery Command WorkStation[®] — that automatically analyzes incoming PDF files and dynamically chooses optimal Fiery print settings.

A SECURE, INTEGRATED PRODUCTION ENVIRONMENT

Built on the Microsoft® Windows 10 platform, the EX C9065/C9070 Print Server complies with customer security requirements such as FIPS 140-2. The server features standard JDF connectivity, with Xerox® Standard Accounting Feature and automate cumbersome task with support for Xerox® ConnectKey® Apps, and is compatible with the Xerox® Global Print Driver®.

SPEED UP MAKEREADY

Easily perform complex document preparation using the intuitive Fiery Impose-Compose, and the optional Fiery JobMaster™.

TURN UP THE IMPACT WITH PERSONALIZATION

With Fiery FreeForm™ Create, you can quickly personalize existing files for free. Add variable elements such as text, images, or barcodes with just a few clicks. Fiery FreeForm Create also works with Xerox® Adaptive CMYK+ toners for extra variability and personalization. Plus, the Fiery server supports industry-leading VDP formats like PDF/VT-1 and 2, PPML, VPS, and Xerox® VIPP® Language.







FIFRY DRIVEN ENGINES

- Xerox® PrimeLink® C9065/C9075 Printer
- Supports all engine finishing devices

HARDWARE/PLATFORM

- Fiery® FS500 Pro software
- Intel® Core™ i5-8500 Processor
- SSD boot drive for OS and Fiery software + 1 TB HDD
- Fiery Installer Builder
- USB media server
- Fiery QuickTouch™ software
- Five USB 3.0 ports, four USB 2.0 ports
- Microsoft® Windows® 10 IoT Enterprise 2019 LTSC

FIERY COLOR TECHNOLOGY

- Fogra VPS (Validation Printing System) Certified
- Idealliance Digital Press Certification
- Fiery Edge™ color profiles
- Fiery Spot-On™
- Fiery TrueBrand
- PANTONE® Color Enabled
- Composite overprint
- Fiery Image Enhance Visual Editor
- Image enhance
- Image smoothing
- Calibration
 - Fiery Calibrator
 - ColorCal (standard, off the glass)
- EFI™ ES-3000 spectrophotometer (option)
- Auto-trapping
- Fiery Smart Estimators
- Supports Xerox® Adaptive CMYK+ Kit

ADOBE INTERPRETER SUPPORT

- CPSI version 3020
- Adobe PDF Print Engine 5.53

PRODUCTIVITY AND WORKFLOW

- Fiery Command WorkStation®
- Fiery JobExpert™
 - Includes exclusive settings for the Xerox® PrimeLink® C9065/C9070
- Fiery Impose-Compose
 - Integration with many third-party offline finishers
- Fierv Prefliaht
- Fiery drivers for Windows and Mac
- Fiery Essential Driver
- Integration with Xerox® Global Print Driver®
- Print time estimation
- Fiery Hot Folders/Virtual Printers
- Fiery WebTools
- Schedule Print, Suspend on Mismatch, Force Print, Print/Process Next, Quick Doc Merge, and Rush Print
- Fiery JobFlow™ Base
- Fiery Remote Scan
- Fiery VUE
- Fiery Go (Android and iOS)
- Booklet Maker
- Pad printing
- Direct mobile printing
- Copy numbering
- Standard support for XLS media
- Paper Cataloa
- Automatic two-sided printing
- Cover selection
- Watermarks Banner sheets
- Sample print
- Output tray selection

PERFORMANCE

- SmartRIP
- Scan-RIP-Print
- Spool-RIP-Print
- Strict ordered printing

FILE FORMAT SUPPORT

- Adobe® PostScript® Levels 1, 2, 3
- Adobe PDF
- Enhanced PCL® 6/PCL 5
- PDF/X-1a, 3, and 4
- Microsoft Office document formats: doc, docx, xls, xlsx, ppt, pptx, pub (via the Fiery driver or Fiery Hot Folders)
- EPS, JPEG, TIFF

VARIABLE DATA PRINTING (VDP)

- Fiery FreeForm™ Create
- Supports the following formats: Fiery FreeForm Plus, VI Compose, Xerox® VIPP® PPML 2.0/2.2/3.0, Creo® VPS, PDF/VT-1 and PDF/VT-2
- VDP Record Range Printing
- Optimized PDF and PS
- Define record length Fiery VDP imposition
- **VDP** Raster Preview
- VDP Resource Manager
- Record and set level finishing support

NETWORKING/CONNECTIVITY

- TCP/IP, AppleTalk, Bonjour support, SNMP, Port 9100, IPP, FTP, SMB, WSD, point and print, print via email (PS/PDF), IPv6 support, LDAP Authentication
- Single and Dual TCP/IP Connectivity for Integration with Xerox Extensible Interface Platform® (EIP)

SECURITY FEATURES

- FIPS 140-2 compliant data encryption
- ISO/IEC 15408 & IEEE Std 2600 (Common Criteria) compliant⁴
- Secure erase, Security Profiles, Security Audit Log (integrates with SIFM solutions)
- Port blocking, IP filtering, 802.1X authentication, IPsec encryption, HTTPs with TLS 1.3 support
- Enhanced certificate management. Fiery self-signed certificates are recreated automatically
- Secure printing, PostScript security, USB security
- Digitally signed software updates
- Option to use a customer hardened Windows OS image to meet security compliance requirements

DIMENSIONS/WEIGHTS

- Print Server
 - Height: 20.75" (527.05 mm)
 - Width: 9.25" (234.95 mm)
 - Depth: 18.25" (463.55 mm)
- Weight: 36.5 lb (16.5 kg)
- NX Station GL (Stand, Server not incl.)
- Height: 60" (1525 mm)
- Width: 31.5" (800 mm)
- Depth: 34.9" (866 mm)
- Weight: 92.5 lbs (41.9 kg)

POWER

- Auto-switching: 100–240 VAC. 50/60 Hz, 6-3 Amps
- Maximum power usage: 350 W, 6 Amps @ 100V
- Typical power usage: 100 W, 1 Amp @ 100V

EMI/EMC

- FCC and ICES-003 (US and Canada)
- CE Mark EN 62368-1:2014 + A11:2017 (EU)
- RCM Mark (Australia and New Zealand)
- UK CA Mark (UK)

- CB Scheme 62368-1, 2nd Edition
- CU-Mark (US and Canada)
- T-Mark (EU)
- UK CA Mark (UK)

FIERY OPTIONS

- Fiery Graphic Arts Pro Package¹
 - Fiery Preflight Pro, Fiery Spot Pro, Fiery ImageViewer, Fiery Postflight, Fiery Control Bar
- Fiery JobMaster™
- Fiery Color Profiler Suite² with EFI™ ES-3000 spectrophotometer
 - Fiery NX Station GL (Keyboard, mouse and stand)
 - Fiery disk drive security kits (Two swappable drive enclosures, additional drive and carrier (SSD and HDD))
- Fiery Hub Kit (Dual IP)

INTEGRATION

- Native Fiery JDF
- Fiery API
- Xerox® FreeFlow® Digital Workflow Collection
- Xerox® Standard Accounting
- MIS and web-to-print integration ready
- Prepress workflow integration (Agfa® Apogee, Kodak® Prinergy, Heidelberg® Prinect, SCREEN EQUIOS)
- Compatible applications include Xerox® Workplace Suite, Xerox® Workplace Cloud, PaperCut MF/NG, Equitrac Office, YSoft SafeQ, Nuance AutoStore, and more
 - For a complete list of integrations, please visit: fierv.efi.com/xerox-apps

ongoing basis With proper configuration by end customer or service provider

⁵ Only available with Xerox® Adaptive CMYK+ Kit

©2022 Xerox Corporation. All rights reserved. Xerox®, Connectkey®, PrimeLink®, and VIPP® are trademarks of

Xerox Corporation in the United States and/or other countries. 09/22 TSK-3620 BR38203 PC9SS-03UB

¹ Free 30-day trial available ² Free trial in demo mode

³ Updated with enhancements and service releases on an