

Xerox® Crease and Two-Sided Trimmer

XEROX® CREASE AND
TWO-SIDED TRIMMER

Give your booklets the premium quality edge.



- 1 Xerox® Crease and Two-Sided Trimmer
- 2 Xerox® Production Ready Booklet Maker Finisher
- 3 Xerox® SquareFold® Trimmer

Xerox offers a wide range of finishing options with features ranging from stacking and stapling to creasing, trimming and squarefold trimming. With the Xerox® Crease and Two-Sided Trimmer*, you have the ability to provide professional-quality creasing and trimming. This production-quality inline device, when used with a Xerox® SquareFold® Trimmer, automatically creates full bleed booklets with the appearance of being perfect bound. The Crease and Two-Sided Trimmer is compact and fits easily within your print operation.

BENEFITS

- The versatile Xerox® Production Ready Finisher, handling more pages, larger sizes and heavier weights, offers a range of mix-and-match options.
- Produces variable sized and page count booklets for a high-quality professional look and feel.
- Delivers superior quality booklets on coated, uncoated and heavyweight stocks while keeping your press printing and your workflow productive.
- When configured with the Xerox® SquareFold Trimmer, creates flat finished booklets and eliminates shingle effect with professional face trim.
- Option for up to five customizable creased folds. Creasing reduces the risk of toner cracking.
- Compact, inline configuration saves labor and time of doing finishing tasks separately.



*Available on select Xerox® Presses

Recommended Finishing Options for the Xerox® Crease and Two-Sided Trimmer

XEROX® CREASE AND TWO-SIDED TRIMMER



XEROX® CREASE AND TWO-SIDED TRIMMER

Function

- Trims 0.24–0.98 in. (6–25 mm) off head and foot of sheets (inboard and outboard edges)
- Provides full bleed trim for booklets when used with the Xerox® SquareFold® Trimmer
- Creates an attractive creased fold

Paper Size for 2-Sided Sheet Trim

- Minimum: 7.64 x 8.27 in. (194 x 210 mm)
- Maximum: 13 x 19.21 in. (330.2 x 488 mm)

Paper Size for 2-Sided Booklet Trim

- Minimum: 7.64 x 10.12 in. (194 x 257 mm)
- Maximum: 13 x 19.21 in. (330.2 x 488 mm)

Paper Weights Supported

- Uncoated: 52–350 gsm
- Coated: 60–350 gsm

Additional Details

- Handles booklets of 30 sheets and up to 3/16 in. (5 mm) thickness
- Must be configured with the Xerox® Production Ready Booklet Maker Finisher or Xerox® Production Ready Finisher Plus
- Contains a Buffer Assembly to regulate booklet processing and keep pace with print engine productivity

Power Requirements

- 100–240 VAC
- 60/50 Hz
- kVA Rating: 0.1 kVA

Dimensions

- 23.81 in. (605 mm) width
- 28.5 in. (724 mm) depth
- 39.05 in. (992 mm) height

Weight

- 518 lb (235 kg)



XEROX® PRODUCTION READY BOOKLET MAKER FINISHER

Function

- Produces stapled sets with a variable-length stapler
- Provides single or dual stapling options
- 100-sheet capacity
- Creates stapled booklets up to 30 sheets (120 imposed pages at 90 gsm)
- Quad staple capability

Stapling Paper Size

- Minimum: 7.17 x 7.17 in. (182 x 182 mm)
- Maximum: 11.69 x 17 in. (297 x 432 mm)

Booklet Making Paper Weight Supported

- Uncoated: 60–350 gsm
- Coated: 60–350 gsm

Power Requirements

- 100–240 VAC
- 60/50 Hz
- kVA Rating: 0.3 kVA

Dimensions


- Xerox® Production Ready Finisher
- 33.66 in. (855 mm) width
- 28.5 in. (724 mm) depth
- 47.09 in. (1,196 mm) height

Xerox® Production Ready Booklet Maker Finisher

- 35.11 in. (892 mm) width
- 28.5 in. (724 mm) depth
- 47.09 in. (1,196 mm) height

Weight

- 231.5 lb (105 kg)



XEROX® SQUAREFOLD® TRIMMER

Function

- Receives booklets from the booklet maker area of the finisher and flattens the booklet spine and creases the cover, thereby reducing the booklet's thickness and giving it the appearance of a perfect-bound book
- Trims 2–20 mm from the fore edge of the booklet, resulting in a neat finished edge

Paper Size

- Minimum: 7.17 x 10.12 in. (182 x 257 mm)
- Maximum: 13 x 19.21 in. (330 x 488 mm)

Paper Weights Supported

- Uncoated: 60–350 gsm
- Coated: 60–350 gsm

Power Requirements

- 100–240 VAC
- 60/50 Hz
- kVA Rating: 0.1 kVA

Dimensions

- 50.4 in. (1,271 mm) width
- 28.5 in. (724 mm) depth
- 21.73 in. (552 mm) height

Weight

- 209 lb (95 kg)



Inline finishing options like the Crease and Two-Sided Trimmer enhance the value of your Xerox® printing systems, as shown on the Xerox® Versant® 3100 Press and the Xerox® Iridesse™ Production Press.

For more information on the Xerox® Crease and Two-Sided Trimmer, contact your Xerox representative, call 1-800-ASK-XEROX or visit us at www.xerox.com.