

Xerox® Colour C60/C70 Printer Colour Multifunction Printer

To interactively build and configure your own Xerox® Colour C60/C70, please visit www.buildyourownxerox.com.





	Xerox® Colour C60 Printer		Xerox [®] Colour C70 Printer	Xerox [®] Colour C70 Printer	
Simplex Speeds	Colour	Black and white	Colour	Black and white	
8.5 x 11 in. / A4 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated	Up to 60 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm Up to 30 ppm	Up to 65 ppm Up to 65 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm	Up to 70 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm Up to 35 ppm Up to 35 ppm	Up to 75 ppm Up to 75 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm Up to 35 ppm	
11 x 17 in. / A3 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated	Up to 30 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm Up to 14 ppm Up to 14 ppm	Up to 33 ppm Up to 33 ppm Up to 21 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm	Up to 35 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm Up to 17 ppm Up to 17 ppm	Up to 37 ppm Up to 37 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm	
12 x 18 in. / SRA3 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated	Up to 27 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm Up to 12 ppm	Up to 29 ppm Up to 29 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	Up to 30 ppm Up to 19 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	Up to 33 ppm Up to 33 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	
Auto Duplex Speeds	Colour	Black and white	Colour	Black and white	
8.5 x 11 in. / A4 Example: 60 to 105 gsm uncoated	Up to 60 ipm 2-sided 30 sheets per minute	Up to 65 ipm 2-sided 32 sheets per minute	Up to 70 ipm 2-sided 35 sheets per minute	Up to 75 ipm 2-sided 35 sheets per minute	
11 x 17 in. / A3 Example: 60 to 105 gsm uncoated	Up to 30 ppm 2-sided 15 sheets per minute	Up to 33 ppm 2-sided 16 sheets per minute	Up to 35 ppm 2-sided 17 sheets per minute	Up to 37 ppm 2-sided 18 sheets per minute	
Device Specifications					
Monthly Duty Cycle	Up to 300,000 pages (maximum volume capacity expected in any one month, not expected to be sustained on a regular basis).1				
Average Monthly Print Volume (AMPV)	10,000 to 50,000 pages per month ²				
Technology	Xerox® EA toner with Ultrα Low Melt Technology (2400 x 2400 dots per inch)				
Control Panel Languages	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan				

Accessories				
Optional	Offset Catch Tray High Capacity Feeder (A4)			
	1 Tray Oversized High Capacity Feeder with Store	age Bin		
	2 Tray Oversized High Capacity Feeder			
	Interface Module BR Finisher (includes Vertical Transport Kit)			
	BR Booklet Maker Finisher (includes Vertical Transport Kit)			
	C Fold / Z Fold Unit for BR Finisher or BR Booklet Maker Finisher			
	Standard Finisher (requires Interface Module)			
	Standard Finisher with Booklet Maker (requires Interface Module) C/Z Folder for Standard Finisher (requires Interface Module and Standard Finisher with or without Booklet Maker)			
	GBC® AdvancedPunch™ (requires Interface Modu			
	l i i i i i i i i i i i i i i i i i i i	GBC® AdvancedPunch™ PRO (requires Interface Module and Standard Finisher with or without Booklet Maker)		
	Xerox® SquareFold® Trimmer Module (requires Ir Convenience Stapler	iterrace Module and Standard Finisher Wit	in Booklet Maker)	
	Xerox® EX-i C60/C70 Print Server Powered by Fie	ry®		
	Xerox® FreeFlow Print Server Integrated for the X			
	Xerox® EX C60/C70 Print Server Powered by Fiery Foreign Device Interface Kit	è		
	Mobility Plate			
	Envelope Fuser Kit			
	USB Hub			
	XMPie® Variable Data Printing PostScript Kit (recommended for Xerox® Integrat	ed Colour Server for the Xerox® Colour C6	0/C70 – PostScript Kit not used with Fiery or FreeFlow Print	
	Servers)		,,	
	Media Card Reader			
	VOIP Fax 1 (3 Line Outside N. America) Fax Kits			
	Server Fax Kit			
	Common Access Card Enablement Kit			
	Xerox® Scan to PC Desktop®			
	Equitrac Office®			
Electrical Requirements	V-lh 110 127V			
North America	Voltage: 110-127V Frequency: 50/60 Hz +/- 3 % , 20 A			
Europe	Voltage: 220-240V Frequency: 50/60 Hz +/- 3%, 10 A			
Accessories North America: Europe:	Each module requires 120V, 15 A Each module requires 220V, 10 A			
Power Consumption				
Running (Average)	C60: 1,052 watts; C70: 1,250 watts			
Sleep Mode (Average)	3 watts (Default time to Sleep mode = 2 min.)			
Low Power Mode Recovery Time	Less than 20 seconds			
Operating Environment				
Required Temperature Range	50° to 82° F / 10° to 28° C (Relative Humidity les	s than 62.5% when temp is 32°C or less)		
Required Relative Humidity	15% to 85% (no condensation)			
Sound Power Levels	Operating: 6.8 B(A); Standby: 3.6 B(A)			
Sound Pressure Levels	Operating: 6.6 B(A); Standby: 18 dB(A)			
Weight (approximate base unit only)				
5		Denth	11-2-1-1	
Dimensions	Width	Depth	Height	
Base Unit with Offset Catch Tray	62 in. / 1,574 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm	
Base Unit with BR Finisher	79.1 in. / 2,009 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm	
Base Unit with BR Booklet Maker Finisher	81.4 in. / 2,068 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm	
Base Unit with BR Booklet Maker Finisher and C Fold / Z Fold Unit	90.6 in. / 2,301 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm	
Base Unit with Standard Finisher	97.7 in. / 2481 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm	
Base Unit with Booklet Maker Finisher	122.9 in. / 3,121.7 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm	
GBC® AdvancedPunch™	12 in. / 305 mm	28.5 in. / 724 mm	38.5 in. / 978 mm	
GBC® AdvancedPunch™ PRO	17.5 in. / 445 mm	28.5 in. / 724 mm	39 in. / 992 mm	

Xerox® SquareFold® Trimmer	42 in. / 1,066.3 mm	28.5 in. / 724 mm	22 in. / 558.8 mm
High Capacity Feeder	15.3 in. / 389 mm	24.2 in. / 614 mm	14.8 in. / 377 mm
One Tray Oversized High Capacity Feeder	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm
Two Tray Oversized High Capacity Feeder	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm
Certifications	<u>'</u>		
	WHQL certification (depending on print Citrix MEDITECH SAP Common Criteria Certification ENERGY STAR® Environmental Choice EPEAT GS Mark NOM EAC/GOST	t server / controller selected)	
	To view the latest list of certifications, g	o to www.xerox.com/OfficeCertifications.	
Graphic Arts Credentials			
	FOGRA certification* PANTONE® Matching System* PANTONE GOE* PANTONE PLUS* Adobe® PDF Print Engine* Adobe® PostScript® 3™ (certified) IDEAlliance Digital Press Certified to GF *requires an additional Print Server opti		
Paper Handling			
Single-pass Automatic Document	t Feeder		
Capacity ³	250 sheets of plain paper – 20 lb. / 75	gsm	
Speed	Up to 200 ipm colour / 200 ipm black o	and white (2-sided, 8.5 x 11 in. / A4)	
Paper Sizes	Custom sizes: 5.5 x 8.5 in. to 11 x 17 in	. / A5 to A3	
Weights	16 to 53 lb. bond / 60 to 200 gsm		
Bypass Tray			
Capacity ³	Up to 250 sheets		
Sizes	Custom sizes: 4 x 6 in. to 13 x 19 in. / 1	02 x 152 mm to 330.2 x 482.6 mm (A5 to SRA3)	
Weights	16 lb. bond to 110 lb. cover / 60 to 300	gsm (60 to 300 gsm uncoated; 106 to 300 gsm coa	ted)
Envelope Capacity	30 to 50 envelopes		
Envelope Sizes	- I	ustom size), C4, C5 (Available as Tray 5. Paper Size D 1 in. / 190 x 170 mm to 240 x 173 mm	efault within tools) run flap open at the trail edge)
Envelope Weights	75 to 90 gsm		
Trays 1 to 4			
Capacity ³	Tray 1: 500 sheets Tray 2: 500 sheets Tray 3: 870 sheets Tray 4: 1,140 sheets		
Sizes	Tray 1: 5.5 x 8.5 in. to 12 x 18 in. / A5 t Tray 2: 5.5 x 8.5 in. to 11 x 17 in. / A5 t Tray 3: 7.25 x 10.5 in., 8.5 x 11 in. / B5, Tray 4: 7.25 x 10.5 in., 8.5 x 11 in. / B5,	o A3 A4	
Weights		er / 60 to 256 gsm (60 to 256 gsm uncoated; 106 to	_
		er / 60 to 256 gsm (60 to 256 gsm uncoated; 106 to	220 gsm coated)
Optional High Capacity Feeder (F			
Capacity ³	2,000 sheets		

Sizes	7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4)
Weights	18 lb. bond to 80 lb. cover / 64 to 220 gsm (uncoated and coated)
	Feeder (OHCF) – 1 or 2 Tray Options
Capacity ³	1 Tray OHCF: 2,000 sheets plus Storage Cabinet 2 Tray OHCF: 4,000 sheets
Sizes	1 Tray OHCF: 7.2 x 10 in. / 182 x 250 mm (B5) to 13 x 19.2 in. / 330 x 488 mm (SRA3) 2 Tray OHCF: 4 x 6 in. / 102 x 152 mm to 13 x 19.2 in. / 330 x 488 mm (SRA3)
Weights	16 lb. bond to 110 lb. cover / 60 to 300 gsm (uncoated and coated)
Total Capacity	
Standard Capacity	3,260 sheets (includes Bypass Tray and Trays 1-4)
Maximum Capacity	7,260 sheets (includes Bypass Tray, Trays 1-4 and Two-tray Oversized High Capacity Feeder)
Automatic Two-Sided	 94 lb. cover / 256 gsm auto duplex 110 lb. cover / 300 gsm manual duplex for all stocks from bypass trays and optional Oversized High Capacity Feeder
Finishing	
Offset Catch Tray	
Capacity ³	500-sheet stacking
Optional BR Finisher (Requires Vert	•
Capacity ³	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) 11x17 in., 8.5 x 14 in., A3 or 200 sets (single-position staple) 8.5 x 11 in. / A4
Sizes	4×6 in. to 12×19 in. / A6 to SRA3 for stacking 7.25 \times 10.5 in. to 11×17 in. / B5 to A3 for stapling 5.5 \times 8.5 in. / A5 output to top tray; punch and offset
Weights	16 lb. bond to 110 lb. cover / 64 to 300 gsm (coated and uncoated)
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Optional BR Booklet Maker Finisher	r (Requires Vertical Transport Kit)
Capacity ³	Offsetting Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in. / A3 / SRA3
Sizes	4×6 in. to 12×19 in. / A6 to SRA3 for stacking 7.25 \times 10.5 in. to 11×17 in. / B5 to A3 for stapling 5.5 \times 8.5 in. / A5 output to top tray; punch and offset
Weights	16 lb. bond to 110 lb. cover / 64 to 300 gsm (coated and uncoated)
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional) Saddle stitch 2 to 16 sheets (7 sheets at 106 to 176 asm costed as 5 sheets at 177 to 220 asm costed)
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, 12 x 18 in., SRA3 supported
Optional C Fold / Z Fold Unit (Optio	onal with BR Finisher and BR Booklet Maker Finisher)
Types	C Fold, Z Fold and Z Half Fold
Capacity ³	40 sheets
Sizes	C Fold and Z Fold: Letter – 8.5 x 11 in. / A4 SEF only Z Half Fold: Tabloid – 11 x 17 in. / A3 only
Weights	16 lb. to 24 lb. bond / 64 to 90 gsm
Output Tray	Envelope Tray: C Fold, Z Fold and Tri-fold Stacker Tray or Top Tray: Z Half Fold

Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 3,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
4 x 6 in. to 13 x 19 in. / A6 to SRA3
18 lb. bond to 110 lb. cover / 64 to 300 gsm
Up to 100 sheets of 20 lb. bond / 80 gsm
2-3 Hole Punch
2-4 Hole Punch
4 Hole Swedish Punch (Optional)
200 sheets of 128 gsm 5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. / A3, A4, B4, B5
18 lb. bond to 80 lb. cover / 64 to 220 gsm
Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings
klet Maker (requires Interface Module)
Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 2,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
4 x 6 in. to 13 x 19 in. / A6 to SRA3
18 lb. bond to 110 lb. cover / 64 to 300 gsm
Up to 100 sheets of 20 lb. bond / 80 gsm
2-3 Hole Punch
2-4 Hole Punch 4 Hole Swedish Punch (Optional)
200 sheets of 128 gsm
5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. / A3, A4, B4, B5 18 lb. bond to 80 lb. cover / 64 to 220 qsm
Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings
Saddle-stitch 2 to 25 sheets of 79 gsm (uncoated) Bi-fold up to 5 sheets 8.5 x 11 in., 8.5 x 13 in., 8.5 x 14 in., 9 x 11 in., 11 x 15 in., 11 x 17 in., 12 x 18 in., 13 x 18 in. / A4, B4, A3, SRA3
ional with Standard Finisher – requires Interface Module)
8.5 x 11 in. / 216 x 279 mm to 13 x 19.2 in. / 330 x 488 mm
20 lb. bond to 80 lb. cover / 75 to 216 qsm (uncoated and coated)
Wide selection of slide-in / slide-out GBC punch die sets available
(Optional with Standard Finisher with or without Booklet Maker – requires Interface Module)
5.5 x 8.5 in. / 148 x 210 mm (A5) LEF to 13 x 19.2 in. / 330 x 488 mm (SRA3) SEF
20 lb. bond to 110 lb. cover / 75 to 300 gsm (uncoated); 28 lb. bond to 110 lb. cover / 106 to 300 gsm (coated) Wide selection of clide in / clide out GRC purch die sets available
Wide selection of slide-in / slide-out GBC punch die sets available
er Module (Optional with Standard Finisher – requires Interface Module) 5 to 20-sheet booklets (up to 80 imaged sides) at 24 lb. / 90 gsm 5 to 25-sheet booklets (up to 100 imaged sides) at 20 lb. / 80 gsm
Custom sizes: 8.5 x 11 in. to 13 x 18 in. / A4 to SRA3
18 lb. bond to 110 lb. cover / 64 to 300 gsm
To list bond to 110 list cover 7 on to 500 gain
50 sheets (24 lb. / 90 gsm media)
so sinces (2 no.), so gair media)
Up to 2/00 v 2/00 doi
Up to 2400 x 2400 dpi
600, 300, 200 and 150 Clustered Dot, 200 Rotated Line Screen (depending on print server / controller selected)
 Advanced registration technology for tighter control Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity (Available on all configurations) + 1.2 mm front to back registration

Print Features	 A true multifunction product – print, copy, fax and scan, including scan to PC, USB or email, and mobile printing Benchmark image quality with 2400 x 2400 dpi resolution and EA low melt toner for a smooth, offset-like finish Makes mobile printing simpler and more convenient Expansive media range lets you print everything from postcards to posters, both coated and uncoated stock, up to 300 gsm Xerox Extensible Interface Platform® (EIP) allows you to connect to third-party software solutions that you can access from the touch-screen of the device Your choice of servers to best fit your environment: Xerox® Integrated Colour Server for the Xerox® Colour C60/C70 Printer Xerox® EX-i C60/C70 Print Server Powered by Fiery® Xerox® FreeFlow® Print Server Integrated for the Xerox® Colour C60/C70 Printer Xerox® EX C60/C70 Print Server Powered by Fiery® Inline finishing options offer a professional polish with stapling, hole-punching, folding and booklet making for presentations, brochures, reports and newsletters Be secure with integrated security features such as IP filtering, image overwrite, secure print, encrypted Scan to Email, authentication and IPv6 support
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Print Solutions	
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.
Сору	
First-copy-out Time From the Platen: From the DADF:	As fast as 7.8 seconds colour / 5.1 seconds black and white As fast as 9.6 seconds colour / 5.3 seconds black and white
Warm Up Time	90 seconds (from cold powered down to Ready Copy)
Digital Imaging	Auto colour Auto rotation Image shift Edge erase Auto centreing Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Colour balance, colour shift and saturation
Reduce / Enlarge	Variable zoom from 25 % to 400 % in 1 % increments Anamorphic zoom Six user-programmable per centages

(Control of the Cont	
Special Features	Auto paper select Auto reduction/enlargement to fit selected paper size Auto tray switching Automatic job recovery Auto colour selection Area Designation Poster mode Annotation Single/Dual colour Booklet creation Multi-up – 2, 4 or 8 up Repeat Image Negative image Mirror image Covers insertion (front only, front and back, back only, blank or printed) Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Job interrupt Book copying Sample job Mixed-size originals Sheet Insert Stamping 2-in-1 X Y Zoom Zoom Range 25 to 400 % Margin Shift
	Photo Mode Poster Mode Preset Reduce / Enlarge Programme Ahead Covers Erase, Image Repeat, Image Rotate Interrupt Job Build
	Job Programme
Scan	
Concurrency	Scan while printing or while it is transferring scan to network or fax jobs
Scan Features	Mixed size originals Edge erase
	Reduction/enlargement Fit to size Scan Build Job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional) Preview scan job
Input Speed	Reduction/enlargement Fit to size Scan Build Job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional)
Input Speed Resolution	Reduction/enlargement Fit to size Scan Build Job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional) Preview scan job
	Reduction/enlargement Fit to size Scan Build Job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional) Preview scan job Up to 200 images per minute colour and black and white 600 x 600 dpi 400 x 400 dpi 300 x 300 dpi
Resolution	Reduction/enlargement Fit to size Scan Build Job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional) Preview scan job Up to 200 images per minute colour and black and white 600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi
Resolution Maximum Scan Area	Reduction/enlargement Fit to size Scan Build Job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional) Preview scan job Up to 200 images per minute colour and black and white 600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi Originals up to 11 x 17 in. / A3 Novell NDPS Novell Pserver / NDS Port 9100 RFC 1179 (LPR)

Som to Horse Som to Horse Som to Horse Som to Dealing PVM Som		
Sout to Disabot (WAN) Sout to Michael Sout to Michael Sout to WAN Sout to Description Sout to Descriptio	Scan Features	Scan to Home
Seat to Mellion of Piers Seat to Mellion of Piers Seat to Seat t		
Son to SFT Son to No. SFT		
Sum in STP Sum in STP Sum in STP Sum in STP Sum in STM Sum		
Source S		
Some of LETP Some in Decision Segment Person Some in Decision Segme		
Som to 18 HTMS Som		
Sum to USB Stronge Beviles Sum to USB Stronge Beviles Sum to Practice President or Sum to Doubline Sum to Huminipated Sum to Microdol Stratebolint Sum to Huminipated		
Sum to Fernical Periodical Peri		
South of Ros/Strees South of Decembration South		
Sout to Doughame Sout to Harminghold South to Marcold Thomas South to South Hard South South to Marcold Thomas South to Marcold		
South to Deminson Secretary Deminsor Secretary Deminsor Demi		Scan to Multiple Destinations
Sout to Domino South Deturning Med Set to Deturn Med Set Set to Set to Med Set		
Sout to Harmongood South Coloration South Coloration Microsoft Dynamics GP South In Microsoft Dynamics GP South In Microsoft Dynamics GP South In Microsoft South South Patients Severe South Microsoft South Microsoft South South Microsoft South Microsof		
Son to Microsoft Dynamics of Son to Microsoft Steerbant Son to Microsoft Steerbant Son to Microsoft Steerbant Son to Microsoft Steerbant Son to Microsoft Network Follow Son to Deart es Jonates of West URL Son to Deart es Jonates of West URL Son to Deart es Jonates of West URL Son to Deart es Jonates of Son to Deart es Jonates of West URL Son to Deart es Jonates of Son to Deart es Jonate		
Son to Live Live Transparies Serve Son to More Sub-Ampresse Fore Son to More More Sub-Ampresse S		g .
Sour to Microsoft Structure with Color of Structure Count to Microsoft Structure Count Structure		
Supported Scan Destination Scan to Microsoft StreePoint (Scan to Tower Find)		· ·
Supported Scan Destination Scan to Principan Products Scan to Homosport Products Scan to Homosp		
Son to Tower TRM Son to Tower TRM Son to Tower TRM Son to Web URI Son to Web URI Son to Web URI Son to Microsoft Network Folder Son to Exact = Synergy		
Scot to Web URI Scot to Mucroal Network Floride's Scot to Mucroal Network Folder's Scot to Mucroal Network Folder's Scot to Mucroal Network Folder's Scot to Exact Experts's Scot Expert		
Sout to Microsoft Network Folder Sont to Excited Symergy Sont to Email Sont to Folder, to PC, to Malibox (private and public), Sant to USB, FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbrail Preview Sont to Email Features S		· ·
Scon to Exact e Syneigy		
Supported Scan Destinations Scan to Email, Scan to Folice, to PC, to Malibox (private and public), Scan to USB, FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbnoal Preview		Scan to Microsoft Network Folder
Oston to Email Features Colour scanning, Auto Colour, Greyscale, Black and white Direct document email from device Menuals or directory Exchange? Notes? LDAP address searching Signing and encryption Email over SSL Proview scan job Authentication Shaff mathentication, PD Defore SMIP, APOP, System credentials Signing and encryption Email over SSL Proview scan job Fox Optional - One or Three Unc Two Options Colour, Auto Colour, Black and white Moximum Scan Area 11 F2SE Fox Send Features Line Fox In Proximate to FIP destination Pax Forward to FIP destination Fax Forward to FIP destination Fax Forward to SMB destination Fax Forward to FIP desti		Scan to Exact e-Synergy
Direct document email from device Manual or directory Exchange / Notes / LDAP address searching Signing and encryption Email over SSL Preview scan job Preview job Preview scan job Preview		Scan to Email, Scan to Folder, to PC, to Mailbox (private and public), Scan to USB, FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbnail Preview
Direct document email from device whomanou or directory Exchange / Notes / LDAP address searching Singing and encryption Email over Size provide scan job Authentication SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fox (Optional) - One or Three Lints - Long Disons	Scan to Email Features	Colour scanning, Auto Colour, Greyscale, Black and white
Signing and encryption Final Invertisation Pol before SMTP, APOP, System credentials Final Invertisation Pol before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication)		
Email over SSL Preview scon job		
Multipation Preview scan job SMTP, APOP, System credentials Single sign on LIDAP, SMB, Kerberos authentication Single sign on LIDAP, SMB, Small sign on LIDAP, SMB, SMB, SMB, SMB, SMB, SMB, SMB, SMB		
Authentication SMTP authentication, POP before SMTP, APOP, System credentials single sign on (LDAP, SMB, Reberos authentication) Fox (Optional) - One or Three Line* Fox Options Compatibility Colour, Auto Colour, Black and white Maximum Scan Area 11 x 17 SEF Fax Send Features IPG x IP Fox Forward to Email Fox Forward to Email Fox Forward to FTP destination Fox		
Single sign on (IDAP, SMB, Kerberos outhentication) Fax (Optional) - One or Three Line Fax Options Councy Auto Colour, Black and white Maximum Scan Area		
Fox Optionally — Octoor, Plack and white Compatibility Colour, Auto Colour, Black and white Maximum Scan Area 11 x 17 SEF Fox Send Features I fiza Lon Fax In Fax Forward to Email Fax Forward to Email Fax Forward to FTP destination Fax Print Features Print from USB Storage Device Medica Print Unicode Printing Fax Features I Fax Lon Fax In Fax Forward to FTP destination Fax Forwa	Authorition	
Compatibility Colour, Auto Colour, Black and white Maximum Scan Area 11 x 17 SEF Fax Send Features If If ICX Aura Fox Variet to Email Fox Forward to Email Fox Forward to Email Fox Forward to Email Fox Forward to Exa destination Fax Forward to Example Fox	Authentication	SMTP authentication, POP before SMTP, APOP, System credentials
Maximum Scan Area 11 x 17 SEF Fax Send Features If Fox I an Fax I P Fox Forward to Email Fax Forward to FTP destination Fax Forward to Fax destination Fax Print Features I Pint from USB Storage Device Media Print Unicode Printing Fax Features I Piox I Fox I Fox I Fox Forward to Email Fax Forward to Email Fax Forward to FTP destination Fax Forward to FTP des		SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication)
Fax Send Features If Gx Lan Fax Forward to Email Fax Forward to Email Fax Forward to FTP destination Fax Forward to FTP	Fax (Optional) – One or Three Line	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options
Lon Fax IP Fax IP Fax Forward to Email Fax Forward to FTP destination Fax Forward to FTP destination Fax Forward to SMB destination Fax Print Features Pint from USB Storage Device Media Print Unicode Printing Fax Features IFGX Lan Fax IP Fax Forward to FTP destination Fax	Fax (Optional) – One or Three Line	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options
IP Fax Fax Forward to Email Fax Forward to EMB destination Fax Forward to FTM destination Fax Forward to Fax If fax Lan Fax If Fax Fax Forward to Email Fax Forward to Email Fax Forward to Email Fax Forward to FTM destination Fax Forward t	Fax (Optional) – One or Three Line Compatibility	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white
Fax Forward to Email Fax Forward to FTP destination Fax Forward to FTP destination Fax Forward to FTP destination Fax Forward to Fax	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF
Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to SMB destination Fax Forward to Fax destination Fax Forward to Fire I destination Fax Forward to FTP destina	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF iFax Lan Fax
Fax Print Features Print Features Print Features Print Features Print Features Print Form USB Storage Device Media Print Unicode Printing Print Form VSB Storage Device Media Print Unicode Printing Print Features Prin	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF iFax Lan Fax IP Fax
Fax Features Fax Features IFax Lan Fax IP Fax Forward to Email Fax Forward to SMB destination Fax Forward to SMB destination Fax Forward to FTPP destination Fax Forward to FTPP destination Fax Forward to FTPP destination Fax Forward to SMB destination Fax Forward to FTPP destination Fax Forward to FTPP destination Fax Forward to FTPP destination Fax Forward to SMB destination Pevice Management Xerox® CentreWare® Internet Serviser—Integrated Web Pages Provided by the Device Pevice Status Web server embedded in Network Controller: • Troy status/contents • Consumables status • Alerts Job Submission Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination)Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF iFax Lan Fax IP Fax Fax Forward to Email
Device Management Web server embedded in Network Controller:	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination
Device Management Web server embedded in Network Controller:	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF IFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination
Fox Features If Cax Lan Fox IP Fax Forward to Email Fax Forward to FTP destination Fax Forward to FTP destination Fax Forward to Fax destination Device Management Xerox® CentreWare® Internet Serv= Integrated Web Pages Provided by the Device Device Status Web server embedded in Network Controller:	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination
Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination Device Management Xerox® CentreWare® Internet Services - Integrated Web Pages Provided by the Device Device Status Web server embedded in Network Controller:	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination Fax Forward to Fax destination Fax Forward to Fax destination Fox Forward to Fax destination Print from USB Storage Device
Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination Device Management Xerox® CentreWare® Internet Services - Integrated Web Pages Provided by the Device Device Status Web server embedded in Network Controller:	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination Fax Forward to Fax destination Print from USB Storage Device Media Print
Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination Fax Forward to Fax destination Device Management Xerox® CentreWare® Internet Servizer - Integrated Web Pages Provided by the Device Device Status Web server embedded in Network Controller:	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination Print from USB Storage Device Media Print Unicode Printing
Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to FTP destination Pevice Management Xerox® CentreWare® Internet Serviser - Integrated Web Pages Provided by the Device Device Status Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Job Submission Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination)Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF iFax Lan Fax IP Fax Fox Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination Fix Forward to Fix destinat
Fax Forward to SMB destination	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF iFax Lan Fax IP Fax Fox Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination Fax Forward to Fax destination Fix Forward to Fax destination Print from USB Storage Device Media Print Unicode Printing iFax Lan Fax IP Fax
Device Management Xerox® CentreWare® Internet Servites - Integrated Web Pages Provided by the Device Device Status Web server embedded in Network Controller:	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination Print from USB Storage Device Media Print Unicode Printing iFax Lan Fax IP Fax Fax Forward to Email
Device Management Xerox® CentreWare® Internet Servics - Integrated Web Pages Provided by the Device Device Status Web server embedded in Network Controller:	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination Print from USB Storage Device Media Print Unicode Printing iFax Lan Fax IP Fax Record Table The Storage Device Media Print Unicode Printing iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination
Xerox® CentreWare® Internet Services - Integrated Web Pages Provided by the Device Device Status Web server embedded in Network Controller:	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF IFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to FMB destination Fax Forward to Fax destination Print from USB Storage Device Media Print Unicode Printing IFax Lan Fax IP Fax Kar Forward to Email Fax Forward to FTP destination Fax Forward to FTP destination
Device Status Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts Job Submission Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination)Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features Fax Features	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF IFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to FMB destination Fax Forward to Fax destination Print from USB Storage Device Media Print Unicode Printing IFax Lan Fax IP Fax Kar Forward to Email Fax Forward to FTP destination Fax Forward to FTP destination
• Tray status/contents • Consumables status • Alerts Job Submission Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination)Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features Fax Features Device Management	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF Ifax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to FTP destination Fax Forward to Fax destination Fax Forward to Fax destination Fix Forward to Fax destination Fax Forward to FTP destination Fax Forward to FTP destination Fax Forward to FAX destination
Consumables status Alerts Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination)Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features Fax Features Device Management	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF Ifax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to FTP destination Fax Forward to Fax destination Fax Forward to Fax destination Fix Forward to Fax destination Fax Forward to FTP destination Fax Forward to FTP destination Fax Forward to FAX destination
• Alerts Job Submission Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination)Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features Fax Features Device Management Xerox® CentreWare® Internet Servi	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF IFax Lan Fax IP Fax Fox Forward to Email Fox Forward to FTP destination Fox Forward to FAX Storage Device Media Print Unicode Printing IFax Lan Fax IP Fax Lan Fax IP Fax Storage Device Media Print Unicode Printing IFax Lan Fax IP Fax Fox Forward to Email Fox Forward to Email Fox Forward to FTP destination
Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination)Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features Fax Features Device Management Xerox® CentreWare® Internet Servi	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF IFax Lan Fax IP Fax Fox Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Print from USB Storage Device Media Print Unicode Printing IFax Lan Fax Lan Fax IP Fax Sax Foward to Email Fax Forward to Email Fax Forward to FTP destination Fox Forward to FTP destination Fax Forward to FTP destination
Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination)Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features Fax Features Device Management Xerox® CentreWare® Internet Servi	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF IFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to FROW destination Fax Forward to FROW destination Fax Forward to FROW destination Print from USB Storage Device Media Print Unicode Printing IFax Lan Fax IP Fax Fax Forward to FROW destination Fax Forward to SMB destination
set, delay and secure, Save job or reprint)	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features Fax Features Device Management Xerox® CentreWare® Internet Servi	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF IFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to FROW destination Fax Forward to FROW destination Fax Forward to FROW destination Print from USB Storage Device Media Print Unicode Printing IFax Lan Fax IP Fax Fax Forward to FROW destination Fax Forward to SMB destination
	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features Fax Features Device Management Xerox® CentreWare® Internet Service Device Status	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fox Options Colour, Auto Colour, Black and white 11 x 17 SEF IFax Lan Fax IP Fax Fax Forward to Email Fax Forward to SMB destination Fax Forward to FXB Storage Device Media Print Unicode Printing IFax Lan Fax IP Fax Fax Fox Forward to Fx MB destination Fax Forward to Fx MB destination Fax Forward to Fx MB destination Fax Forward to Fx MB destination Fix Forward to Fx MB destination Fix Fox IP Fax Fax Forward to Email Fax Forward to SMB destination Fax Forward to Fx MB destination Fx Fx Fx Fx MB destination Fx Fx Fx Fx MB d
Device Administration Allows simple, remote installation setting of configuration ontions and management of the device	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features Fax Features Device Management Xerox® CentreWare® Internet Service Device Status	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF Ifax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Firom USB Storage Device Media Print Unicode Printing IFax Lan Fax IP Fax Fax Forward to Email Fax Forward to Email Fax Forward to SMB destination Fax Forward to SMB destination Fax Forward to FTP destinati
	Fax (Optional) – One or Three Line Compatibility Maximum Scan Area Fax Send Features Fax Print Features Fax Features Device Management Xerox® CentreWare® Internet Service Device Status	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Fax Options Colour, Auto Colour, Black and white 11 x 17 SEF Ifax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Firom USB Storage Device Media Print Unicode Printing IFax Lan Fax IP Fax Fax Forward to Email Fax Forward to Email Fax Forward to SMB destination Fax Forward to SMB destination Fax Forward to FTP destinati

Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese
Remote Services	
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® SuppliesAssistant®	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
Xerox® MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting / repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.
Security	
Features	Secure Print IPsec HTTPS (SSL) Embedded Fax Port Blocking IPv6 Support IPv4 and IPv6 Environments OS Security Updates 802.1X Support (IEEE Standard) Secure Login Network Authentication IP Address Restriction Job Audit Tray Data Encryption 128-bit AES Encryption 256-bit AES Encryption Image Overwrite Common Criteria Certification
Print Server	
	for the Xerox® Colour C60/C70 Printer
Processor	1.0 GHz Dual-core
Memory	4 GB system plus 1 GB page memory
System Disk	320 GB Hard Disk Drive
Display	10.4 in. colour touchscreen flat-panel
Device Operating System	VxWorks
Page Description Languages	Adobe® PostScript® 3™ PDF PCL® 5c, 6 XML Paper Specification (XPS®) (optional)
Operating Systems	Windows XP Windows Server 2003 (32- and 64-bit) Windows Server 2012 Windows Vista (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8 (32- and 64-bit) Mac OS® 10.7 and above Solaris® 9, 10 HP-UX® 11 v2 IBM® AIX® 5 Red Hat® Fecora® Core 15-17 Red Hat Enterprise 4 and 5 openSUSE® 11 and 12 Ubuntu® Unix®

Print Drivers Supported	Please refer to www.xerox.com/support for specifics. As new operating system versions are added, support is also added for Xerox® C60/C70 Color Printer. Also note that there is more than one print driver based on the configuration purchased (e.g. digital front ends, Xerox® Global Print Driver)
	Windows Vista, 32-bit, SP2 Windows Vista, 64-bit, SP2 Windows 7, 32-bit
	Windows 7, 64-bit Windows 8, 32-bit
	Windows 8, 64-bit Windows 8.1 Update 1, 32-bit Windows 8.1 Update 1, 64-bit Windows 10, 32-bit Windows 10, 64-bit Windows Server 2008, 32-bit Windows Server 2008, 64-bit Windows Server 2008 R2, 64-bit
	Windows Server 2012, 64-bit Windows Server 2012 R2, 64-bit Citrix® XenApp 5.0, 6.0 and 6.5 Citrix XenDesktop 7.6 Novell Netware 6.x: NDPS, NDS, iPrint Novell Open Enterprise Server Cluster: Windows Server 2008 32- and 64-bit, 2008 R2, 64-bit; Server 2012 64-bit; 2012 R2 64-bit Xerox® Mobile Express Driver®
	XPS Print Driver Xerox® Global Print Driver®
Features	Automatic two-sided Bi-directional Print Drivers provide device and job status
	 Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print) Secure print Delay print Embedded Web server for remote control/monitor/setup Enhanced Gloss
	 Sample set Booklet creation Cover selection Paper selection by attribute
	 N-up Watermarks Banner sheets Fit to new paper size Output tray selection Print calibration Print from USB Plus more!
Connectivity	Ethernet interface (10 MBTX / sec, 100 MBTX / sec, 1000 MBTX / sec)
·	For more information, go to www.xerox.com/C70IntegratedColorServer.
Additional Print Server Options	
Xerox® EX-i C60/C70 Print Serve	r Powered by Fiery®
Hardware/Platform	 Fiery® FS200 software Intel Pentium G1820 Processor (2.7 GHz) Performance optimized by proprietary combination of EFI Technology, VX600 ASIC and software
Memory	2 GB
Hard Drive	500 GB
Server Operating System	Linux®
Print Languages (PDL)	Adobe® PostScript® 3™ (v3019), PCL 6C (emulation), Adobe Acrobat 9
Features	 Productivity starts with a fast RIP. The Integrated Fiery Colour Server enables you to print large and/or complex Microsoft® Office® documents, PowerPoint® files and colour-critical PDFs accurately and quickly. Simplify and streamline your workflow. Automate job submission of repetitive job types to achieve productive, error-free workflows with Hot Folders and Virtual Printers. Take advantage of commonly used Fiery presets to save time when submitting jobs. With Fiery server technology, even novice users can perform complex jobs using the pre-set drivers configured for the task. Get the colour right. Produce precise, exact colour from all applications, platforms and formats with Fiery colour management tools. Turn up the impact with variable information. Customise your output to a specific audience with varying text, photos and graphics with the Integrated Fiery Colour Server's basic variable data printing capabilities.
Connectivity	Direct Connection (Single IP)

Fiery Productivity Package Option Xerox® FreeFlow® Print Server Integral	Fiery JDF Graphic arts filters for Hot Folders Fiery Image Enhance Visual Editor Fiery ImageViewer Postflight report Control bar Configurable auto trapping Paper simulation For more information, go to www.xerox.com/C70EXiFieryColorServer.
Processor	Intel® Dual Core Pentium G3420 Processor
Memory	16 GB
System Disk	1 TB 7200 SATA or equal
Print Languages (PDL)	Adobe® PostScript® Level 1, 2, 3 PDF up to version 1.7 (Acrobat XI), including PDF/VT-1 specification version 1.1, PDF/X-1a, PDF/X-3 and PDF/X-4 EPS TIFF v6, native and multi-page (TIFF-IT is not supported) Xerox® Variable-data Intelligent PostScript Printware (VIPP) (license required) Jobs submitted from Xerox® FreeFlow® Workflow Offerings Compatible with Xerox® FreeFlow Variable Information Suite Version 9.0 JPEG Microsoft Word and PowerPoint documents XPS IPDS (license required) PPML The following file formats are not supported: ASCII PCL
Features	Simple Windows 7 platform for a familiar experience Integrated / Bustled setup. Perfect for small footprint and quick and easy site setups Accepts Native Microsoft Office® files for Direct Print (from walk-up USB PowerPoint®, for example) Productive All the advantages of a Xerox Production workflow – delivered in a value-oriented solution Streamlined drag/drop submission from tablets and more Powerful Bring the power of Xerox® patented RIP technology in a value oriented solution Latest direct Adobe PDF Print Engine and GC credentials included Includes Variable Data Print / Colour Management / Production Workflows Tints and Highlights fine-tuned for better accuracy Duotone, Tri-tone and Quad-tone support Spot Colour Editor Calibration and Profiling with XRite i1, Pro2 (optional) Job Accounting reporting Custom Paper Catalogue IPDS and PPML Faster job programming with 'Select by Tray' job programming Simplified and intuitive job recovery Enhanced imposition
Connectivity	Direct Connection (Single IP)
	For more information, go to www.xerox.com/C70FreeflowPrintServer.
Xerox® EX C60/C70 Print Server Pov	wered by Fiery®
Processor	Intel® Core™ i5-4570S Processor 2.9 up to 3.60 GHz with Turbo, Quad Core Performance optimised by proprietary combination of EFI technology, VX600 ASIC and software
Memory (ESS)	4 GB
System Disk	1 TB
Print Languages (PDL)	Adobe PostScript® Level 1, 2, 3; PDF/X-1a, 3 and 4; EPS; Adobe Acrobat® 9.1, Native PDF 1.3, 1.4, 1.5, 1.6 and 1.7; CT/LW; TIFF, TIFF/IT, DCS2, JPEG Microsoft Native Formats (DOC, XLS, PUB, PPT) enabled through Fiery Hot Folders feature EFI™ FreeForm 1, and FreeForm 2 VDP

Features Job-based Calibration Integration – Fiery Spot-On finds the best match of PANTONE®, PANTONE Series, RGB, CMYK, L*a*b* and Spot Colours - Colour Modes for prefessional proofing and enhanced production colour requirements - Maximum print density • Fiery Graphic Arts Package, Premium Edition (optional) provices expert tools for preflighting and troubleshooting jobs • Fiery Colour Profiler Suite (optional) creates, verifies and edits color profiles with a single profiling solution • Fiery technology increases your profits by delivering high-impact documents with vibrant images and colour that exceed your customers' expectations and also meets tight turnaround times and allows you to do more work by automating manual tasks and removing bottlenecks that slow down • Fiery technology increases your profits by delivering high-impact documents with vibrant images and colour that exceed your customers' expectations and also meets tight turnaround times and allows you to do more work by automating manual tasks and removing bottlenecks that slow down • With Fiery technology, you can produce effective marketing pieces with the widest range of output options, including automatic identification of job elements such as text, images and spot colours. This feature also eliminates the need to re-programme jobs, making the process simple and quick. It is ideal for producing powerful marketing materials, personalised communications and packaging and photo publishing applications. • Fiery ColourWise gives high-quality colour out-of-the-box and integrates the essential components of Fiery Graphic Arts Package, Premium Edition, Fiery Spot-On and the Fiery Colour Profiler Suite to control and manage colour throughout your workflow. • The Fiery Command WorkStation increases your production and reduces errors and waste by centralising job management via its intuitive user interface. Simplify your labour-intensive document composition and imposition tasks even more by using Fiery SeeQuence Impose and Compose's intuitive interface. • Fiery JDF technology connects EFI solutions and Fiery-enabled solutions, so you can move job information through your system faster and more efficiently. By supporting the Adobe PDF Print Engine, Fiery servers also offer a native end-to-end PDF workflow, therefore improving the consistency and flexibility of your printed output from design to print. • Using Fiery servers and Fiery Command Workstation, you get a new level of integration for process and profit improvement, including seamless connectivity to Xerox® FreeFlow® for workflow automation. Connectivity Direct Connection (Single IP), Network Switch, (Dual IP) For more information, go to www.xerox.com/C70EXPrintServer.

Supplies	Description	Yield	Part Number	
Customer Replaceable Items				
Toner Cartridges (Metered)	Black	30,000 pages ⁴	006R01521	
	Cyan	34,000 pages ⁴	006R01524	
	Magenta	32,000 pages ⁴	006R01523	
	Yellow	34,000 pages ⁴	006R01522	
Toner Cartridges (Sold)	Black	30,000 pages ⁴	006R01659	
	Cyan	34,000 pages ⁴	006R01660	
	Magenta	32,000 pages ⁴	006R01661	
	Yellow	34,000 pages ⁴	006R01662	
Black Drum Cartridge	1 Cartridge	190,000 pages ⁴	013R00663	
Colour Drum Cartridge	1 Cartridge per Colour	85,000 pages ⁴	013R00664	
Charge Corotron	For Black Drum	190,000 pages ⁴	013R00650	
Fuser	110V 220V	200,000 pages ⁴ 200,000 pages ⁴	008R13102 008R13065	
Waste Toner Container	1 Cartridge	50,000 pages ⁴	008R12990	
Feed Roll Kits	1 Assembly	300,000 pages ⁴	008R13169	
Staple Cartridges	For BR Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964	
	For BR Booklet Maker Finisher (4 cartridges per carton)	5,000 each cartridge	008R13177	
	Staple Cartridge and Waste Container for Standard Finisher	5,000 each cartridge	008R13041	
Staple Refills	For BR Finisher, BR Booklet Maker Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill (15,000 total)	008R12941	

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

To view a product video, visit www.xerox.com. Build and configure your own Xerox® Colour C60/C70 Printer at www.buildyourownxerox.com.



² Expected regular monthly throughput.

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁶ Approximate pages. Declared Yield based on 5 page job size, 30% colour and 70% Black and white ratio, using letter / A4 media. Yield will vary based on media size, image area coverage, job run length, media orientation and usage patterns.