

Xerox® Colour C60/C70 Printer

Colour Multifunction Printer

To interactively build and configure your own Xerox® Colour C60/C70, please visit www.buildyourownxerox.com.



| Xerox® Colour C60 Printer | | Xerox® Colour C70 Printer | | |
|---|---|--|--|--|
| Simplex Speeds | Colour | Black and white | Colour | Black and white |
| 8.5 x 11 in. / A4 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated | Up to 60 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm | Up to 65 ppm Up to 65 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm | Up to 70 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm Up to 35 ppm | Up to 75 ppm Up to 75 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm |
| 11 x 17 in. / A3 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated | Up to 30 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm Up to 14 ppm | Up to 33 ppm Up to 33 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm | Up to 35 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm Up to 17 ppm | Up to 37 ppm Up to 37 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm |
| 12 x 18 in. / SRA3 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated | Up to 27 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm | Up to 29 ppm Up to 29 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm | Up to 30 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm | Up to 33 ppm Up to 33 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm |
| Auto Duplex Speeds | Colour | Black and white | Colour | Black and white |
| 8.5 x 11 in. / A4 Example: 60 to 105 gsm uncoated | Up to 60 ipm 2-sided 30 sheets per minute | Up to 65 ipm 2-sided 32 sheets per minute | Up to 70 ipm 2-sided 35 sheets per minute | Up to 75 ipm 2-sided 35 sheets per minute |
| 11 x 17 in. / A3 Example: 60 to 105 gsm uncoated | Up to 30 ppm 2-sided 15 sheets per minute | Up to 33 ppm 2-sided 16 sheets per minute | Up to 35 ppm 2-sided 17 sheets per minute | Up to 37 ppm 2-sided 18 sheets per minute |
| Device Specifications | | | | |
| Monthly Duty Cycle | Up to 300,000 pages (maximum volume capacity expected in any one month, not expected to be sustained on a regular basis). ¹ | | | |
| Average Monthly Print Volume (AMPV) | 10,000 to 50,000 pages per month ² | | | |
| Technology | Xerox® EA toner with Ultra Low Melt Technology (2400 x 2400 dots per inch) | | | |
| Control Panel Languages | International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan | | | |

Xerox® Colour C60/C70 Printer

| Accessories | | | |
|--|--|---------------------|-----------------------|
| Optional | Offset Catch Tray High Capacity Feeder (A4) 1 Tray Oversized High Capacity Feeder with Storage Bin 2 Tray Oversized High Capacity Feeder Interface Module BR Finisher (includes Vertical Transport Kit) BR Booklet Maker Finisher (includes Vertical Transport Kit) C Fold / Z Fold Unit for BR Finisher or BR Booklet Maker Finisher Standard Finisher (requires Interface Module) Standard Finisher with Booklet Maker (requires Interface Module) C/Z Folder for Standard Finisher (requires Interface Module and Standard Finisher with or without Booklet Maker) GBC® AdvancedPunch™ (requires Interface Module and Standard Finisher with or without Booklet Maker) GBC® AdvancedPunch™ PRO (requires Interface Module and Standard Finisher with or without Booklet Maker) Xerox® SquareFold® Trimmer Module (requires Interface Module and Standard Finisher with Booklet Maker) Convenience Stapler Xerox® EX-i C60/C70 Print Server Powered by Fiery® Xerox® FreeFlow Print Server Integrated for the Xerox® Colour C60/C70 Printer Xerox® EX C60/C70 Print Server Powered by Fiery® Foreign Device Interface Kit Mobility Plate Envelope Fuser Kit USB Hub XMPie® Variable Data Printing PostScript Kit (recommended for Xerox® Integrated Colour Server for the Xerox® Colour C60/C70 – PostScript Kit not used with Fiery or FreeFlow Print Servers) Media Card Reader VOIP Fax 1 (3 Line Outside N. America) Fax Kits Server Fax Kit Common Access Card Enablement Kit Xerox® Scan to PC Desktop® Equitrac Office® | | |
| Electrical Requirements | | | |
| North America | Voltage: 110-127V Frequency: 50/60 Hz +/- 3%, 20 A | | |
| Europe | Voltage: 220-240V Frequency: 50/60 Hz +/- 3%, 10 A | | |
| Accessories North America: Europe: | Each module requires 120V, 15 A Each module requires 220V, 10 A | | |
| Power Consumption | | | |
| Running (Average) | C60: 1,052 watts; C70: 1,250 watts | | |
| Sleep Mode (Average) | 3 watts (Default time to Sleep mode = 2 min.) | | |
| Low Power Mode Recovery Time | Less than 20 seconds | | |
| Operating Environment | | | |
| Required Temperature Range | 50° to 82° F / 10° to 28° C (Relative Humidity less than 62.5% when temp is 32° C or less) | | |
| Required Relative Humidity | 15% to 85% (no condensation) | | |
| Sound Power Levels | Operating: 6.8 B(A); Standby: 3.6 B(A) | | |
| Sound Pressure Levels | Operating: 56 dB(A); Standby: 18 dB(A) | | |
| Weight (approximate base unit only) | 604 lb., 273 kg | | |
| Dimensions | Width | Depth | Height |
| Base Unit with Offset Catch Tray | 62 in. / 1,574 mm | 31.6 in. / 803.5 mm | 54.8 in. / 1,391.5 mm |
| Base Unit with BR Finisher | 79.1 in. / 2,009 mm | 31.6 in. / 803.5 mm | 54.8 in. / 1,391.5 mm |
| Base Unit with BR Booklet Maker Finisher | 81.4 in. / 2,068 mm | 31.6 in. / 803.5 mm | 54.8 in. / 1,391.5 mm |
| Base Unit with BR Booklet Maker Finisher and C Fold / Z Fold Unit | 90.6 in. / 2,301 mm | 31.6 in. / 803.5 mm | 54.8 in. / 1,391.5 mm |
| Base Unit with Standard Finisher | 97.7 in. / 2,481 mm | 31.6 in. / 803.5 mm | 54.8 in. / 1,391.5 mm |
| Base Unit with Booklet Maker Finisher | 122.9 in. / 3,121.7 mm | 31.6 in. / 803.5 mm | 54.8 in. / 1,391.5 mm |
| GBC® AdvancedPunch™ | 12 in. / 305 mm | 28.5 in. / 724 mm | 38.5 in. / 978 mm |
| GBC® AdvancedPunch™ PRO | 17.5 in. / 445 mm | 28.5 in. / 724 mm | 39 in. / 992 mm |

Xerox® Colour C60/C70 Printer

| | | | |
|---|--|-------------------|-------------------|
| Xerox® SquareFold® Trimmer | 42 in. / 1,066.3 mm | 28.5 in. / 724 mm | 22 in. / 558.8 mm |
| High Capacity Feeder | 15.3 in. / 389 mm | 24.2 in. / 614 mm | 14.8 in. / 377 mm |
| One Tray Oversized High Capacity Feeder | 38.9 in. / 988 mm | 30.0 in. / 762 mm | 39.1 in. / 992 mm |
| Two Tray Oversized High Capacity Feeder | 38.9 in. / 988 mm | 30.0 in. / 762 mm | 39.1 in. / 992 mm |
| Certifications | | | |
| | WHQL certification (depending on print server / controller selected) Citrix MEDITECH SAP Common Criteria Certification ENERGY STAR® Environmental Choice EPEAT GS Mark NOM EAC/GOST To view the latest list of certifications, go to www.xerox.com/OfficeCertifications . | | |
| Graphic Arts Credentials | | | |
| | FOGRA certification* PANTONE® Matching System* PANTONE GOE* PANTONE PLUS* Adobe® PDF Print Engine* Adobe® PostScript® 3™ (certified) IDEAlliance Digital Press Certified to GRACol® specifications *requires an additional Print Server option | | |
| Paper Handling | | | |
| Single-pass Automatic Document Feeder | | | |
| Capacity³ | 250 sheets of plain paper – 20 lb. / 75 gsm | | |
| Speed | Up to 200 ipm colour / 200 ipm black and white (2-sided, 8.5 x 11 in. / A4) | | |
| Paper Sizes | Custom sizes; 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3 | | |
| Weights | 16 to 53 lb. bond / 60 to 200 gsm | | |
| Bypass Tray | | | |
| Capacity³ | Up to 250 sheets | | |
| Sizes | Custom sizes: 4 x 6 in. to 13 x 19 in. / 102 x 152 mm to 330.2 x 482.6 mm (A5 to SRA3) | | |
| Weights | 16 lb. bond to 110 lb. cover / 60 to 300 gsm (60 to 300 gsm uncoated; 106 to 300 gsm coated) | | |
| Envelope Capacity | 30 to 50 envelopes | | |
| Envelope Sizes | #10 Commercial, Monarch (including custom size), C4, C5 (Available as Tray 5. Paper Size Default within tools) run flap open at the trail edge) Custom sizes: 7.5 x 6.7 in. to 9.45 x 6.81 in. / 190 x 170 mm to 240 x 173 mm Digital Laser envelopes recommended | | |
| Envelope Weights | 75 to 90 gsm | | |
| Trays 1 to 4 | | | |
| Capacity³ | Tray 1: 500 sheets Tray 2: 500 sheets Tray 3: 870 sheets Tray 4: 1,140 sheets | | |
| Sizes | Tray 1: 5.5 x 8.5 in. to 12 x 18 in. / A5 to SRA3 Tray 2: 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3 Tray 3: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4 Tray 4: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4 | | |
| Weights | Trays 1 and 2: 16 lb. bond to 96 lb. cover / 60 to 256 gsm (60 to 256 gsm uncoated; 106 to 220 gsm coated) Trays 3 and 4: 16 lb. bond to 96 lb. cover / 60 to 256 gsm (60 to 256 gsm uncoated; 106 to 220 gsm coated) | | |
| Optional High Capacity Feeder (HCF) | | | |
| Capacity³ | 2,000 sheets | | |
| Sizes | 7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4) | | |
| Weights | 16 lb. bond to 80 lb. cover / 60 to 220 gsm (uncoated and coated) | | |
| Optional Oversized High Capacity Feeder (OHCF) – 1 or 2 Tray Options | | | |
| Capacity³ | 1 Tray OHCF: 2,000 sheets plus Storage Cabinet 2 Tray OHCF: 4,000 sheets | | |

Xerox® Colour C60/C70 Printer

| | |
|--|--|
| Sizes | 1 Tray OHCF: 7.2 x 10 in. / 182 x 250 mm (B5) to 13 x 19.2 in. / 330 x 488 mm (SRA3) 2 Tray OHCF: 4 x 6 in. / 102 x 152 mm to 13 x 19.2 in. / 330 x 488 mm (SRA3) |
| Weights | 16 lb. bond to 110 lb. cover / 60 to 300 gsm (uncoated and coated) |
| Total Capacity | |
| Standard Capacity | 3,260 sheets (includes Bypass Tray and Trays 1-4) |
| Maximum Capacity | 7,260 sheets (includes Bypass Tray, Trays 1-4 and Two-tray Oversized High Capacity Feeder) |
| Automatic Two-Sided | <ul style="list-style-type: none"> • 94 lb. cover / 256 gsm auto duplex • 110 lb. cover / 300 gsm manual duplex for all stocks from bypass trays and optional Oversized High Capacity Feeder |
| Finishing | |
| Offset Catch Tray | |
| Capacity³ | 500-sheet stacking |
| Optional BR Finisher (Requires Vertical Transport Kit) | |
| Capacity³ | Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) 11x17 in., 8.5 x 14 in., A3 or 200 sets (single-position staple) 8.5 x 11 in. / A4 |
| Sizes | 4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling 5.5 x 8.5 in. / A5 output to top tray; punch and offset |
| Weights | 16 lb. bond to 110 lb. cover / 64 to 300 gsm (coated and uncoated) |
| Stapling | Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported |
| Hole Punch North America: Europe: | 2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional) |
| Optional BR Booklet Maker Finisher (Requires Vertical Transport Kit) | |
| Capacity³ | Offsetting Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in. / A3 / SRA3 |
| Sizes | 4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling 5.5 x 8.5 in. / A5 output to top tray; punch and offset |
| Weights | 16 lb. bond to 110 lb. cover / 64 to 300 gsm (coated and uncoated) |
| Stapling | Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported |
| Hole Punch North America: Europe: | 2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional) |
| Booklet Maker | Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, 12 x 18 in., SRA3 supported |
| Optional C Fold / Z Fold Unit (Optional with BR Finisher and BR Booklet Maker Finisher) | |
| Types | C Fold, Z Fold and Z Half Fold |
| Capacity³ | 40 sheets |
| Sizes | C Fold and Z Fold: Letter – 8.5 x 11 in. / A4 SEF only Z Half Fold: Tabloid – 11 x 17 in. / A3 only |
| Weights | 16 lb. to 24 lb. bond / 64 to 90 gsm |
| Output Tray | Envelope Tray: C Fold, Z Fold and Tri-fold Stacker Tray or Top Tray: Z Half Fold |
| Optional Standard Finisher (requires Interface Module) | |
| Capacity | Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 3,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 |
| Sizes | 4 x 6 in. to 13 x 19 in. / A6 to SRA3 |
| Weights | 18 lb. bond to 110 lb. cover / 64 to 300 gsm |
| Multiposition Stapling | Up to 100 sheets of 20 lb. bond / 80 gsm |

Xerox® Colour C60/C70 Printer

| | |
|--|--|
| Hole-punching North America: Europe: | 2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional) |
| Interposing Capacity Capacity: Sizes: Weights: | 200 sheets of 128 gsm 5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. / A3, A4, B4, B5 18 lb. bond to 80 lb. cover / 64 to 220 gsm |
| Decurling | Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings |
| Optional Standard Finisher with Booklet Maker (requires Interface Module) | |
| Capacity | Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 2,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 |
| Sizes | 4 x 6 in. to 13 x 19 in. / A6 to SRA3 |
| Weights | 18 lb. bond to 110 lb. cover / 64 to 300 gsm |
| Multiposition Stapling | Up to 100 sheets of 20 lb. bond / 80 gsm |
| Hole-punching North America: Europe: | 2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional) |
| Interposing Capacity Capacity: Sizes: Weights: | 200 sheets of 128 gsm 5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. / A3, A4, B4, B5 18 lb. bond to 80 lb. cover / 64 to 220 gsm |
| Decurling | Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings |
| Booklet Making Capacity | Saddle-stitch 2 to 25 sheets of 79 gsm (uncoated) Bi-fold up to 5 sheets 8.5 x 11 in., 8.5 x 13 in., 8.5 x 14 in., 9 x 11 in., 11 x 15 in., 11 x 17 in., 12 x 18 in., 13 x 18 in. / A4, B4, A3, SRA3 |
| Optional GBC® AdvancedPunch (Optional with Standard Finisher – requires Interface Module) | |
| Punch Configuration Sizes | 8.5 x 11 in. / 216 x 279 mm to 13 x 19.2 in. / 330 x 488 mm |
| Weights | 20 lb. bond to 80 lb. cover / 75 to 216 gsm (uncoated and coated) Wide selection of slide-in / slide-out GBC punch die sets available |
| Optional GBC® AdvancedPunch PRO (Optional with Standard Finisher with or without Booklet Maker – requires Interface Module) | |
| Punch Configuration Sizes | 5.5 x 8.5 in. / 148 x 210 mm (A5) LEF to 13 x 19.2 in. / 330 x 488 mm (SRA3) SEF |
| Weights | 20 lb. bond to 110 lb. cover / 75 to 300 gsm (uncoated); 28 lb. bond to 110 lb. cover / 106 to 300 gsm (coated) Wide selection of slide-in / slide-out GBC punch die sets available |
| Optional Xerox® SquareFold® Trimmer Module (Optional with Standard Finisher – requires Interface Module) | |
| Capacity | 5 to 20-sheet booklets (up to 80 imaged sides) at 24 lb. / 90 gsm 5 to 25-sheet booklets (up to 100 imaged sides) at 20 lb. / 80 gsm |
| Sizes | Custom sizes: 8.5 x 11 in. to 13 x 18 in. / A4 to SRA3 |
| Weights | 18 lb. bond to 110 lb. cover / 64 to 300 gsm |
| Convenience Stapler | |
| Capacity | 50 sheets (24 lb. / 90 gsm media) |
| Print | |
| Print Resolution | Up to 2400 x 2400 dpi |
| Line Screens | 600, 300, 200 and 150 Clustered Dot, 200 Rotated Line Screen (depending on print server / controller selected) |
| Registration | <ul style="list-style-type: none"> Advanced registration technology for tighter control Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity (Available on all configurations) + 1.2 mm front to back registration |
| First-print-out Time | PS- A4 LEF Simplex Colour 10.4 seconds / Black and white 8.5 seconds |

Xerox® Colour C60/C70 Printer

| | |
|--|---|
| Print Features | <ul style="list-style-type: none"> • A true multifunction product – print, copy, fax and scan, including scan to PC, USB or email, and mobile printing • Benchmark image quality with 2400 x 2400 dpi resolution and EA low melt toner for a smooth, offset-like finish • Makes mobile printing simpler and more convenient • Expansive media range lets you print everything from postcards to posters, both coated and uncoated stock, up to 300 gsm • Xerox Extensible Interface Platform® (EIP) allows you to connect to third-party software solutions that you can access from the touch-screen of the device • Your choice of servers to best fit your environment: <ul style="list-style-type: none"> – Xerox® Integrated Colour Server for the Xerox® Colour C60/C70 Printer – Xerox® EX-i C60/C70 Print Server Powered by Fiery® – Xerox® FreeFlow® Print Server Integrated for the Xerox® Colour C60/C70 Printer – Xerox® EX C60/C70 Print Server Powered by Fiery® • Inline finishing options offer a professional polish with stapling, hole-punching, folding and booklet making for presentations, brochures, reports and newsletters • Be secure with integrated security features such as IP filtering, image overwrite, secure print, encrypted Scan to Email, authentication and IPv6 support |
| Xerox® Mobile Express Driver® | Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favourite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. |
| Xerox® Global Print Driver® | A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. |
| Print Solutions | |
| Xerox® Mobile Print Cloud (Optional) | Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it. |
| Xerox® Mobile Print Solution (Optional) | Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment. |
| Copy | |
| First-copy-out Time From the Platen: From the DADF: | As fast as 7.8 seconds colour / 5.1 seconds black and white As fast as 9.6 seconds colour / 5.3 seconds black and white |
| Warm Up Time | 90 seconds (from cold powered down to Ready Copy) |
| Digital Imaging | Auto colour Auto rotation Image shift Edge erase Auto centreing Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Colour balance, colour shift and saturation |
| Reduce / Enlarge | Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable per centages |

Xerox® Colour C60/C70 Printer

| | |
|--|--|
| Special Features | <p>Auto paper select Auto reduction/enlargement to fit selected paper size Auto tray switching Automatic job recovery Auto colour selection Area Designation Poster mode Annotation Single/Dual colour Booklet creation Multi-up – 2, 4 or 8 up Repeat Image Negative image Mirror image Covers insertion (front only, front and back, back only, blank or printed) Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Job interrupt Book copying Sample job Mixed-size originals Sheet Insert Stamping 2-in-1 X Y Zoom Zoom Range 25 to 400 % Margin Shift Photo Mode Poster Mode Preset Reduce / Enlarge Programme Ahead Covers Erase, Image Repeat, Image Rotate Interrupt Job Build Job Programme</p> |
| Scan | |
| Concurrency | Scan while printing or while it is transferring scan to network or fax jobs |
| Scan Features | <p>Mixed size originals Edge erase Reduction/enlargement Fit to size Scan Build Job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional) Preview scan job</p> |
| Input Speed | Up to 200 images per minute colour and black and white |
| Resolution | <p>600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi</p> |
| Maximum Scan Area | Originals up to 11 x 17 in. / A3 |
| Network Print Services | <p>Novell NDPS Novell Pserver / NDS Port 9100 RFC 1179 (LPR) Print to Mailbox and Release</p> |
| File Formats | <p>PDF Image Only PDF (Searchable) PDF (Linearised) PDF (A-1 Level A) TIFF V6 JFIF XPS</p> |
| Document Management Fields (Metadata) | <p>One to six user-programmable metadata fields per scan job Customised fields viewed on user interface Variable data entered using virtual keyboard</p> |

Xerox® Colour C60/C70 Printer

| | |
|---|---|
| Scan Features | <p>Scan to Home Scan to Desktop WIA Scan to Desktop TWAIN Scan to Mailbox Scan to FTP Scan to sFTP Scan via NDS Scan via SMB Scan via HTTP Scan via HTTPS Scan to USB Storage Device Scan to Remote Printer Scan to Fax Server Scan to Multiple Destinations Scan to Documentum Scan to DocuShare Scan to Domino Scan to Hummingbird Scan to Interwoven WorkSite Scan to Live Link Enterprise Server Scan to Microsoft Dynamics GP Scan to MS Exchange web folder Scan to Microsoft SharePoint Scan to SharePoint Portal Server Scan to Thompson ProLaw Scan to Tower TRIM Scan to Web URL Scan to Microsoft Network Folder Scan to Exact e-Synergy</p> |
| Supported Scan Destinations (Standard) | Scan to Email, Scan to Folder, to PC, to Mailbox (private and public), Scan to USB, FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbnail Preview |
| Scan to Email Features | <p>Colour scanning, Auto Colour, Greyscale, Black and white Direct document email from device Manual or directory Exchange / Notes / LDAP address searching Signing and encryption Email over SSL Preview scan job</p> |
| Authentication | <p>SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication)</p> |
| Fax (Optional) – One or Three Line Fax Options | |
| Compatibility | Colour, Auto Colour, Black and white |
| Maximum Scan Area | 11 x 17 SEF |
| Fax Send Features | <p>iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination</p> |
| Fax Print Features | <p>Print from USB Storage Device Media Print Unicode Printing</p> |
| Fax Features | <p>iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination</p> |
| Device Management | |
| Xerox® CentreWare® Internet Services – Integrated Web Pages Provided by the Device | |
| Device Status | <p>Web server embedded in Network Controller:</p> <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts |
| Job Submission | <p>Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)</p> |
| Device Administration | Allows simple, remote installation setting of configuration options and management of the device |

Xerox® Colour C60/C70 Printer

| | |
|--|---|
| Browsers | Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12 |
| Support | Install print / scan drivers and online support available via web page |
| Languages Supported | International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese |
| Remote Services | |
| Xerox® MeterAssistant® | Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time. |
| Xerox® SuppliesAssistant® | Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory. |
| Xerox® MaintenanceAssistant | Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting / repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime. |
| Security | |
| Features | Secure Print IPsec HTTPS (SSL) Embedded Fax Port Blocking IPv6 Support IPv4 and IPv6 Environments OS Security Updates 802.1X Support (IEEE Standard) Secure Login Network Authentication IP Address Restriction Job Audit Tray Data Encryption 128-bit AES Encryption 256-bit AES Encryption Image Overwrite Common Criteria Certification |
| Print Server | |
| Xerox® Integrated Colour Server for the Xerox® Colour C60/C70 Printer | |
| Processor | 1.0 GHz |
| Memory | 4 GB system plus 1 GB page memory |
| System Disk | 320 GB Hard Disk Drive |
| Display | 10.4 in. colour touchscreen flat-panel |
| Device Operating System | VxWorks |
| PDLs Page Description Languages | Adobe® PostScript® 3™ PDF PCL® 5c, 6 XML Paper Specification (XPS®) (optional) |
| Operating Systems | Windows® XP Windows Server 2003 (32- and 64-bit) Windows Server 2008 (32- and 64-bit) Windows Server 2012 Windows Vista (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Mac OS® 10.7 and above Solaris® 9, 10 HP-UX® 11 v2 IBM® AIX® 5 Red Hat® Fecora® Core 15-17 Red Hat Enterprise 4 and 5 openSUSE® 11 and 12 Ubuntu® Unix® |

Xerox® Colour C60/C70 Printer

| | |
|---|--|
| Print Drivers Supported | <p>Please refer to www.xerox.com/support for specifics. As new operating system versions are added, support is also added for Xerox® C60/C70 Colour Printer. Also note that there is more than one print driver based on the configuration purchased (e.g. digital front ends, Xerox® Global Print Driver)</p> <p>Windows Vista, 32-bit, SP2 Windows Vista, 64-bit, SP2 Windows 7, 32-bit Windows 7, 64-bit Windows 8, 32-bit Windows 8, 64-bit Windows 8.1 Update 1, 32-bit Windows 8.1 Update 1, 64-bit Windows 10, 32-bit Windows 10, 64-bit Windows Server 2008, 32-bit Windows Server 2008, 64-bit Windows Server 2008 R2, 64-bit Windows Server 2012, 64-bit Windows Server 2012 R2, 64-bit Citrix® XenApp 5.0, 6.0 and 6.5 Citrix XenDesktop 7.6 Novell Netware 6.x: NDPS, NDS, iPrint Novell Open Enterprise Server Cluster: Windows Server 2008 32- and 64-bit, 2008 R2, 64-bit; Server 2012 64-bit; 2012 R2 64-bit Xerox® Mobile Express Driver® XPS Print Driver Xerox® Global Print Driver®</p> |
| Features | <ul style="list-style-type: none"> • Automatic two-sided • Bi-directional Print Drivers provide device and job status • Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print) • Secure print • Delay print • Embedded Web server for remote control/monitor/setup • Enhanced Gloss • Sample set • Booklet creation • Cover selection • Paper selection by attribute • N-up • Watermarks • Banner sheets • Fit to new paper size • Output tray selection • Print calibration • Print from USB <p>Plus more!</p> |
| Connectivity | Ethernet interface (10 MBTX / sec, 100 MBTX / sec, 1000 MBTX / sec) |
| | For more information, go to www.xerox.com/C70IntegratedColorServer . |
| Additional Print Server Options | |
| Xerox® EX-i C60/C70 Print Server Powered by Fiery® | |
| Hardware/Platform | <ul style="list-style-type: none"> • Fiery® FS200 software • Intel Pentium G1820 Processor (2.7 GHz) • Performance optimized by proprietary combination of EFI Technology, VX600 ASIC and software |
| Memory | 2 GB |
| Hard Drive | 500 GB |
| Server Operating System | Linux® |
| Print Languages (PDL) | Adobe® PostScript® 3™ (v3019), PCL 6C (emulation), Adobe Acrobat 9 |
| Features | <ul style="list-style-type: none"> • Productivity starts with a fast RIP. The Integrated Fiery Colour Server enables you to print large and/or complex Microsoft® Office® documents, PowerPoint® files and colour-critical PDFs accurately and quickly. • Simplify and streamline your workflow. Automate job submission of repetitive job types to achieve productive, error-free workflows with Hot Folders and Virtual Printers. • Take advantage of commonly used Fiery presets to save time when submitting jobs. With Fiery server technology, even novice users can perform complex jobs using the pre-set drivers configured for the task. • Get the colour right. Produce precise, exact colour from all applications, platforms and formats with Fiery colour management tools. • Turn up the impact with variable information. Customise your output to a specific audience with varying text, photos and graphics with the Integrated Fiery Colour Server's basic variable data printing capabilities. |
| Connectivity | Direct Connection (Single IP) |

Xerox® Colour C60/C70 Printer

| | |
|---|--|
| Fiery Productivity Package Option | <ul style="list-style-type: none"> • Fiery JDF • Graphic arts filters for Hot Folders • Fiery Image Enhance Visual Editor • Fiery ImageViewer • Postflight report • Control bar • Configurable auto trapping • Paper simulation |
| | For more information, go to www.xerox.com/C70EXiFieryColorServer . |
| Xerox® FreeFlow® Print Server Integrated for the Xerox® Colour C60/C70 Printer | |
| Processor | Intel® Dual Core Pentium G3420 Processor |
| Memory (ESS) | 16 GB |
| System Disk | 1 TB 7200 SATA or equal |
| Print Languages (PDL) | <p>Adobe® PostScript® Level 1, 2, 3 PDF up to version 1.7 (Acrobat XI), including PDF/VT-1 specification version 1.1, PDF/X-1a, PDF/X-3 and PDF/X-4 EPS TIFF v6, native and multi-page (TIFF-IT is not supported) Xerox® Variable-data Intelligent PostScript Printware (VIPPP) (license required) Jobs submitted from Xerox® FreeFlow® Workflow Offerings Compatible with Xerox® FreeFlow Variable Information Suite Version 9.0 JPEG Microsoft Word and PowerPoint documents XPS IPDS (license required) PPML</p> <p>The following file formats are not supported: ASCII PCL</p> |
| Features | <p>Simple</p> <ul style="list-style-type: none"> • Windows 7 platform for a familiar experience • Integrated / Bustled setup. Perfect for small footprint and quick and easy site setups • Accepts Native Microsoft Office® files for Direct Print (from walk-up USB PowerPoint®, for example) <p>Productive</p> <ul style="list-style-type: none"> • All the advantages of a Xerox Production workflow – delivered in a value-oriented solution • Streamlined drag/drop submission from tablets and more <p>Powerful</p> <ul style="list-style-type: none"> • Bring the power of Xerox® patented RIP technology in a value oriented solution • Latest direct Adobe PDF Print Engine and GC credentials included • Includes Variable Data Print / Colour Management / Production Workflows <p>Tints and Highlights fine-tuned for better accuracy Duotone, Tri-tone and Quad-tone support</p> <ul style="list-style-type: none"> • Spot Colour Editor • Calibration and Profiling with XRite i1, Pro2 (optional) • Job Accounting reporting • Custom Paper Catalogue • IPDS and PPML • Faster job programming with 'Select by Tray' job programming • Simplified and intuitive job recovery • Enhanced imposition |
| Connectivity | Direct Connection (Single IP) |
| | For more information, go to www.xerox.com/C70FreeflowPrintServer . |
| Xerox® EX C60/C70 Print Server Powered by Fiery® | |
| Processor | Intel® Core™ i5-4570S Processor 2.9 up to 3.60 GHz with Turbo, Quad Core Performance optimised by proprietary combination of EFI technology, VX600 ASIC and software |
| Memory (ESS) | 4 GB |
| System Disk | 1 TB |
| Print Languages (PDL) | <p>Adobe PostScript® Level 1, 2, 3; PDF/X-1a, 3 and 4; EPS; Adobe Acrobat® 9.1, Native PDF 1.3, 1.4, 1.5, 1.6 and 1.7; CT/LW; TIFF, TIFF/IT, DCS2, JPEG Microsoft Native Formats (DOC, XLS, PUB, PPT) enabled through Fiery Hot Folders feature EFI™ FreeForm 1, and FreeForm 2 VDP</p> |

Xerox® Colour C60/C70 Printer

| | |
|-----------------|--|
| Features | <ul style="list-style-type: none"> • Job-based Calibration Integration <ul style="list-style-type: none"> – Fiery Spot-On finds the best match of PANTONE®, PANTONE Series, RGB, CMYK, L*a*b* and Spot Colours – Colour Modes for professional proofing and enhanced production colour requirements – Maximum print density • Fiery Graphic Arts Package, Premium Edition (optional) provides expert tools for preflighting and troubleshooting jobs • Fiery Colour Profiler Suite (optional) creates, verifies and edits color profiles with a single profiling solution • Fiery technology increases your profits by delivering high-impact documents with vibrant images and colour that exceed your customers' expectations and also meets tight turnaround times and allows you to do more work by automating manual tasks and removing bottlenecks that slow down production. • Fiery technology increases your profits by delivering high-impact documents with vibrant images and colour that exceed your customers' expectations and also meets tight turnaround times and allows you to do more work by automating manual tasks and removing bottlenecks that slow down production. • With Fiery technology, you can produce effective marketing pieces with the widest range of output options, including automatic identification of job elements such as text, images and spot colours. This feature also eliminates the need to re-programme jobs, making the process simple and quick. It is ideal for producing powerful marketing materials, personalised communications and packaging and photo publishing applications. • Fiery ColourWise gives high-quality colour out-of-the-box and integrates the essential components of Fiery Graphic Arts Package, Premium Edition, Fiery Spot-On and the Fiery Colour Profiler Suite to control and manage colour throughout your workflow. • The Fiery Command WorkStation increases your production and reduces errors and waste by centralising job management via its intuitive user interface. Simplify your labour-intensive document composition and imposition tasks even more by using Fiery SeeSequence Impose and Compose's intuitive interface. • Fiery JDF technology connects EFI solutions and Fiery-enabled solutions, so you can move job information through your system faster and more efficiently. By supporting the Adobe PDF Print Engine, Fiery servers also offer a native end-to-end PDF workflow, therefore improving the consistency and flexibility of your printed output from design to print. • Using Fiery servers and Fiery Command Workstation, you get a new level of integration for process and profit improvement, including seamless connectivity to Xerox® FreeFlow® for workflow automation. |
|-----------------|--|

| | |
|---------------------|--|
| Connectivity | Direct Connection (Single IP), Network Switch, (Dual IP) |
| | For more information, go to www.xerox.com/C70EXPrintServer . |

| Supplies | Description | Yield | Part Number |
|-----------------------------------|---|----------------------------------|-------------|
| Customer Replaceable Items | | | |
| Toner Cartridges (Metered) | Black | 30,000 pages ⁴ | 006R01521 |
| | Cyan | 34,000 pages ⁴ | 006R01524 |
| | Magenta | 32,000 pages ⁴ | 006R01523 |
| | Yellow | 34,000 pages ⁴ | 006R01522 |
| Toner Cartridges (Sold) | Black | 30,000 pages ⁴ | 006R01659 |
| | Cyan | 34,000 pages ⁴ | 006R01660 |
| | Magenta | 32,000 pages ⁴ | 006R01661 |
| | Yellow | 34,000 pages ⁴ | 006R01662 |
| Black Drum Cartridge | 1 Cartridge | 190,000 pages ⁴ | 013R00663 |
| Colour Drum Cartridge | 1 Cartridge per Colour | 85,000 pages ⁴ | 013R00664 |
| Charge Corotron | For Black Drum | 190,000 pages ⁴ | 013R00650 |
| Fuser | 110V | 200,000 pages ⁴ | 008R13102 |
| | 220V | 200,000 pages ⁴ | 008R13065 |
| Waste Toner Container | 1 Cartridge | 50,000 pages ⁴ | 008R12990 |
| Feed Roll Kits | 1 Assembly | 300,000 pages ⁴ | 008R13169 |
| Staple Cartridges | For BR Finisher and Convenience Stapler (1 cartridge per carton) | 5,000 each cartridge | 008R12964 |
| | For BR Booklet Maker Finisher (4 cartridges per carton) | 5,000 each cartridge | 008R13177 |
| | Staple Cartridge and Waste Container for Standard Finisher | 5,000 each cartridge | 008R13041 |
| Staple Refills | For BR Finisher, BR Booklet Maker Finisher and Convenience Stapler (3 refills per carton) | 5,000 each refill (15,000 total) | 008R12941 |

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput.

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ Approximate pages. Declared Yield based on 5 page job size, 30% colour and 70% Black and white ratio, using letter / A4 media. Yield will vary based on media size, image area coverage, job run length, media orientation and usage patterns.

To view a product video, visit www.xerox.com. Build and configure your own Xerox® Colour C60/C70 Printer at www.buildyourownxerox.com.

