



# Xerox® Primelink C9065/C9070 Printer - Europe Paper and Specialty Media Guide

For your convenience, this guide contains the Recommended Media List

The **Recommended Media List** contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance.

Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List for a specific Xerox® printer or digital press will give optimum performance. This is how Antalis can offer 100% Performance Guaranteed.

Learn more at [www.performance-guaranteed.com](http://www.performance-guaranteed.com)

## General information:

All media is listed by product, machine run mode, Image Quality System Setting, weight (standard gsm), re-order number, size and tray runability. The additional information column is for hints and tips on how to run certain media applications. Media recommendations made in this publication are based on qualification tests\* conducted using standard test images with moderate to heavy image area coverage. Test duration for each product/media type is based on the suggested machine monthly copy/print volume. Test machines are maintained within specifications defined by user documentation.

\* Testing environment Temperature 23 degrees C ±2, Relative Humidity 20-40%.

\*Machine reliability specifications may be affected by increased usage of the Heavyweight 1, Heavyweight 2, Heavyweight 3, Heavyweight 4, Coated 1, Coated 2 and Coated 3 modes. In addition, variances in machine reliability may occur due to extended use of some media types. Your Xerox service representative can advise you on using Heavyweight 1, Heavyweight 2, Heavyweight 3, Heavyweight 4, Coated 1, Coated 2 and Coated 3 modes or special application media types for long duration copy/print runs.

Auto-duplexing of Coated 1, Coated 2 and Heavyweight 2 media may cause increased jams. When this occurs, use manual duplexing. Increased jams may occur when Output Format is Auto or Face Down. Use Face Up output format if this occurs. OHCF is strongly recommended when feeding Heavyweight 2, Heavyweight 3, and Coated 2 media.

Environmental conditions may require that coated paper be fed one at a time through Tray 5 (Bypass). Relative Humidity greater than 40% could cause multifeeds. Oversize High Capacity Feeder Option (OHCF) prevents multifeeds for Coated 1, Coated 2 and Coated 3 modes when Relative Humidity is greater than 40%. Output may require removal at 25 sheets in the tray when not using a finisher.

Oversize High Capacity Feeder Option is recommended for optimal feeding performance of Coated 2 Side (C2S) media. Coated 1, Coated 2 and Coated 3 modes prevent multifeeds, especially in high humidity environments. Coated 1 Side (C1S) media has best feeding performance in high humidity when using Coated 2 or Coated 3 mode. In low humidity environment, Heavyweight 2 or Heavyweight 3 mode may yield better image quality.

For Manual Duplex, it may help to manually remove curl after printing side1 before placing sheets into feeder for side 2.

Customers should inquire directly of their paper distributor or manufacturer for any guarantees they may offer. When purchasing a particular media product for the first time, customers are advised to purchase small quantities to ensure their expectations are met.



©2019 Antalis. All rights reserved. Xerox®, Primelink C9065/C9070, Xerox and Design® are trademarks of Xerox Corporation in the United States and other countries and are used under license from Xerox Corporation. Antalis is a trademark licensee of Xerox Corporation.

## Xerox® Primelink C9065/C9070 Printer - Recommended Media List - Europe - November 2019

The Recommended Media List contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance. Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List for a specific Xerox® printer or digital press will give optimum performance. This is how Antalis can offer 100% Performance Guaranteed.

- Plain/Recycled (64-105gsm)
- Transparency
- Heavyweight 1 (106 - 176gsm)
- Heavyweight 2 (177 - 220gsm)
- Heavyweight 3/4 (221 - 300gsm)
- Transfer Paper
- Label
- Paper Types are selected within System Settings
- Coated 1 (106 - 150gsm)
- Coated 2 (151 - 220gsm)
- Coated 3 (221 - 300gsm)

A=Auto Duplex  
M=Manual Duplex  
S=Simplex Only

Media	Paper Type	Image Quality System Setting	Weight	Re-Order #	Type	Size	Trays 1 - 4				Tray 6-7		Tray 5 (Bypass)	
							1	2	3	4	HCF	OHCF		5
Xerox® Premier	Plain	Plain B	80 gsm	003R91720	A4	A4	A	A	A	A	A	A	A	
				003R91721			A	A				A	A	
	Plain	Plain C	90 gsm	003R91854	A4	A4	A	A	A	A	A	A	A	
				003R91853	A3	A	A				A	A		
On Light Production Finisher, do not staple more than 70 sheets per set.														
Xerox® Business	Plain	Plain B	80 gsm	003R91820	A4	A4	A	A	A	A	A	A	A	
				003R91821	A3	A3	A	A			A	A	A	
Xerox® Recycled Supreme 100%	Recycled	Recycled B	80 gsm	003R95860	A4	A4	A	A	A	A	A	A	A	
				003R95861	A3	A3	A	A			A	A	A	
On Light Production Finisher, do not staple more than 70 sheets per set.														
Xerox® Colour Impressions	Plain	Plain B	80 gsm	003R97661	A4	A4	A	A	A	A	A	A	A	
				003R97662	A3	A	A				A	A		
	Plain	Plain C	90 gsm	003R97663	A4	A4	A	A	A	A	A	A	A	
				003R97664	A3	A	A				A	A		
				003R97665	SRA3	SRA3					A	A	A	
	Plain	Plain D	100 gsm	003R97666	A4	A4	A	A	A	A	A	A	A	A
				003R97667	A3	A	A				A	A		
				003R97668	SRA3	SRA3					A	A	A	
	Heavyweight 1	HW1A	120gsm	003R98685	A4	A4	A	A				A	A	A
				003R97669	A3	A	A				A	A		
			003R97670	SRA3	SRA3					A	A	A		
Heavyweight 1	HW1C	160gsm	003R98007	A4	A4	A	A				A	A	A	
			003R98008	A3	A	A				A	A			
			003R98686	SRA3	SRA3					A	A	A		
Heavyweight 3		250 gsm	003R98687	A4	A4						S	M	M	
			003R97671	A3	A3							S	M	M
			003R97672	SRA3	SRA3							S	M	M

## Xerox® Primelink C9065/C9070 Printer - Recommended Media List - Europe - November 2019

The Recommended Media List contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance. Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List for a specific Xerox® printer or digital press will give optimum performance. This is how Antalis can offer 100% Performance Guaranteed.

- Plain/Recycled (64-105gsm)
- Transparency
- Heavyweight 1 (106 - 176gsm)
- Heavyweight 2 (177 - 220gsm)
- Heavyweight 3/4 (221 - 300gsm)
- Transfer Paper
- Label
- Paper Types are selected within System Settings
- Coated 1 (106 - 150gsm)
- Coated 2 (151 - 220gsm)
- Coated 3 (221 - 300gsm)

A=Auto Duplex  
M=Manual Duplex  
S=Simplex Only

Media	Paper Type	Image Quality System Setting	Weight	Re-Order #	Type	Size	Trays 1 - 4				Tray 6-7		Tray 5 (Bypass)	
							1	2	3	4	HCF	OHCF	5	
Xerox® Colotech+ (Gold Label)	Plain	Plain C	90 gsm	003R99000	A4	A4	A	A	A	A	A	A	A	On Light Production Finisher, do not staple more than 70 sheets per set.
				003R99001			A	A				A	A	
				003R99002								A	A	
	Plain	Plain D	100 gsm	003R99004	A4	A4	A	A	A	A	A	A	A	On Light Production Finisher, do not staple more than 70 sheets per set.
				003R99006			A	A				A	A	
				003R99007								A	A	
	Heavyweight 1	HW1A	120gsm	003R99009	A4	A4	A	A	A	A	A	A	A	
				003R99010			A	A				A	A	
				003R99011								A	A	
	Heavyweight 1	HW1C	160gsm	003R99014	A4	A4	A	A	A	A	A	A	A	
				003R99015			A	A				A	A	
				003R99016								A	A	
Heavyweight 2		200 gsm	003R99018	A4	A4	A <sup>1</sup>	A <sup>1</sup>	S	S	A <sup>1</sup>	A	A	<sup>1</sup> Auto-duplex is supported from Printer System Software version 60.20.11, otherwise Simplex Only.	
			003R99019			A <sup>1</sup>	A <sup>1</sup>				A	A		
			003R99020			A <sup>1</sup>					A	A		
Heavyweight 2		220 gsm	003R99022	A4	A4	A <sup>1</sup>	A <sup>1</sup>	S	S	A <sup>1</sup>	A	A	Increased jams may occur when auto-duplexing. Use Manual Duplexing when this occurs. Increased jams may occur when Output Format is Auto or Face Down. Use Face Up output format if this occurs.	
			003R99023			A <sup>1</sup>	A <sup>1</sup>				A	A		
			003R99024			A <sup>1</sup>					A	A		
Heavyweight 3		250 gsm	003R99026	A4	A4	A <sup>1</sup>	A <sup>1</sup>	S	S	A <sup>1</sup>	A <sup>1</sup>	A <sup>1</sup>	<sup>1</sup> Auto-duplex is supported from Printer System Software version 60.20.11, otherwise Simplex Only. Increased jams may occur when auto-duplexing. Use Manual Duplexing when this occurs. Increased jams may occur when Output Format is Auto or Face Down. Use Face Up output format if this occurs.	
			003R99027			A <sup>1</sup>	A <sup>1</sup>				A <sup>1</sup>	A <sup>1</sup>		
			003R99028								A <sup>1</sup>	A <sup>1</sup>		
Heavyweight 4		280 gsm	003R99030	A4	A4						S	M	Image Quality defects near the trail edge of output may require adjustment using Adjust Image Transfer within Maintenance feature of Tools.	
			003R99031									S		M
			003R99032									S		M
Heavyweight 4		300 gsm	003R99034	A4	A4						S	M	Only output to OTC and Top Tray for Business Ready and Production Ready Finisher. Image Quality defects near the trail edge of output may require adjustment using Adjust Image Transfer within Maintenance feature of tools.	
			003R99035									S		M
			003R99036									S		M
Heavyweight 4		350 gsm	003R99039	SRA3	SRA3						S	S		

## Xerox® Primelink C9065/C9070 Printer - Recommended Media List - Europe - November 2019

The Recommended Media List contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance. Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List for a specific Xerox® printer or digital press will give optimum performance. This is how Antalis can offer 100% Performance Guaranteed.

- Plain/Recycled (64-105gsm)
- Transparency
- Heavyweight 1 (106 - 176gsm)
- Heavyweight 2 (177 - 220gsm)
- Heavyweight 3/4 (221 - 300gsm)
- Transfer Paper
- Label
- Paper Types are selected within System Settings
- Coated 1 (106 - 150gsm)
- Coated 2 (151 - 220gsm)
- Coated 3 (221 - 300gsm)

A=Auto Duplex  
M=Manual Duplex  
S=Simplex Only

Media	Paper Type	Image Quality System Setting	Weight	Re-Order #	Type	Size	Trays 1 - 4				Tray 6-7		Tray 5 (Bypass)	
							1	2	3	4	HCF	OHCF	5	
Xerox® Colotech+ Gloss Coated	Coated 1	Coated 1A	120gsm	003R90336	A4	A4	A	A	A	A	A	A	M	
				003R90337			A	A				A	M	
				003R90338			A					A	M	
	Coated 1	Coated 1B	140gsm	003R90339	A4	A4	A	A	A	A	A	A	M	
				003R90340			A	A				A	M	
				003R90341			A					A	M	
	Coated 2	Coated 2A	170gsm	003R90342	A4	A4	S	S	S	S	S	A	M	
				003R90343			S	S				A	M	
				003R90344			S					A	M	
	Coated 2	Coated 2B	210gsm	003R90345	A4	A4	S	S	S	S	S	A	M	
003R90346				S			S				A	M		
003R90347				S							A	M		
Coated 3	Coated 3A	250gsm	003R90348	A4	A4						S	M		
			003R90349								S	M		
			003R90350								S	M		
Coated 3	Coated 3B	280gsm	003R90351	A4	A4						S	M		
			003R90352								S	M		
			003R90353								S	M		
Coated 3	Coated 3B	350gsm	003R90354	SRA3	SRA3						S	S	Only output to OTC and Top Tray for Business Ready and Production Ready Finisher. Image Quality defects near the trail edge of output may require adjustment using Adjust Image Transfer within Maintenance feature of tools.	
Xerox® Colotech+ Silk Coated	Coated 1	Coated 1A	120gsm	003R90355	A4	A4	A	A	A	A	A	A	M	
				003R90356			A	A				A	M	
				003R90357			A					A	M	
	Coated 1	Coated 1B	140gsm	003R90358	A4	A4	A	A	A	A	A	A	M	
				003R90359			A	A				A	M	
				003R90360			A					A	M	
	Coated 2	Coated 2A	170gsm	003R90361	A4	A4	S	S	S	S	S	A	M	
				003R90362			S	S				A	M	
				003R90363			S					A	M	
	Coated 2	Coated 2B	210gsm	003R90364	A4	A4	S	S	S	S	S	A	M	
003R90365				S			S				A	M		
003R90366				S							A	M		
Coated 3	Coated 3A	250gsm	003R90367	A4	A4						S	M		
			003R90368								S	M		
			003R90369								S	M		
Coated 3	Coated 3B	280gsm	003R90370	A4	A4						S	M		
			003R90371								S	M		
			003R90372								S	M		
Coated 3	Coated 3B	350gsm	003R90373	SRA3	SRA3						S	S	Only output to OTC and Top Tray for Business Ready and Production Ready Finisher. Image Quality defects near the trail edge of output may require adjustment using Adjust Image Transfer within Maintenance feature of tools.	

## Xerox® Primelink C9065/C9070 Printer - Recommended Media List - Europe - November 2019

The Recommended Media List contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance. Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List for a specific Xerox® printer or digital press will give optimum performance. This is how Antalis can offer 100% Performance Guaranteed.

- Plain/Recycled (64-105gsm)
- Transparency
- Heavyweight 1 (106 - 176gsm)
- Heavyweight 2 (177 - 220gsm)
- Heavyweight 3/4 (221 - 300gsm)
- Transfer Paper
- Label
- Paper Types are selected within System Settings
- Coated 1 (106 - 150gsm)
- Coated 2 (151 - 220gsm)
- Coated 3 (221 - 300gsm)

A=Auto Duplex  
M=Manual Duplex  
S=Simplex Only

Media	Paper Type	Image Quality System Setting	Weight	Re-Order #	Type	Size	Trays 1 - 4				Tray 6-7		Tray 5 (Bypass)	
							1	2	3	4	HCF	OHCF	S	
Xerox® Colotech+ Supergloss	Coated 1 or Coated 2 or Heavyweight 2		160gsm	003R97680		A4						S	M	Environmental conditions may require that this product be fed one sheet at a time. Gloss variation can occur from machine rolls, especially on high area coverage prints. Preference for Coated 1, Coated 2, or Heavyweight 2 may occur.
				003R97681		A3						S	M	
	Coated 2 or Heavyweight 2	Coated 2B	210gsm	003R97682		A4						S	M	Environmental conditions may require that coated paper be fed one at a time through Tray 5 (Bypass). Relative Humidity greater than 40% could cause multifeeds. Output may require removal at 25 sheets in the tray when not using a finisher. Gloss variation can occur from machine rolls, especially on high area coverage prints. Preference for Coated 2 or Heavyweight 2 may occur. OHCF prevents multifeeds better using Coated 2 when Relative Humidity is greater than 40%.
				003R97683		A3						S	M	
	Coated 3 or Heavyweight 3		250gsm	003R97684		SRA3						S	M	
				003R97686		A4						S	M	
	003R97687	A3						S	M					
	003R97688	SRA3						S	M					
	Xerox® Colour Copier/Laser Labels	Label Mode	Label 1		003R93872	1-up	A4	S	S	S	S	S		S
003R95813				4-up	A4	S	S	S	S	S		S		
003R93874				8-up	A4	S	S	S	S	S		S		
003R93875				14-up	A4	S	S	S	S	S		S		
003R95815				21-up	A4	S	S	S	S	S		S		
003R97524	24-up	A4	S	S	S	S	S		S					
Xerox® Premium Transparency Mono Xerox® Premium Transparency Colour Xerox® Premium Transparency Universal	Transparency Mode			003R98202		A4	S	S	S	S		S	S	It is not recommended to output more than 20 transparencies at a time. If your job is larger than 20 pages, use Transparency Separators feature.
			003R98205	A4	S	S	S	S		S	S			
			003R98220	A4	S	S	S	S		S	S			
Xerox® Dividers	Tab Stock 1		160gsm	003R90873 (5 bank)		A4/A4cover							S	For copy jobs, A4 size should be selected. For print jobs, A4 cover size should be selected. Tab stock functionality and work flow will vary for different Digital Front End Print/Network Controllers. Please consult the Network controller documentation when running tabs.
	Tab Stock 2		200 gsm	003R91012 (5 bank)		A4/A4cover							S	
Xerox® Universal Transfer Paper	Transfer Paper			003R93544		A4							S	Transfer Paper is not intended as sole application of machine. Limit Monthly usage. Use a machine with Offset Catch Tray rather than finishing devices if possible to minimize the risk of paper jams. While the job is printing, remove each sheet as it exits the machine to avoid stacking problems in the exit tray
			003R93545		A3								S	

## Xerox® Primelink C9065/C9070 Printer - Recommended Media List - Europe - November 2019

The Recommended Media List contains Xerox® paper and specialty media, digitally optimized, designed from stringent specifications and manufactured for optimal and constant image quality performance. Xerox® branded paper and specialty media have undergone rigorous testing by Xerox®. Any paper and print media that is featured on the Recommended Media List for a specific Xerox® printer or digital press will give optimum performance. This is how Antalis can offer 100% Performance Guaranteed.

- Plain/Recycled (64-105gsm)
- Transparency
- Heavyweight 1 (106 - 176gsm)
- Heavyweight 2 (177 - 220gsm)
- Heavyweight 3/4 (221 - 300gsm)
- Transfer Paper
- Label
- Paper Types are selected within System Settings
- Coated 1 (106 - 150gsm)
- Coated 2 (151 - 220gsm)
- Coated 3 (221 - 300gsm)

A=Auto Duplex  
M=Manual Duplex  
S=Simplex Only

Media	Paper Type	Image Quality System Setting	Weight	Re-Order #	Type	Size	Trays 1 - 4				Tray 6-7		Tray 5 (Bypass)	
							1	2	3	4	HCF	OHCF	S	
Xerox® Premium Digital Carbonless Paper (Precollated)	Plain	Plain B	80 gsm	003R99105 (White/Yellow) 003R99133 (White/Yellow)	2-Part	A4 A3	S	S	S	S	S	S	S	Use boxes labelled "Expanded Machine Compatibility" only. Carbonless Paper is not intended for extensive or exclusive usage. Limit monthly volumes. Use a machine equipped with an Offset Catch Tray rather than finishing devices if possible to minimize the risk of paper jams.
	Plain	Plain B	80 gsm	003R99108 (White/Yellow/Pink)	3-Part Straight	A4					S	S	S	
	Plain	Plain B	80 gsm	003R99109 (White/Yellow/Pink)	3-Part Reverse	A4	S	S	S	S				
	Plain	Plain B	80 gsm	003R99112 (White/Yellow/Pink/Blue)	4-Part Reverse	A4	S	S	S	S				
Xerox® Premium Digital Carbonless Paper (Singles)	Plain	Plain B	80 gsm	003R99069	CB White	A4	S	S	S	S	S	S	S	Use boxes labelled "Expanded Machine Compatibility" only. Carbonless Paper is not intended for extensive or exclusive usage. Limit monthly volumes. Use a machine equipped with an Offset Catch Tray rather than finishing devices if possible to minimize the risk of paper jams.
	Plain	Plain B	80 gsm	003R99070	CFB White	A4	S	S	S	S	S	S	S	
	Plain	Plain B	80 gsm	003R99075	CF White	A4	S	S	S	S	S	S	S	
	Plain	Plain B	80 gsm	003R99071	CFB Yellow	A4	S	S	S	S	S	S	S	
	Plain	Plain B	80 gsm	003R99077	CF Pink	A4	S	S	S	S	S	S	S	

**Xerox® Primelink C9065/C9070 Printer - Recommended Media List - Europe - November 2019**

The Xerox®CUSTOM Media List contains custom media that has been tested on the Xerox® Primelink C9065/C9070 Printer for image quality and performance. Custom media on this list are digitally optimized, designed and manufactured for performance in Xerox® digital printing equipment. Best Practices for Operation are outlined below. Customers should validate the Best Practices for Operation are acceptable for their application.

A=Auto Duplex  
S=Simplex Only  
M=Manual Duplex  
PCW=Post Consumer Waste  
ECF=Elemental Chlorine Free

Media	Mode	Image Quality System Setting	Weight	Re-Order #	Size	Trays 1 - 4				Tray 6		Tray 5 (Bypass)	Additional Information
						1	2	3	4	HCF	OHCF	5	
<b>ID Cards</b>													
Xerox® ValuPeelCard Matt 1 card/sheet	Heavyweight 2 (177-220)	HW2B	161 gsm Carrier; 301 gsm Card	003R97952	A4							A	1) Deletions may occur if imaged near the edges of the card 2) Deliver to the Offset Catch Tray 3) Load Tray 5 (MSI / Bypass) LEF (Long Edge Feed) with cards toward back of the machine (inboard) 4) Load / Stack no more than 80 Sheets at-a-time 5) Not intended for extensive / exclusive usage
Xerox® ValuPerfCard Matt 1 card/sheet	Heavyweight 2 (177-220)	HW2B	161 gsm Carrier; 251 gsm Card	003R97690	A4							A	1) Deletions may occur if imaged near the edges of the card 2) Deliver to the Offset Catch Tray 3) Load Tray 5 (MSI / Bypass) LEF (Long Edge Feed) with cards toward back of the machine (inboard) 4) Load / Stack no more than 80 Sheets at-a-time 5) Not intended for extensive / exclusive usage
<b>Magnets</b>													
Xerox® DocuMagnet Matt 1 card/sheet	Heavyweight 3 (221-257)		165 gsm	003R96072	A4							S	1) Load MSI / Bypass Tray 5 in LEF (Long Edge Feed) orientation with cards on trailing edge 2) No more than 75 sheets should be loaded in feed tray at one time 3) Select Face-Up Delivery to the Offset Catch Tray 4) Stack no more than 75 sheets in OCT 5) Not intended for extensive / exclusive usage
<b>Synthetics</b>													
Xerox® Premium NeverTear 95µm	Coated 1 (106-128)	Coated 1A	122 gsm	003R98056	A4							S	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static 4) Not intended for extensive / exclusive usage
Xerox® Premium NeverTear 120µm	Coated 1 (151-176)	Coated 1B	167 gsm	003R98058	A4							M	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static 4) Not intended for extensive / exclusive usage
Xerox® Premium NeverTear Gloss White Label Permanent Adhesive	Heavyweight Label 1 (177-220)		217 gsm	007R92031	A4							S	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static 4) Not intended for extensive / exclusive usage
Xerox® Premium NeverTear Matt White Label Permanent Adhesive	Heavyweight Label 1 (177-220)		220 gsm	007R92024	A4							S	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static in the card 4) Not intended for extensive / exclusive usage
Xerox® Premium NeverTear Clear Label Low Tack Adhesive	Heavyweight XHW Label (221-256)		225 gsm	007R92052	A4							S	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static 4) Not intended for extensive / exclusive usage
Xerox® Premium NeverTear Matt Clear (Frosted) Label Permanent Adhesive	Heavyweight Label 1 (177-220)		223 gsm	007R92045	A4							S	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static 4) Not intended for extensive / exclusive usage
Xerox® Premium NeverTear Glass Clear Label Permanent Adhesive	Heavyweight Label 1 (177-220)		219 gsm	007R92038	A4							S	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static 4) Not intended for extensive / exclusive usage