

# Recommended Materials for Phaser 790

For use in the USA and Canada

Revision 1.6, Publish Date: Sept. 27th, 2002

Last Revision 1.5 was published on July 3rd, 2002

For the most recent version of this quarterly published document, visit [www.xdss.com](http://www.xdss.com), select "Free Downloads", then "Color".

## Important Note:

Media recommendations made in this publication are based on qualification tests\* conducted using standard test images with moderate to heavy image area coverage. Test duration for each product/media type is based on the suggested machine monthly copy/print volume. Test machines are maintained within specifications defined by user documentation.

\* Testing Environment temperature range of 60-75 deg. F, Relative Humidity range 20-40%.

Machine reliability specifications may be affected by increased usage of Thick Paper mode. In addition, variances in machine reliability may occur due to extended use of some media types. Your Xerox Sales or Service representative can advise you on using Thick Paper mode or special application media types for long duration copy/print runs.

For specifications and a description of the various media types discussed in this publication, please refer to the Color Material Usage Guide (reorder number 701P34322) that comes with your equipment.

© 2001 Xerox Corporation. All rights reserved.

Xerox®, The Document Company®, the stylized X®, and all Xerox product names and product names and product numbers mentioned in this publication are trademarks of Xerox Corporation. Other company trademarks are also acknowledged.

**Recommended Material List (US and Canada)**

For the most recent version of this document, visit [www.xdss.com/](http://www.xdss.com/) select "Free Downloads", then "Color".

Internal Trays: Plain Paper Mode ( 64-105 gsm)				<b>Phaser 790</b>					<b>A= Auto M=Manual Duplex S=Simplex PCW=Post Consumer Waste ECF=Elemental Chlorine Free</b>
Bypass Tray: Plain Paper Mode (64-105gsm)		Cover Mode (106-220gsm)							
Media	Mode	Weight	Re-Order #	Type	Size	Internal	Bypass	Additional Information	
Xerox Digital Color Xpressions +	Plain	90 gsm / 24lb	3R11380		8.5 x 11	A	M		
			3R11382		8.5 x 14	A	M		
			3R11383		17 x 11	A	M		
	Cover	105 gsm/ 28 lb	3R11385		8.5 x 11	A	M		
			3R11386		17 x 11	A	M		
			3R11387		8.5 x 11		M		
	Cover	120gsm/ 32 lb	3R11388		17 x 11		M		
			3R11389		12 x 18		M		
Xerox Digital Color Xpressions 98' (Ultra White)	Plain	105gsm/ 28lb	3R5529		8.5 x 11	A	M	PCW=30%	
			3R5530		17 x 11	A	M		
			3R5531		18 x 12		M		
	Cover	216gsm/ 80lb	3R5537		8.5 x 11		M		
			3R5538		17 x 11		M		
			3R5539		18 x 12		M		
Xerox Digital Color Silk Coated Text and Cover	Coated	120 gsm/ 80 lb	3R11354		8.5 x 11		S	ECF	
			3R11355		17 x 11		S		
			3R11356		18 x 12		S		
	Coated	140 gsm/ 100 lb	3R11360		8.5 x 11		S	ECF	
			3R11361		17 x 11		S		
			3R11362		18 x 12		S		
	Cover	210gsm/ 80 lb	3R11357		8.5 x 11		S	Manual Duplex with Short End Feed must be run in Cover Dup Mode. ECF	
			3R11358		17 x 11		S		
			3R11359		18 x 12		S		

**Recommended Material List (US and Canada)**

For the most recent version of this document, visit [www.xdss.com/](http://www.xdss.com/) select "Free Downloads", then "Color".

Internal Trays: Plain Paper Mode ( 64-105 gsm)				<b>Phaser 790</b>					<b>A= Auto M=Manual Duplex S=Simplex PCW=Post Consumer Waste ECF=Elemental Chlorine Free</b>
Bypass Tray: Plain Paper Mode (64-105gsm)		Cover Mode (106-220gsm)					Internal	Bypass	
Media	Mode	Weight	Re-Order #	Type	Size	Internal	Bypass		
Xerox Digital Color Gloss Coated Text and Cover	Gloss	120 gsm/ 80 lb	3R11330		8.5 x 11		S	ECF	
			3R11331		17 x 11		S		
			3R11332		18 x 12		S		
	Gloss	140 gsm/ 100 lb	3R11336		8.5 x 11		S	ECF	
			3R11337		17 x 11		S		
			3R11338		18 x 12		S		
	Cover	210gsm/ 80 lb	3R11333		8.5 x 11		S	ECF	
			3R11334		17 x 11		S		
			3R11335		18 x 12		S		
Xerox Super Gloss Coated Cover	Glossy Mode	10 pt / 210 gsm	3R6293		8.5 x 11		S	ECF	
			3R6294		17 x 11		S		
Xerox Digital Color Transparency	Transparency Mode		3R12172		8.5 x 11		S	PCW=25%	

**WARRANTY DISCLAIMER**

Xerox makes no guarantees or warranties, either express or implied, concerning the performance, use or replacement of non-Xerox branded media or throughput products. Customers should inquire directly of their paper distributor or manufacturer for any guarantees they may offer. When purchasing a particular media product for the first time, customers are advised to purchase small quantities to insure that their expectations are met.

The quality of Xerox supplies is consistent from ream to ream, carton to carton, and it is backed by a Xerox 100% guarantee. The quality of non-Xerox branded paper may vary from ream to ream or carton to carton, so for optimum performance on Xerox color equipment, use only the best--Xerox Supplies.

© 2001 Xerox Corporation. All rights reserved.

Xerox®, The Document Company®, the stylized X®, and all Xerox product names and product names and product numbers mentioned in this publication are trademarks of Xerox Corporation. Other company trademarks are also acknowledged.