

Xerox 550 / 560 / 570 North America Custom Materials List July 2013

The Xerox CUSTOM Media List contains custom media that has been tested on the Xerox 550 / 560 / 570 for image quality and performance. Custom media on this list are digitally optimized, designed and manufactured for performance in Xerox digital printing equipment. Best Practices for Operation are outlined below. Customers should validate the Best Practices for Operation are acceptable for their application.

Any alterations to the product's basic design, including sheet size, must be tested and approved by the Xerox Media & Compatibles Technology Center.

When purchasing a particular media product for the first time, customers are advised to purchase small quantities to insure that expectations are met. CUSTOM media may be ordered through the Xerox Supply Account Manager.

Media	Mode	Quality System	Weight	Re-Order #	Size	Trays 1 - 4				Tray 6		Tray 5 (Bypass)	Additional Information
						1	2	3	4	HCF	OHCF	5	
<div style="display: flex; justify-content: space-between; align-items: center;"> <div style="font-size: small;"> Plain/Recycled (64-105gsm) Heavyweight 1(106-176gsm) Heavyweight 2 (176-220gsm) Heavyweight 3 (221-300gsm) Transparency </div> <div style="font-size: small;"> Coated 1 (106-176gsm) Coated 2 (177-220gsm) Coated 3 (221-300gsm) Label Transfer Paper </div> <div style="font-size: small; color: red;"> CML Xerox 550 / 560 /570 </div> <div style="font-size: small;"> A=Auto Duplex S=Simplex Only M=Manual Duplex PCW=Post Consumer Waste ECF=Elemental Chlorine Free </div> </div>													
ID Cards													
Xerox 1-up Client Card w/ 32# Ledger Carrier	Heavyweight 1 (151 176)	HW1C	120 gsm Carrier; 185 gsm Card	Contact your local Supplies representative	8.5 x 11	A							1) Deletions may occur if imaged near the edges of the card 2) Deliver to the Offset Catch Tray 3) Load Tray 1 LEF (Long Edge Feed) with cards toward the back of the tray (inboard) 4) Not intended for extensive / exclusive usage
Xerox 2-up Client Card w/ 32# Ledger Carrier	Heavyweight 1 (151 176)	HW1C	120 gsm Carrier; 185 gsm Card	Contact your local Supplies representative	8.5 x 11	A							1) Deletions may occur if imaged near the edges of the card 2) Deliver to the Offset Catch Tray 3) Load Tray 1 LEF (Long Edge Feed) with cards toward the back of the tray (inboard) 4) Stacking may be compromised due to static in the card 5) Not intended for extensive / exclusive usage
Xerox 2-up Client Card w/ 90# Index Carrier	Heavyweight 2 (177 220)		160 gsm Carrier; 224 gsm Card	Contact your local Supplies representative	8.5 x 11	A							1) Deletions may occur if imaged near the edges of the card 2) Deliver to the Offset Catch Tray 3) Load Tray 1 LEF (Long Edge Feed) with cards toward the back of the tray (inboard) 4) Stacking may be compromised due to static in the card 5) Not intended for extensive / exclusive usage
Xerox 1-up Client Card w/ 60# Xpressions Carrier	Heavyweight 1 (151 176)	HW1B	161 gsm Carrier; 225 gsm Card	P12101	8.5 x 11							A	1) Deletions may occur if imaged near the edges of the card 2) Deliver to the Offset Catch Tray 3) Load Tray 5 (MSI / Bypass) SEF (Short Edge Feed) with cards on the trailing edge 4) Not intended for extensive / exclusive usage
Xerox 2-up Client Card w/ 60# Xpressions Carrier	Heavyweight 1 (151 176)	HW1B	161 gsm Carrier; 225 gsm Card	P12102	8.5 x 11							A	1) Deletions may occur if imaged near the edges of the card 2) Deliver to the Offset Catch Tray 3) Load Tray 5 (MSI / Bypass) SEF (Short Edge Feed) with cards on the trailing edge 4) Stacking may be compromised due to static in the card 5) Not intended for extensive / exclusive usage
Xerox 1-up Value Peel Card w/ 60# Xpressions Carrier	Heavyweight 2 (177 220)	HW2B	161 gsm Carrier; 301 gsm Card	P13201	8.5 x 11							A	1) Deletions may occur if imaged near the edges of the card 2) Deliver to the Offset Catch Tray 3) Load Tray 5 (MSI / Bypass) LEF (Long Edge Feed) with cards toward back of the machine (inboard) 4) Load / Stack no more than 80 Sheets at-a-time 5) Not intended for extensive / exclusive usage
Xerox 1-up Value Perf Card w/ 60# Xpressions Carrier	Heavyweight 2 (177 220)	HW2B	161 gsm Carrier; 251 gsm Card	P13301	8.5 x 11							A	1) Deletions may occur if imaged near the edges of the card 2) Deliver to the Offset Catch Tray 3) Load Tray 5 (MSI / Bypass) LEF (Long Edge Feed) with cards toward back of the machine (inboard) 4) Load / Stack no more than 80 Sheets at-a-time 5) Not intended for extensive / exclusive usage
Magnets													
Xerox 13 mil Digital Magnet Media	Coated 3 Reload (257 - 300)	Coated 3B	-----	Contact your local Supplies representative	8.5 x 11							S	1) Select Face-Up Delivery to the Offset Catch Tray 2) Sheets must be separated and fed one-at-a-time 3) Load individual sheets into MSI / Bypass Tray in LEF (Long Edge Feed) orientation 4) Not intended for extensive / exclusive usage
Xerox DocuMagnet w/ 60# Xpressions Carrier	Heavyweight 3 (221 - 257)		165 gsm	P12418	8.5 x 11							S	1) Load MSI / Bypass Tray 5 in LEF (Long Edge Feed) orientation with cards on trailing edge 2) No more than 75 sheets should be loaded in feed tray at one time 3) Select Face-Up Delivery to the Offset Catch Tray 4) Stack no more than 75 sheets in OCT 5) Not intended for extensive / exclusive usage
Xerox DocuMagnet w/ 8pt. Gloss Carrier	Coated 3 (221 - 256)		183 gsm	P13402	8.5 x 11							S	1) Load MSI / Bypass Tray 5 in LEF (Long Edge Feed) orientation with cards on trailing edge 2) No more than 75 sheets should be loaded in feed tray at one time 3) Select Face-Up Delivery to the Offset Catch Tray 4) Stack no more than 75 sheets in OCT 5) Not intended for extensive / exclusive usage

The Xerox CUSTOM Media List contains custom media that has been tested on the Xerox 550 / 560 /570 for image quality and performance. Custom media on this list are digitally optimized, designed and manufactured for performance in Xerox digital printing equipment. Best Practices for Operation are outlined below. Customers should validate the Best Practices for Operation are acceptable for their application.

Any alterations to the product's basic design, including sheet size, must be tested and approved by the Xerox Media & Compatibles Technology Center.

When purchasing a particular media product for the first time, customers are advised to purchase small quantities to insure that expectations are met. CUSTOM media may be ordered through the Xerox Supply Account Manager.

Media	Mode	Quality System	Weight	Re-Order #	Size	Trays 1 - 4				Tray 6		Tray 5 (Bypass)	Additional Information
						1	2	3	4	HCF	OHCf	5	
						Plain/Recycled (64-105gsm) Heavyweight 1(106-176gsm) Heavyweight 2 (176-220gsm) Heavyweight 3 (221-300gsm) Transparency Coated 1 (106-176gsm) Coated 2 (177-220gsm) Coated 3 (221-300gsm) Label Transfer Paper CML Xerox 550 / 560 /570 A=Auto Duplex S=Simplex Only M=Manual Duplex PCW=Post Consumer Waste ECF=Elemental Chlorine Free							
Mail													
Xerox All-In-One Mailer	Heavyweight 2 (177-220)		179 gsm	P31102 P31101	8.5 x 14 11x17	A	A					A	1) Deliver to the Offset Catch Tray 2) Load Internal Trays in SEF (Short Edge Feed) orientation 3) Not intended for extensive / exclusive usage
Xerox Z-Fold Pressure Seal	Heavyweight 1 (151-176)	HW1A	107 gsm	Contact your local Supplies representative	8.5 x 11	A	A					A	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load Internal Trays in LEF (Long Edge Feed) orientation 3) Not intended for extensive / exclusive usage
Synthetics													
Xerox 4.5 mil Duradocument Paper	Coated 1 (106-128)	Coated 1A	103 gsm	Contact your local Supplies representative	8.5 x 11	A	A					A	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static in the card 4) Not intended for extensive / exclusive usage
Xerox 7 mil Duradocument Paper	Coated 1 (106-128)	Coated 2A	160 gsm	Contact your local Supplies representative	8.5 x 11	A	A					A	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static in the card 4) Not intended for extensive / exclusive usage
Xerox 10 mil Duradocument Paper	Coated 1 (106-128)	Coated 2B	208 gsm	Contact your local Supplies representative	8.5 x 11	A	A					A	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static in the card 4) Not intended for extensive / exclusive usage
Xerox 3.7 mil Premium Nevertear	Coated 1 (106-128)		122 gsm	3R12414	8.5 x 11							S	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static in the card 4) Not intended for extensive / exclusive usage
Xerox 4.7 mil Premium Nevertear	Coated 1 (151-176)		167 gsm	3R12363	8.5 x 11							M	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static in the card 4) Not intended for extensive / exclusive usage
Xerox Gloss White Polyester Label w/ Permanent Adhesive	Heavyweight Label 1 (177-220)		217 gsm	3R14600	8.5 x 11							S	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static in the card 4) Not intended for extensive / exclusive usage
Xerox Matte White Polyester Label w/ Permanent Adhesive	Heavyweight Label 1 (177-220)		220 gsm	3R14604	8.5 x 11							S	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static in the card 4) Not intended for extensive / exclusive usage
Xerox Gloss Clear Polyester Label w/ Low Tack Adhesive	Heavyweight XHW Label (221-256)		225 gsm	3R14612	8.5 x 11							S	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static in the card 4) Not intended for extensive / exclusive usage
Xerox Frosted Clear Polyester Label w/ Permanent Adhesive	Heavyweight Label 1 (177-220)		223 gsm	3R14616	8.5 x 11							S	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static in the card 4) Not intended for extensive / exclusive usage
Xerox Gloss Clear Polyester Label w/ Permanent Adhesive	Heavyweight Label 1 (177-220)		219 gsm	3R14640	8.5 x 11							S	1) Select Face-Up Delivery to the Offset Catch Tray 2) Load MSI / Bypass Tray in LEF (Long Edge Feed) orientation 3) Stacking may be compromised due to static in the card 4) Not intended for extensive / exclusive usage

The Xerox CUSTOM Media List contains custom media that has been tested on the Xerox 550 / 560 /570 for image quality and performance. Custom media on this list are digitally optimized, designed and manufactured for performance in Xerox digital printing equipment. Best Practices for Operation are outlined below. Customers should validate the Best Practices for Operation are acceptable for their application.

Any alterations to the product's basic design, including sheet size, must be tested and approved by the Xerox Media & Compatibles Technology Center.

When purchasing a particular media product for the first time, customers are advised to purchase small quantities to insure that expectations are met. CUSTOM media may be ordered through the Xerox Supply Account Manager.

Plain/Recycled (64-105gsm)	Coated 1 (106-176gsm)	CML Xerox 550 / 560 /570	A=Auto Duplex S=Simplex Only M=Manual Duplex PCW=Post Consumer Waste ECF=Elemental Chlorine Free
Heavyweight 1(106-176gsm)	Coated 2 (177-220gsm)		
Heavyweight 2 (176-220gsm)	Coated 3 (221-300gsm)		
Heavyweight 3 (221-300gsm)	Label		
Transparency	Transfer Paper		

Media	Mode	Quality System	Weight	Re-Order #	Size	Trays 1 - 4				Tray 6		Tray 5 (Bypass)	Additional Information
						1	2	3	4	HCF	OHCf	5	

Photo

Xerox Everflat (60# Color Xpressions)	Heavyweight 1 (151 176)	HW1C	162 gsm	3R12487	8.5 x 11							M	<ol style="list-style-type: none"> 1. Hinge / Spine should always be run in the trailing edge orientation. 2. Set Output delivery to Face Up orientation. 3. Do not image over the recessed hinge. 4. Deletions may be visible on output imaged in close proximity to the hinge / spine. 5. Carefully fan all sheets before loading into the paper tray. 6. Do not fill the tray beyond the Fill Line. 7. For template and design layout, go to www.xerox.com/supplies
--	----------------------------	------	---------	---------	----------	--	--	--	--	--	--	---	---