

Recommended Media List

Xerox® iGen® 5 Digital Production Press

This Recommended Media List contains Xerox® Paper and Specialty Media that has been extensively tested on the Xerox® iGen® 5 Digital Production Press for image quality and performance by Xerox® at the Xerox® Media Technology Center.

The paper and specialty media on this list are approved by Xerox and recommended for use in all configurations of the Xerox® iGen® 5 Digital Production Press.

All Xerox® Paper and Specialty Media on this list are digitally optimized, designed and manufactured for optimal performance in Xerox digital printing equipment and carry the Domtar 100% Performance Guarantee. Domtar offers a 100% Performance Guarantee for any Xerox® Paper or Specialty Media that is featured on the Recommended Media List for a specific Xerox printer or digital press. This is your assurance that if you are unhappy with the performance of recommended

Xerox® Paper or Specialty Media, Domtar will either take back the unused product and replace it or refund your money – guaranteed.

Domtar Paper Company, LLC. and Domtar Inc., (collectively referred to as “Domtar”), are the exclusive U.S. and Canadian trademark licensees of Xerox® Paper and Specialty Media. Domtar’s and Xerox’s extensive collaborative testing and stringent specifications ensure that we are able to guarantee the performance and consistency of Xerox® Paper and Specialty Media.



Recommended Media List

General Information

Customers should validate that the Best Practices for Operation for the selected Xerox® Paper or Specialty Media are acceptable for their application. When purchasing a particular media product for the first time, customers are advised to purchase small quantities to ensure that expectations are met.

Media observations made in this publication are based on tests conducted using standard images with moderate to heavy image area coverage. Test machines are maintained within specifications defined by user documentation. Where applicable, suggested adjustments and best practices are included to optimize media performance. Note that “size” designation is for sheet dimensions only, and is not used to indicate grain direction.

The Stock Library Montage application can be updated with the most current Recommended Media List by downloading the “Recommended Media List.rml” file from Xerox.com. This file can be found on Xerox.com under the Support and Drivers tab, searching on iGen®. Instructions on how to update the Stock Library Manager media list are included with the file.

To view the most current Recommended Media List, please visit www.xeroxpaperusa.com/resources/recommended-media-list.

Warranty Disclaimer

Domtar and Xerox make no guarantees or warranties, either expressed or implied, concerning the performance, use or replacement of non-Xerox branded media or throughput products. Customers should inquire directly of their paper distributor or manufacturer for any guarantees they may offer. When purchasing a particular media product for the first time, customers are advised to purchase small quantities to insure their expectations are met. The quality of Xerox supplies is consistent from ream to ream and is backed by a 100% guarantee such that if you are unhappy with the performance of recommended Xerox® Paper or Specialty Media, Domtar will either take back the unused product and replace it or refund your money. The quality of non-Xerox branded paper may vary from ream to ream or carton to carton, so for optimum performance on Xerox color equipment, use only the best: Xerox supplies.

To learn more about Xerox® Paper and Specialty Media, please call 1-866-814-2401.

To learn more about the benefits of using Xerox Supplies (toner and ink), please contact your Xerox Supplies Representative at 1.800.822.2200 (U.S.) or 1.800.668.0199 (Canada).

Xerox® iGen® 5 Digital Production Press Guaranteed Media List

Item Number	Paper & Specialty Media Description	Size	gsm	Sides Coated	Coating Type	Type	Sequence	Color	Thickness (microns)	Cleanup	Finish	Notes
Xerox® Vitality™ Index Paper												
3R11747	90 lb. Index	8.5 x 11	163	Uncoated	N/A	Plain	0	White	198	No	Regular	
3R11748	90 lb. Index	17 x 11	163	Uncoated	N/A	Plain	0	White	198	No	Regular	
3R11749	110 lb. Index	8.5 x 11	199	Uncoated	N/A	Plain	0	White	241	No	Regular	
Xerox® Bold™ Digital Printing Paper												
3R11540	24 lb. / 60 lb. Text	8.5 x 11	90	Uncoated	N/A	Plain	0	White	96	No	Regular	
3R11541	8.5 x 11 3HP	8.5 x 11	90	Uncoated	N/A	Plain	0	White	96	No	Regular	
3R11542	24 lb. / 60 lb. Text	8.5 x 14	90	Uncoated	N/A	Plain	0	White	96	No	Regular	
3R11543	24 lb. / 60 lb. Text	11 x 17	90	Uncoated	N/A	Plain	0	White	96	No	Regular	
3R11760	8.5 x 11	8.5 x 11	105	Uncoated	N/A	Plain	0	White	109	No	Regular	
3R11761	28 lb. / 70 lb. Text	8.5 x 11 3HP	105	Uncoated	N/A	Plain	0	White	109	No	Regular	
3R20150	28 lb. / 70 lb. Text	8.5 x 14	105	Uncoated	N/A	Plain	0	White	109	No	Regular	
3R11762	28 lb. / 70 lb. Text	17 x 11	105	Uncoated	N/A	Plain	0	White	109	No	Regular	
3R11763	28 lb. / 70 lb. Text	18 x 12	105	Uncoated	N/A	Plain	0	White	109	No	Regular	
3R11764	32 lb. / 80 lb. Text	8.5 x 11	120	Uncoated	N/A	Plain	0	White	128	No	Regular	
3R11765	32 lb. / 80 lb. Text	17 x 11	120	Uncoated	N/A	Plain	0	White	128	No	Regular	
3R11766	32 lb. / 80 lb. Text	18 x 12	120	Uncoated	N/A	Plain	0	White	128	No	Regular	
3R11767	60 lb. Cover	8.5 x 11	163	Uncoated	N/A	Plain	0	White	170	No	Regular	
3R11768	60 lb. Cover	17 x 11	163	Uncoated	N/A	Plain	0	White	170	No	Regular	
3R11770	80 lb. Cover	8.5 x 11	216	Uncoated	N/A	Plain	0	White	224	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4.
3R11771	80 lb. Cover	17 x 11	216	Uncoated	N/A	Plain	0	White	224	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4.
3R11772	80 lb. Cover	18 x 12	216	Uncoated	N/A	Plain	0	White	224	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4.
3R11774	100 lb. Cover	8.5 x 11	270	Uncoated	N/A	Plain	0	White	273	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4.
3R11775	100 lb. Cover	17 x 11	270	Uncoated	N/A	Plain	0	White	273	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4.
3R11776	100 lb. Cover	18 x 12	270	Uncoated	N/A	Plain	0	White	273	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4.
Xerox® Bold™ Digital Printing Paper, 30% Recycled												
3R20160	28 lb. / 70 lb. Text	8.5 x 11	105	Uncoated	N/A	Plain	0	White	109	No	Regular	
3R20161	28 lb. / 70 lb. Text	17 x 11	105	Uncoated	N/A	Plain	0	White	109	No	Regular	
3R20162	28 lb. / 70 lb. Text	18 x 12	105	Uncoated	N/A	Plain	0	White	109	No	Regular	
3R20163	60 lb. Cover	8.5 x 11	163	Uncoated	N/A	Plain	0	White	170	No	Regular	
3R20164	60 lb. Cover	17 x 11	163	Uncoated	N/A	Plain	0	White	170	No	Regular	
3R20165	60 lb. Cover	18 x 12	163	Uncoated	N/A	Plain	0	White	170	No	Regular	
3R20166	80 lb. Cover	8.5 x 11	216	Uncoated	N/A	Plain	0	White	224	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4.
3R20167	80 lb. Cover	17 x 11	216	Uncoated	N/A	Plain	0	White	224	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4.
3R20168	80 lb. Cover	18 x 12	216	Uncoated	N/A	Plain	0	White	224	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4.
3R20169	100 lb. Cover	8.5 x 11	270	Uncoated	N/A	Plain	0	White	273	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4.
3R20170	100 lb. Cover	17 x 11	270	Uncoated	N/A	Plain	0	White	273	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4.
3R20171	100 lb. Cover	18 x 12	270	Uncoated	N/A	Plain	0	White	273	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4.
Xerox® Bold™ Digital Printing Paper, 100% Recycled												
3R11815	28 lb. / 70 lb. Text	8.5 x 11	105	Uncoated	N/A	Plain	0	White	112	No	Regular	
Xerox® Bold™ Coated Gloss Digital Printing Paper												
3R11450	80 lb. Text	8.5 x 11	120	C2S	Gloss	Plain	0	White	102	Yes	Smooth	
3R11451	80 lb. Text	17 x 11	120	C2S	Gloss	Plain	0	White	102	Yes	Smooth	
3R11452	80 lb. Text	18 x 12	120	C2S	Gloss	Plain	0	White	102	Yes	Smooth	
3R11443	80 lb. Text	19 x 13	121	C2S	Gloss	Plain	0	White	102	Yes	Smooth	

Xerox® iGen® 5 Digital Production Press Guaranteed Media List

3R11454	100 lb. Text	8.5 x 11	144	C2S	Gloss	Plain	0	White	122	Yes	Smooth
3R11455	100 lb. Text	17 x 11	144	C2S	Gloss	Plain	0	White	122	Yes	Smooth
3R11456	100 lb. Text	18 x 12	144	C2S	Gloss	Plain	0	White	122	Yes	Smooth
3R11444	100 lb. Text	19 x 13	144	C2S	Gloss	Plain	0	White	122	Yes	Smooth
3R11457	100 lb. Text	20.5 x 14.33	144	C2S	Gloss	Plain	0	White	122	Yes	Smooth
3R11458	80 lb. Cover	8.5 x 11	210	C2S	Gloss	Plain	0	White	183	Yes	Smooth
3R11459	80 lb. Cover	17 x 11	210	C2S	Gloss	Plain	0	White	183	Yes	Smooth
3R11460	80 lb. Cover	18 x 12	210	C2S	Gloss	Plain	0	White	183	Yes	Smooth
3R11445	80 lb. Cover	19 x 13	210	C2S	Gloss	Plain	0	White	183	Yes	Smooth
3R11461	80 lb. Cover	20.5 x 14.33	210	C2S	Gloss	Plain	0	White	183	Yes	Smooth
3R11462	100 lb. Cover	8.5 x 11	280	C2S	Gloss	Plain	0	White	244	Yes	Smooth
3R11463	100 lb. Cover	17 x 11	280	C2S	Gloss	Plain	0	White	244	Yes	Smooth
3R11464	100 lb. Cover	18 x 12	280	C2S	Gloss	Plain	0	White	244	Yes	Smooth
3R11446	100 lb. Cover	19 x 13	280	C2S	Gloss	Plain	0	White	244	Yes	Smooth
3R11465	100 lb. Cover	20.5 x 14.33	280	C2S	Gloss	Plain	0	White	244	Yes	Smooth
3R11307	100 lb. Cover	26 x 14.33	280	C2S	Gloss	Plain	0	White	244	Yes	Smooth
3R11466	110 lb. Cover	8.5 x 11	300	C2S	Gloss	Plain	0	White	264	Yes	Smooth
3R11467	110 lb. Cover	17 x 11	300	C2S	Gloss	Plain	0	White	264	Yes	Smooth
3R11468	110 lb. Cover	18 x 12	300	C2S	Gloss	Plain	0	White	264	Yes	Smooth
3R11448	130 lb. Cover	18 x 12	350	C2S	Gloss	Plain	0	White	315	Yes	Smooth
Xerox® Bold™ Coated Satin Digital Printing Paper											
3R11470	80 lb. Text	8.5 x 11	120	C2S	Semi-Gloss	Plain	0	White	102	Yes	Smooth
3R11471	80 lb. Text	17 x 11	120	C2S	Semi-Gloss	Plain	0	White	102	Yes	Smooth
3R11472	80 lb. Text	18 x 12	120	C2S	Semi-Gloss	Plain	0	White	102	Yes	Smooth
3R11496	80 lb. Text	19 x 13	120	C2S	Semi-Gloss	Plain	0	White	102	Yes	Smooth
3R11474	100 lb. Text	8.5 x 11	144	C2S	Semi-Gloss	Plain	0	White	119	Yes	Smooth
3R11475	100 lb. Text	17 x 11	144	C2S	Semi-Gloss	Plain	0	White	119	Yes	Smooth
3R11476	100 lb. Text	18 x 12	144	C2S	Semi-Gloss	Plain	0	White	119	Yes	Smooth
3R11497	100 lb. Text	19 x 13	144	C2S	Semi-Gloss	Plain	0	White	119	Yes	Smooth
3R11477	100 lb. Text	20.5 x 14.33	144	C2S	Semi-Gloss	Plain	0	White	119	Yes	Smooth
3R11478	80 lb. Cover	8.5 x 11	210	C2S	Semi-Gloss	Plain	0	White	191	Yes	Smooth
3R11479	80 lb. Cover	17 x 11	210	C2S	Semi-Gloss	Plain	0	White	191	Yes	Smooth
3R11480	80 lb. Cover	18 x 12	210	C2S	Semi-Gloss	Plain	0	White	191	Yes	Smooth
3R11518	80 lb. Cover	19 x 13	210	C2S	Semi-Gloss	Plain	0	White	191	Yes	Smooth
3R11481	80 lb. Cover	20.5 x 14.33	210	C2S	Semi-Gloss	Plain	0	White	191	Yes	Smooth
3R11482	100 lb. Cover	8.5 x 11	280	C2S	Semi-Gloss	Plain	0	White	251	Yes	Smooth
3R11463	100 lb. Cover	17 x 11	280	C2S	Semi-Gloss	Plain	0	White	251	Yes	Smooth
3R11484	100 lb. Cover	18 x 12	280	C2S	Semi-Gloss	Plain	0	White	251	Yes	Smooth
3R11519	100 lb. Cover	19 x 13	280	C2S	Semi-Gloss	Plain	0	White	251	Yes	Smooth
3R11485	100 lb. Cover	20.5 x 14.33	280	C2S	Semi-Gloss	Plain	0	White	251	Yes	Smooth
3R11312	100 lb. Cover	26 x 14.33	280	C2S	Semi-Gloss	Plain	0	White	251	Yes	Smooth
3R11486	110 lb. Cover	8.5 x 11	300	C2S	Semi-Gloss	Plain	0	White	277	Yes	Smooth
3R11487	110 lb. Cover	17 x 11	300	C2S	Semi-Gloss	Plain	0	White	277	Yes	Smooth
3R11488	110 lb. Cover	18 x 12	300	C2S	Semi-Gloss	Plain	0	White	277	Yes	Smooth
3R11495	130 lb. Cover	18 x 12	350	C2S	Semi-Gloss	Plain	0	White	353	Yes	Smooth
Xerox® Bold™ Super Gloss Cover											
3R11680	8 Point	8.5 x 11	170	C1S	High-Gloss	Plain	0	White	203	Yes	Smooth
3R11681	8 Point	17 x 11	170	C1S	High-Gloss	Plain	0	White	203	Yes	Smooth
3R11682	8 Point	18 x 12	170	C1S	High-Gloss	Plain	0	White	203	Yes	Smooth
3R11683	10 Point	8.5 x 11	219	C1S	High-Gloss	Plain	0	White	254	Yes	Smooth
3R11684	10 Point	17 x 11	219	C1S	High-Gloss	Plain	0	White	254	Yes	Smooth
3R11685	10 Point	18 x 12	219	C1S	High-Gloss	Plain	0	White	254	Yes	Smooth
3R11686	12 Point	8.5 x 11	247	C1S	High-Gloss	Plain	0	White	305	Yes	Smooth
3R11687	12 Point	17 x 11	247	C1S	High-Gloss	Plain	0	White	305	Yes	Smooth
3R11688	12 Point	18 x 12	247	C1S	High-Gloss	Plain	0	White	305	Yes	Smooth
Xerox® Revolution NeverTear™											
3R20172	5 mil	8.5 x 11	135	C2S	Matte	Plain	0	White	127	Yes	Smooth
3R20173	5 mil	8.5 x 11 3HP	135	C2S	Matte	Plain	0	White	127	Yes	Smooth

Static build up may affect media runnability and/or stacking.
 Static build up may affect media runnability and/or stacking.

Xerox® iGen® 5 Digital Production Press Guaranteed Media List

Media ID	Media Description	Dimensions	Weight	Area	Coating	Finish	Color	Yield	Notes
3R20174	5 mil	11 x 17	135	C2S	Gloss	Plain	White	127	Static build up may affect media runnability and/or stacking.
3R20175	5 mil	12 x 18	135	C2S	Matte	Plain	White	127	Static build up may affect media runnability and/or stacking.
3R20176	8 mil	8.5 x 11	230	C2S	Matte	Plain	White	203	Static build up may affect media runnability and/or stacking.
3R20177	8 mil	12 x 18	230	C2S	Matte	Plain	White	203	Static build up may affect media runnability and/or stacking.
3R20178	8 mil	14.33 x 20.5	230	C2S	Matte	Plain	White	203	Static build up may affect media runnability and/or stacking.
3R20179	10 mil	8.5 x 11	300	C2S	Matte	Plain	White	254	Static build up may affect media runnability and/or stacking.
3R20180	10 mil	12 x 18	300	C2S	Matte	Plain	White	254	Static build up may affect media runnability and/or stacking.
3R20181	10 mil	14.33 x 20.5	300	C2S	Matte	Plain	White	254	Static build up may affect media runnability and/or stacking.
3R20182	14 mil	8.5 x 11	450	C2S	Matte	Plain	White	356	Static build up may affect media runnability and/or stacking.
3R20183	14 mil	12 x 18	450	C2S	Matte	Plain	White	256	Static build up may affect media runnability and/or stacking.
3R20184	14 mil	14.33 x 20.5	450	C2S	Matte	Plain	White	256	Static build up may affect media runnability and/or stacking.
3R20185	8 mil Pre-Scored Horizontal	8.5 x 11	230	C2S	Matte	Plain	White	127	Static build up may affect media runnability and/or stacking.
3R20186	8 mil Pre-Scored Vertical	8.5 x 11	230	C2S	Matte	Plain	White	127	Static build up may affect media runnability and/or stacking.
3R20187	8 mil Pre-Perforated Shelf Tags	8.5 x 11	230	C2S	Matte	Plain	White	127	Static build up may affect media runnability and/or stacking.
3R20188	8 mil Pre-Perforated Door Hangers	8.5 x 11	230	C2S	Matte	Plain	White	127	Static build up may affect media runnability and/or stacking.
3R20189	8 mil Pre-Perforated Luggage Tags	8.5 x 11	230	C2S	Matte	Plain	White	127	Static build up may affect media runnability and/or stacking.
3R20190	8 mil Pre-Perforated Badges	8.5 x 11	230	C2S	Matte	Plain	White	127	Static build up may affect media runnability and/or stacking.
3R20191	8 mil Pre-Perforated ID Cards	8.5 x 11	230	C2S	Matte	Plain	White	127	Static build up may affect media runnability and/or stacking.
3R20192	8 mil Pre-Perforated Parking Passes	8.5 x 11	230	C2S	Matte	Plain	White	127	Static build up may affect media runnability and/or stacking.
3R20193	8 mil Pre-Perforated Portrait Badges	8.5 x 11	230	C2S	Matte	Plain	White	127	Static build up may affect media runnability and/or stacking.
Xerox® Revolution™ ID Cards									
3R20077	2-Side Laminated with Perf-Out, 1-Up	8.5 x 11	163	C2S (Card Area)	Gloss	Plain	White	170	If transfer set point adjustments are required for snow detects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4. Stack quality and stack height may be affected due to media structure or high area coverage. For uniform image quality do not image within 5 mm of card edge. Load and stack 50-100 sheets maximum due to media structure. TAB may need to be cleaned prior to running media. An Enabler Kit is available to facilitate loading and stacking of greater volumes.
3R20078	2-Side Laminated with Perf-Out, 2-Up	8.5 x 11	163	C2S (Card Area)	Gloss	Plain	White	170	If transfer set point adjustments are required for snow detects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4. Stack quality and stack height may be affected due to media structure or high area coverage. For uniform image quality do not image within 5 mm of card edge. Load and stack 50-100 sheets maximum due to media structure. TAB may need to be cleaned prior to running media. An Enabler Kit is available to facilitate loading and stacking of greater volumes.
3R14733	1-Side Laminated with Peel-Off, 1-Up	8.5 x 11	163	C1S (Card Area)	Gloss	Plain	White	170	For uniform image quality do not image within 5 mm of card edge. Load and stack 50-100 sheets maximum due to media structure. TAB may need to be cleaned prior to running media. An Enabler Kit is available to facilitate loading and stacking of greater volumes.
3R14734	1-Side Laminated with Peel-Off, 2-Up	8.5 x 11	163	C1S (Card Area)	Gloss	Plain	White	170	For uniform image quality do not image within 5 mm of card edge. Load and stack 50-100 sheets maximum due to media structure. TAB may need to be cleaned prior to running media.
3R14735	1-Side Laminated with Microperforation, 1-Up	8.5 x 11	163	C1S (Card Area)	Gloss	Plain	White	170	For uniform image quality do not image within 5 mm of card edge. Load and stack 50-100 sheets maximum due to media structure. TAB may need to be cleaned prior to running media.
3R14736	1-Side Laminated with Microperforation, 2-Up	8.5 x 11	163	C1S (Card Area)	Gloss	Plain	White	170	For uniform image quality do not image within 5 mm of card edge. Load and stack 50-100 sheets maximum due to media structure. TAB may need to be cleaned prior to running media.
3R14700	7 mil Synthetic with Microperforation, 1-Up	8.5 x 11	216	Uncoated	N/A	Plain	White	194	For uniform image quality do not image within 5 mm of card edge. Load and stack 50-100 sheets maximum due to media structure. TAB may need to be cleaned prior to running media.
3R14701	7 mil Synthetic with Microperforation, 2-Up	8.5 x 11	216	Uncoated	N/A	Plain	White	194	For uniform image quality do not image within 5 mm of card edge. Load and stack 50-100 sheets maximum due to media structure. TAB may need to be cleaned prior to running media.

Xerox® iGen® 5 Digital Production Press Guaranteed Media List

3R14714	7 mil Synthetic with Peel-Off, 1-Up	8.5 x 11	200	Uncoated	N/A	Plain	0	White	170	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4. Stack quality and stack height may be affected due to media structure or high area coverage. For uniform image quality do not image within 5 mm of card edge. TAB may need to be cleaned prior to running media. A DocuCard Enabler Kit is available to facilitate feeding and stacking of greater volumes. For feeding without an Enabler Kit feed tray load max is 50-100 sheets. Load card inboard for Long Edge Feed and trail edge for Short Edge Feed.
3R14716	7 mil Synthetic with Peel-Off, 2-Up	8.5 x 11	200	Uncoated	N/A	Plain	0	White	170	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4. Stack quality and stack height may be affected due to media structure or high area coverage. For uniform image quality do not image within 5 mm of card edge. TAB may need to be cleaned prior to running media. A DocuCard Enabler Kit is available to facilitate feeding and stacking of greater volumes. For feeding without an Enabler Kit feed tray load max is 50-100 sheets. Load card inboard for Long Edge Feed and trail edge for Short Edge Feed.
Xerox® Revolution™ Carbonless – Premium Digital												
3R12420	2-Part Straight/Reverse	8.5 x 11	80	Uncoated	N/A	Ordered	2	White/Canary	110	Yes	Regular	This media may have a mottled appearance due to paper formation (image density and gloss). Optimization of decurler settings may be needed for best stacking and runnability. Fuser Fluid II is recommended for duplex applications. Reverse PreCollated product run face up to stacker is recommended.
3R12422	2-Part Straight/Reverse	8.5 x 14	80	Uncoated	N/A	Ordered	2	White/Canary	110	Yes	Regular	This media may have a mottled appearance due to paper formation (image density and gloss). Optimization of decurler settings may be needed for best stacking and runnability. Fuser Fluid II is recommended for duplex applications. Reverse PreCollated product run face up to stacker is recommended.
3R12423	2-Part Straight/Reverse	11 x 17	80	Uncoated	N/A	Ordered	2	White/Canary	110	Yes	Regular	This media may have a mottled appearance due to paper formation (image density and gloss). Optimization of decurler settings may be needed for best stacking and runnability. Fuser Fluid II is recommended for duplex applications. Reverse PreCollated product run face up to stacker is recommended.
3R12421	2-Part Straight/Reverse	8.5 x 11	80	Uncoated	N/A	Ordered	2	White/Pink	110	Yes	Regular	This media may have a mottled appearance due to paper formation (image density and gloss). Optimization of decurler settings may be needed for best stacking and runnability. Fuser Fluid II is recommended for duplex applications. Reverse PreCollated product run face up to stacker is recommended.
3R12424	3-Part Reverse	8.5 x 11	80	Uncoated	N/A	Ordered	3	Pink/Canary/White	110	Yes	Regular	This media may have a mottled appearance due to paper formation (image density and gloss). Optimization of decurler settings may be needed for best stacking and runnability. Fuser Fluid II is recommended for duplex applications. Reverse PreCollated product run face up to stacker is recommended.
3R12425	3-Part Straight	8.5 x 11	80	Uncoated	N/A	Ordered	3	White/Canary/Pink	110	Yes	Regular	This media may have a mottled appearance due to paper formation (image density and gloss). Optimization of decurler settings may be needed for best stacking and runnability. Fuser Fluid II is recommended for duplex applications. Reverse PreCollated product run face up to stacker is recommended.
3R12427	3-Part Straight	8.5 x 14	80	Uncoated	N/A	Ordered	3	White/Canary/Pink	110	Yes	Regular	This media may have a mottled appearance due to paper formation (image density and gloss). Optimization of decurler settings may be needed for best stacking and runnability. Fuser Fluid II is recommended for duplex applications. Reverse PreCollated product run face up to stacker is recommended.
3R12426	3-Part Straight (Mini Carton)	8.5 x 11	80	Uncoated	N/A	Ordered	3	White/Canary/Pink	110	Yes	Regular	This media may have a mottled appearance due to paper formation (image density and gloss). Optimization of decurler settings may be needed for best stacking and runnability. Fuser Fluid II is recommended for duplex applications. Reverse PreCollated product run face up to stacker is recommended.
3R12429	4-Part Reverse	8.5 x 11	80	Uncoated	N/A	Ordered	4	Goldend/Pink/Canary/White	110	Yes	Regular	This media may have a mottled appearance due to paper formation (image density and gloss). Optimization of decurler settings may be needed for best stacking and runnability. Fuser Fluid II is recommended for duplex applications. Reverse PreCollated product run face up to stacker is recommended.

Xerox® iGen® 5 Digital Production Press Guaranteed Media List

3R12430	4-Part Straight	8.5 x 11	80	Uncoated	N/A	Ordered	4	White/Canary/Pink/ Goldentrod	110	Yes	Regular	This media may have a mottled appearance due to paper formation (image density and gloss). Optimization of decurler settings may be needed for best stacking and runnability. Fuser Fluid II is recommended for duplex applications. Reverse PreCollated product run face up to stacker is recommended. This media may have a mottled appearance due to paper formation (image density and gloss).
3R12434	Singles CB	8.5 x 11	80	Uncoated	N/A	Plain	0	White	110	Yes	Regular	Optimization of decurler settings may be needed for best stacking and runnability. Fuser Fluid II is recommended for duplex applications. Reverse PreCollated product run face up to stacker is recommended. This media may have a mottled appearance due to paper formation (image density and gloss).
3R12435	Singles CFB	8.5 x 11	80	Uncoated	N/A	Plain	0	White	110	Yes	Regular	Optimization of decurler settings may be needed for best stacking and runnability. Fuser Fluid II is recommended for duplex applications. Reverse PreCollated product run face up to stacker is recommended. This media may have a mottled appearance due to paper formation (image density and gloss).
3R12437	Singles CFB	8.5 x 11	80	Uncoated	N/A	Plain	0	Canary	110	Yes	Regular	Optimization of decurler settings may be needed for best stacking and runnability. Fuser Fluid II is recommended for duplex applications. Reverse PreCollated product run face up to stacker is recommended. This media may have a mottled appearance due to paper formation (image density and gloss).
3R12439	Singles CF	8.5 x 11	80	Uncoated	N/A	Plain	0	Pink	110	Yes	Regular	Optimization of decurler settings may be needed for best stacking and runnability. Fuser Fluid II is recommended for duplex applications. Reverse PreCollated product run face up to stacker is recommended. This media may have a mottled appearance due to paper formation (image density and gloss).
Xerox® Revolution™ Label												
3R05772	1-Up, Die Cut	8.5 x 11	190	C1S	Matte	Plain	0	White	187	No	Smooth	For uniform image quality, do not image within 3 mm of label edges. Simplex only recommended Imaging over die cuts or label edges may adversely affect fuser, roll life.
3R12371	1-Up, Full Sheet	8.5 x 11	190	C1S	Matte	Plain	0	White	187	No	Smooth	For uniform image quality, do not image within 3 mm of label edges. Simplex only recommended Imaging over die cuts or label edges may adversely affect fuser, roll life.
3R05773	4-Up	8.5 x 11	190	C1S	Matte	Plain	0	White	187	No	Smooth	For uniform image quality, do not image within 3 mm of label edges. Simplex only recommended Imaging over die cuts or label edges may adversely affect fuser, roll life.
3R06332	10-Up	8.5 x 11	190	C1S	Matte	Plain	0	White	187	No	Smooth	For uniform image quality, do not image within 3 mm of label edges. Simplex only recommended Imaging over die cuts or label edges may adversely affect fuser, roll life.
3R06333	30-Up	8.5 x 11	190	C1S	Matte	Plain	0	White	187	No	Smooth	For uniform image quality, do not image within 3 mm of label edges. Simplex only recommended Imaging over die cuts or label edges may adversely affect fuser, roll life.
3R06330	2-Up, CD/DVD	8.5 x 11	190	C1S	Matte	Plain	0	White	187	No	Smooth	For uniform image quality, do not image within 3 mm of label edges. Simplex only recommended Imaging over die cuts or label edges may adversely affect fuser, roll life.
3R14626	4 mil Vinyl with Permanent Adhesive	8.5 x 11	274	C1S	Gloss	Plain	0	White	254	No	Smooth	For uniform image quality, do not image within 5 mm of score. For additional image quality tips please contact the media hotline. Imaging over die cuts or label edges may adversely affect fuser, roll life.
3R14627	4 mil Vinyl with Permanent Adhesive	12 x 18	274	C1S	Gloss	Plain	0	White	254	No	Smooth	For uniform image quality, do not image within 5 mm of score. For additional image quality tips please contact the media hotline. Imaging over die cuts or label edges may adversely affect fuser, roll life.
3R14628	4 mil Vinyl with Removable Adhesive	8.5 x 11	274	C1S	Gloss	Plain	0	White	254	No	Smooth	For uniform image quality, do not image within 5 mm of score. For additional image quality tips please contact the media hotline. Imaging over die cuts or label edges may adversely affect fuser, roll life.
3R14629	4 mil Vinyl with Removable Adhesive	12 x 18	274	C1S	Gloss	Plain	0	White	254	No	Smooth	For uniform image quality, do not image within 5 mm of score. For additional image quality tips please contact the media hotline. Imaging over die cuts or label edges may adversely affect fuser, roll life.
Xerox® Revolution™ Mailing Media												
3R12445	Business Reply Envelope	8.5 x 11	160	Uncoated	N/A	Plain	0	White	150	No	Regular	This media may have a mottled appearance due to paper formation (image density and gloss). Stack quality and stack height may be affected due to media structure or high area coverage. Load and stack 200-300 envelopes maximum due to media structure.
Xerox® Revolution™ Tabs -- Plain Paper												
3R20113	90 lb. Index, Single Straight	9 x 11	163	Uncoated	N/A	Pre-Cut Tab	4	White	198	No	Regular	
3R04417	90 lb. Index, Single Straight	9 x 11	163	Uncoated	N/A	Pre-Cut Tab	5	White	198	No	Regular	
3R04418	90 lb. Index, Single Straight	9 x 11 3HP	163	Uncoated	N/A	Pre-Cut Tab	5	White	198	No	Regular	
3R04407	90 lb. Index, Single Position 1 & 5	9 x 11	163	Uncoated	N/A	Pre-Cut Tab	0	White	198	No	Regular	

Xerox® iGen® 5 Digital Production Press Guaranteed Media List

3R04409	90 lb. Index, Single Position 2 & 4	9 x 11	163	Uncoated	N/A	Pre-Cut Tab 0	White	198	No	Regular	
3R04411	90 lb. Index, Single Position 3	9 x 11	163	Uncoated	N/A	Pre-Cut Tab 0	White	198	No	Regular	
3R05422	90 lb. Index, Single Reverse	9 x 11	163	Uncoated	N/A	Pre-Cut Tab 3	White	198	No	Regular	
3R05423	90 lb. Index, Single Reverse	9 x 11 3HP	163	Uncoated	N/A	Pre-Cut Tab 3	White	198	No	Regular	
3R05426	90 lb. Index, Single Reverse	9 x 11	163	Uncoated	N/A	Pre-Cut Tab 4	White	198	No	Regular	
3R05427	90 lb. Index, Single Reverse	9 x 11 3HP	163	Uncoated	N/A	Pre-Cut Tab 4	White	198	No	Regular	
3R04415	90 lb. Index, Single Reverse	9 x 11	163	Uncoated	N/A	Pre-Cut Tab 5	White	198	No	Regular	
3R04416	90 lb. Index, Single Reverse	9 x 11 3HP	163	Uncoated	N/A	Pre-Cut Tab 5	White	198	No	Regular	
3R05713	90 lb. Index, Single Reverse	9 x 11	163	Uncoated	N/A	Pre-Cut Tab 8	White	198	No	Regular	
3R05714	90 lb. Index, Single Reverse	9 x 11 3HP	163	Uncoated	N/A	Pre-Cut Tab 8	White	198	No	Regular	
Xerox® Revolution™ Tabs – Printable Plastic											
3R05709	90 lb. Index, Single Straight	9 x 11	163	Uncoated	N/A	Pre-Cut Tab 5	White	198	No	Regular	
3R05710	90 lb. Index, Single Straight	9 x 11 3HP	163	Uncoated	N/A	Pre-Cut Tab 5	White	198	No	Regular	
3R05520	90 lb. Index, Single Reverse	9 x 11	163	Uncoated	N/A	Pre-Cut Tab 5	White	198	No	Regular	
3R05521	90 lb. Index, Single Reverse	9 x 11 3HP	163	Uncoated	N/A	Pre-Cut Tab 5	White	198	No	Regular	
3R12477	60 lb. Cover, Single Reverse	9 x 11	163	Uncoated	N/A	Pre-Cut Tab 5	White	170	No	Regular	
Xerox® Revolution™ Marketing Media											
3R12407	Presentation Folder, 10 Point	12 x 18	219	C1S	High-Gloss	Plain	White	254	Yes	Smooth	For uniform image quality, do not image within 5 mm of score. Image degradation may be present on uncoated side (side 2).
3R20106	FunFlip®, 3"x3" Size	8.5 x 11	230	Uncoated	N/A	Plain	White	234	Yes	Regular	For uniform image quality, do not image within 3 mm of label edges. Simplex only recommended
3R14742	FunFlip®, Greeting Card Size	8.5 x 11	230	Uncoated	N/A	Plain	White	234	Yes	Regular	For uniform image quality, do not image within 3 mm of label edges. Simplex only recommended
3R20016	Tri-Fold Brochure, 32 lb.	8.5 x 11	120	Uncoated	N/A	Plain	White	120	No	Regular	If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 3.
Various & Custom	14 pt Folding Media with various perffold shapes	Various	256	C1S	High-Gloss	Plain	White	356	Yes	Smooth	For uniform image quality, do not image within 5 mm of score. This media is adversely reactive in dry environments.
Various & Custom	16 pt Folding Media with various perffold shapes	Various	350	C1S	High-Gloss	Plain	White	462	Yes	Smooth	Simplex only recommended
3R12821	Transparency for Color Printing with Paperback	11 x 17	180	C1S	Gloss	Transparency 0	Clear	187	No	Smooth	This media may have a mottled appearance due to paper formation (image density and gloss). Simplex only recommended
Xerox® Revolution™ Magnet Media											
3R14686	17 mil. High-Gloss	12 x 18	350	C1S	High-Gloss	Plain	White	439	No	Smooth	Static build up may affect media runnability and/or stacking. Feed from a lower tray only
3R14731	Integrated Card, 60 lb. Cover	8.5 x 11	280	Uncoated	N/A	Plain	White	170	No	Regular	To enable running Service must set NVM 12509 (Lower Tray Multifeed Detected FLTByP). To maximum value. Output to top tray or bypass tray, if enabled. Skew up to 10 mm may be seen.
3R14732	Integrated Card, 8 pt C1S	8.5 x 11	280	C1S	Gloss	Plain	White	194	No	Smooth	For best image quality, do not image within 40 mm of lead or tail edge of the media. If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4.

For uniform image quality, do not image within 5 mm of score. Image degradation may be present on uncoated side (side 2).
 For uniform image quality, do not image within 3 mm of label edges. Simplex only recommended
 For uniform image quality, do not image within 3 mm of label edges. Simplex only recommended
 If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 3.
 For uniform image quality, do not image within 5 mm of score. This media is adversely reactive in dry environments.
 Simplex only recommended
 This media is adversely reactive in dry environments.
 Simplex only recommended
 This media may have a mottled appearance due to paper formation (image density and gloss).
 Simplex only recommended
 Static build up may affect media runnability and/or stacking.
 Output to top tray only, 80 sheets.
 Do not invert.

Static build up may affect media runnability and/or stacking.
 Feed from a lower tray only
 To enable running Service must set NVM 12509 (Lower Tray Multifeed Detected FLTByP). To maximum value.
 Output to top tray or bypass tray, if enabled.
 Skew up to 10 mm may be seen.
 For best image quality, do not image within 40 mm of lead or tail edge of the media. If Transfer set point adjustments are required for snow defects, refer to the Snow Sample Artifact Procedure in the latest Customer Maintenance Manual Section 4.
 Simplex only recommended
 For uniform image quality, do not image within 5 mm of card edge.
 An Enabler Kit is available to facilitate feeding and stacking of greater volumes.
 Simplex only recommended
 For uniform image quality do not image within 5 mm of card edge.
 An Enabler Kit is available to facilitate feeding and stacking of greater volumes.



Domtar is the exclusive trademark licensee of the Xerox® Paper and Specialty Media Line within the United States and Canada.

Working collaboratively with the Xerox Corporation and our Media Partners, Domtar designs and manufactures the Xerox® Paper and Specialty Media line to bring you the most extensive line of digitally optimized products in the United States and Canada.

With the Domtar Performance Guarantee, you can be assured that if you are unhappy with the performance of the product, you may return the unused portion and Domtar will either replace it, or refund your money.

Xerox® Paper and Specialty Media products are widely available for purchase through office supply dealers, paper merchants, office supply stores, online as well as in selected retail stores.

www.domtar.com
www.xeroxpaperUSA.com
www.xeroxpaper.ca