

Recommended Xerox Media for Phaser 6600 / WorkCentre 6605 (USA and Canada)

For use in the US and Canada

Version 1.0, Publish Date: September 2012

Important Notes:

All media is listed by product, machine run mode, weight (standard gsm), re-order number, size, and tray runability. The additional information column is for hints and tips on how to run certain media applications.

Media recommendations made in this publication are based on qualification tests* conducted using standard test images with moderate to heavy image area coverage. Test duration for each product/media type is based on the suggested machine monthly copy/print volume. Test machines are maintained within specifications defined by user documentation.

* Testing Environment temperature range of 60-75 deg. F, Relative Humidity range 20-40%.

*Machine reliability specifications may be affected by increased usage of the Transparency, Card Stock, Label, and Special modes. In addition, variances in machine reliability may occur due to extended use of some media types. Your Xerox service representative can advise you on special application media types for long duration copy/print runs.

For specifications and a description of the various media types discussed in this publication, please refer to www.Xerox.com.

For additional recommended Phaser media, look under Supplies on: <http://www.office.xerox.com/> and select your Product Family.

© 2011 Xerox Corporation. All rights reserved.

XEROX®, the sphere of connectivity, and all Xerox product names and product numbers mentioned in this publication are trademarks of Xerox Corporation. Other company trademarks are also acknowledged.



Phaser 6600 / WorkCentre 6605
Recommended Media List
North America
September 2012 V1.0



Plain (60 - 105 gsm)	Lightweight Glossy Cardstock (106 - 163 gsm)	Lightweight Cardstock (106 - 163 gsm)
	Heavyweight Glossy Cardstock (164 - 216 gsm)	Heavyweight Cardstock (164 - 216 gsm)
		Labels

Trays	
A = Auto Duplex	S = Simplex Only
M = Manual Duplex	n = not supported
Bypass Tray	Tray 1 and 2

Media	Paper Type Setting	Weight	Re-Order #	Type	Size	Bypass Tray	Tray 1 and 2	Additional Information
Xerox Business 4200	Plain	75 gsm / 20 lb	3R2047		8.5 x 11	A	A	
			3R2641 (3-hole)		8.5 x 11	A		
			3R2051		8.5 x 14	A		
		90 gsm / 24lb	3R2531		8.5 x 11	A		
		105 gsm / 28 lb	3R2353		8.5 x 11	A	A	
Xerox Business Recycled Paper	Plain	75 gsm / 20 lb	3R6296	Recycled	8.5 x 11	A	A	
			3R6297 (3-hole)		8.5 x 11	A	A	
			3R6298		8.5 x 14	A	A	
Xerox Color Xpressions Select	Plain	90 gsm / 24 lb	3R11540		8.5 x 11	A	A	
			3R11541 (3-hole)		8.5 x 11	A	A	
			3R11542		8.5 x 14	A	A	
Xerox Color Xpressions Elite	Plain	105 gsm / 28 lb	3R11760		8.5 x 11	A	A	
			3R11761 (3-hole)		8.5 x 11	A	A	
	Lightweight Cardstock	120 gsm / 32 lb	3R11764		8.5 x 11	A	A	
	Lightweight Cardstock	163 gsm / 60 lb cvr	3R11767		8.5 x 11	A	A	
	Heavyweight Cardstock	216 gsm / 80 lb cvr	3R11770		8.5 x 11	S	S	
Xerox Digital Color Elite Gloss Text and Cover (C2S)	Lightweight Glossy Cardstock	120 gsm / 80 lb txt	3R11450	Gloss Text	8.5 x 11	A	A	
	Lightweight Glossy Cardstock	140 gsm / 100 lb txt	3R11454	Gloss Text	8.5 x 11	A	A	
	Heavyweight Glossy Cardstock	210 gsm / 80 lb cvr	3R11458	Gloss Cover	8.5 x 11	S	S	
Xerox Digital Color Elite Silk Text and Cover (C2S)	Lightweight Glossy Cardstock	120 gsm / 80 lb txt	3R11470	Silk Text	8.5 x 11	A	A	
	Lightweight Glossy Cardstock	140 gsm / 100 lb txt	3R11474	Silk Text	8.5 x 11	A	A	
	Heavyweight Glossy Cardstock	210 gsm / 80 lb cvr	3R11478	Silk Cover	8.5 x 11	S	S	
Plain Paper Labels	Labels		3R12050	33 up	8.5 x 11	S	n	

Gloss variation can occur from machine rolls on high coverage, solid fill prints; if so, adjust the fuser temperature, reduce coverage, or try a different paper. Tray 1 or Tray 2 may reduce jam issues or improve pick performance seen with the bypass tray. High humidity may cause misfeeds or multifeeds.