

# Recommended Xerox Media for Phaser 7800

For use in the US and Canada

Publish Date: May, 2012

## Important Notes:

All media are listed by product, paper type, paper settings, weight (standard gsm), re-order number, size, and tray runability. The additional information column is for hints and tips on how to run certain media applications.

Media recommendations made in this publication are based on qualification tests\* conducted using standard test images with moderate to heavy image area coverage. Test duration for each product/media type is based on the suggested machine monthly copy/print volume. Test machines are maintained within specifications defined by user documentation.

\*Testing Environment temperature range of 60-75 deg. F, Relative Humidity range 30-50%. For those customers operating equipment in environments of extremely low or high humidity - not all products on this list have been validated under these conditions.

\*Machine reliability specifications may be affected by increased usage of Card stocks, Glossy papers, and other special modes. In addition, variances in machine reliability may occur due to extended use of some media types. Your Xerox service representative can advise you on special application media types for long duration copy/print runs.

For specifications and a description of the various media types discussed in this publication, please refer to [www.xerox.com](http://www.xerox.com).

© 2009 Xerox Corporation. All rights reserved.

XEROX®, the sphere of connectivity, and all Xerox product names and product numbers mentioned in this publication are trademarks of Xerox Corporation. Other company trademarks are also acknowledged.





